

# BULLDOG® & HEPA-AIRE®

## Negative Air Machines

### Performance & Specifications

	BD2KM	BD2KMA	H2KM	H2KMA
<b>Net Weight W/Filters</b>	117 lbs.	117 lbs.	124 lbs	124 lbs
<b>Dimensions</b> Length Width Height	39.5 in 28.5 in 31.625 in	39.5 in 28.5 in 31.625 in	35.75 in 26 in 30.25 in	35.75 in 26 in 30.25 in
<b>Operating Speeds</b>	2	2	2	2
<b>Peak Rated Airflow</b>	2,000 (H) 1,300 (L)	2,000 (H) 1,300 (L)	2,000 (H) 1,300 (L)	2,000 (H) 1,300 (L)
<b>Cabinet Material</b>	UL94HB flame retardant resin	UL94HB flame retardant resin	Galvanized Steel	Galvanized Steel
<b>Construction</b>	Rotational Molding	Rotational Molding	Solid Rivets	Solid Rivets
<b>Exhaust Collar Diameter</b>	12"	12"	12"	12"
<b>Carrying Handles</b>	Yes (4)	Yes (4)	Yes (2)	Yes (2)
<b>Casters</b> (2 Fixed, 2 Locking Swivel)	Yes (4" dia.)	Yes (4" dia.)	Yes (4" dia.)	Yes (4" dia.)
<b>Recessed Controls</b>	Yes	Yes	Yes	Yes
<b>Blower Type</b>	Squirrel Cage	Squirrel Cage	Squirrel Cage	Squirrel Cage
<b>Motor Output</b>	1.0 HP	1.0 HP	1.0 HP	1.0 HP
<b>Circuit Requirements</b>	120V/60Hz /15A	120V/60Hz /15A	120V/60Hz/15A	120V/60Hz/15A
<b>Operating Amp Draw</b>	< 10.0 A	< 10.0 A	< 10.0 A	< 10.0 A
<b>Thermal Overload Protection</b>	Yes	Yes	Yes	Yes
<b>Filter Change Lamp</b>	Yes	Yes	Yes	Yes
<b>Audio Filter Alarm</b>	No	Yes	No	Yes
<b>Filtration Stages</b>	2-3	2-3	2-3	2-3
<b>99.97% HEPA Filter</b>	Yes (6" or 12")	Yes (6" or 12")	Yes (6" or 12")	Yes (6" or 12")
<b>First Stage Prefilter Part#</b>	H2001	H2001	H2001	H2001
<b>Second Stage Prefilter Part#</b>	H2002	H2002	H2002	H2002
<b>Optional Second Stage Prefilter Part#</b>	VL2024	VL2024	VL2024	VL2024
<b>HEPA Filter Part #</b>	H242406-99	H242406-99	H242406-99	H242406-99
<b>Optional HEPA Filter Part #</b>	H2010M	H2010M	H2010M	H2010M

Note: \*Airflow ratings are based on third party testing conducted @ 120 VAC with clean filters in accordance with generally accepted testing methods using electronic flow measurement equipment. Different testing methods may produce higher or lower results.