

4 CONNECTION / ASSEMBLY

2536 : Viper® P30+ Electro-Mechanical Press Fitting Machine



One of the lightest machine in its category: 4,5kg without jaw.
Crimping control by micro-processor:
 Systematic crimping control with LED display (green or red).
Automatic return of the piston.
USB/PC connection: Read numbers of cycles to anticipate maintenance (18 000 cycles).

180° pivoting head.

Maintenance indicator with preventive alert at 15 000 cycles before machine shutdown at 18 000 cycles.

Checks temperature and only works in optimum conditions (-10° +50°) in order to avoid wrong crimping.

230V – 50Hz power supply.

Ergonomic Soft Touch® handle for a perfect grip and comfort in use.

Optimum user safety: crimping control by electronic board. Systematic crimping control with LED display (green or red).

No-load cycle impossible to minimize risks of injury: a sensor detects the clamp when mounted on the Viper P30+.

The exact force required for crimping is calculated by the machine's internal program: moderate wear of mechanical components.

Size: 315 x 230 x 85 mm.

View all systems compatible with VIRAX inserts and clamps at the end of the catalogue.



Description	Size mm	Crimping force kN	Kg	Ref.
Viper® P30+ 230 V	460 x 450 x 140	32-35	7,800	253630

Capacities

Copper: Ø 12 - 54 mm.

Stainless steel: Ø 12 - 54 mm.

PER/PEX: Ø 12 - 32 mm.

Multilayer: Ø 12 - 110 mm.

Electro-zinc steel (or carbon steel): Ø 12 – 54 mm.

Delivered with

- Without crimping laws,
- In a case.

2532 - 2535 : Accessories for Press Fitting Machines

For	Description	Kg	Ref.
Viper® M21+ / Viper® P25+	Battery 18 V - 3 Ah Li-ion	0,790	253505
Viper® M21+	Battery 18 V - 1,5 Ah - Li-ion	0,450	253506
Viper® M21+ / Viper® P25+	240 V Charger - for 18 V - Li-ion battery	0,800	253507
Viper® M20+ / P22+	Battery 14,4 V - 2,4 Ah Li-Ion	0,645	253244
Viper® M20+ / P22+	230 V Charger - for 14,4 V battery - 2,4 Ah Li-Ion	0,740	251844
Viper® M20+ / P22+	Mains adaptor 230V	0,980	252938

