

3 ■ BENDING

MANUAL HYDRAULIC BENDER

2402 : Manual Hydraulic Bender



Bending capacity:
Gas pipes: Ø 3/8" to 4" (nfa 49115-en10255).
Locksmith's pipes: Ø 12 à 50 mm.
Multilayer pipes: Ø 40 to 63 mm.
Angle: 0 to 90°.

For medium and heavy series gas pipes.

Manual bender for site or workshop. Virax hydraulic benders have single-acting spring return pistons. Bender kits come in a wooden chest complete with formers and accessories.

Tip: Use Virax hydraulic ram oil for best protection. All necessary precautions must be taken when filling the ram to avoid foreign matter entering the reservoir as this may impair operation. Use horizontally.

* Supplied in a wooden chest.

** Supplied in two wooden chests.



For pipe	Formers	Ram	Type	Kg	Ref.
Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4"	Manual - no.1	Sliding cheek	44,500	240233*
Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2"	Manual - no.2	Open cheek	77,000	240242*
Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2"	Manual - no.2	Sliding cheek	71,000	240243*
Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2 - 2.1/2 - 3"	Manual - no.3	Hinged cheek	170,000	240252**
Multilayer	40 - 50 - 63 mm	Manual - n°2	Sliding cheek	54,000	240249*

2402 : Manual Hydraulic Bender for Locksmith's Pipe

For locksmith's pipes and electrical conduit.
 (Supplied without formers)

Capacity mm	Ram	Type	Kg	Ref.
Ø 12 to 50	Manual - no.2	Sliding Cheeks	58,000	240279



www.virax.com

Simple, quick and easy to use.
 Browse and download our online catalogue,
 Discover the new products,
 Find a point of sale,
 Subscribe to our newsletter,
 Ask for an appointment,
 In just a few clicks!