



XAVS 375 JD IT4

Purpose built for the most demanding job sites and conditions, Atlas Copco XAVS 375 HardHat™ will stand the test of time.



Atlas Copco

ALL THE OPTIONS YOU NEED YOUR SPECIFIC APPLICATIONS

The HardHat™ features a revolutionary polyethylene canopy design - the toughest in the industry. It will not rust, dent, corrode or fade, and it resists extreme temperatures. The canopy protects the compressor from damage at the work site, which helps reduce the cost of ownership and boost resale value. Because it will "take a beating" in a variety of applications, it's ideal for the rental industry.

Technical data

MODEL		XAVS 375 JD IT4
Actual Free Air Delivery	cfm	375
Working Pressure @ Rated Flow	psi	200
Working Pressure Range	psi	58-225
Discharge Outlet Quantity		1 x 1 1/2" 2 x 3/4"
Oil Capacity	Gal (L)	6.3 (23.8)

Engine - John Deere		
Model	John Deere	4045HFC93
Displacement	L	4.5
Cylinder		4
Tier	US EPA	iT4
Power	HP	125
Rated Speed (high)	RPM	2400
Rated Speed (low)	RPM	1500
Fuel Tank Capacity	Gal (L)	58 (219)
Fuel Consumption @ 100% FAD	Gal/hr (L/hr)	6.5 (24.6)
Sound Pressure Level @75% Load	dB (A)	76

Dimensions		
Trailer	in	161 x 71.5 x 70
Weight (wet), Trailer Mounted	lbs	4,470
Trailer (Skid Mounted)	in	113 x 71.5 x 65
Weight (wet), Skid Mounted	lbs	4,590

Photos and illustrations contained herein might depict products with optional and/or extra components which are not included with the standard version of the product and, therefore, are not included in a purchase of such product unless the customer specifically purchases such optional/extra components. We reserve the right to change the specifications and design of products described in this literature without notice. Not all products are available in all markets.

*According to ISO1217 ed 3.2009 annex D

STANDARD FEATURES

- HardHat™ Enclosure
- Extremely Reliable John Deere power with 5 year engine warranty
- Interim Tier 4 exhaust emission compliance
- Operates under widely varying climatic conditions, water-cooled engine, large capacity oil cooling system, high efficiency heavy-duty two-stage intake filters (with cartridge replacement indicators)
- Highly efficient oil extraction system means low oil consumption
- Large capacity fuel tank placed low for good road handling and easy filling
- Gull wing doors for easy access to engine and components
- Few moving parts, minimum mechanical wear
- Rugged and reliable, needing little maintenance
- Optional after-cooler / water separator & filtration system for cool, dry & clean air
- 375 CFM @ operating pressures from 58-225 PSI easily adjustable to meet the specified requirements of the job.

OPTIONS

- Cold Weather Package
- Hose Reels (Single or Double)
- LoJack® Stolen Vehicle Recovery System
- Support Mounted Frame (less running gear)
- 2" Ball Hitch
- After-cooler w/ Water Separator
- P.F.F. After-cooler w/Filtration & Water Separator
- Hydraulic brakes



Tier4 Interim

Atlas Copco

Danger: Compressed air should never be supplied as breathing air unless air is properly purified for breathing. Atlas Copco assumes no responsibility or liability related to the purchaser's/user's breathing air system

Atlas Copco. Tel 1.800.732.6762
www.atlascopco.us