



Model Number	XRXS 1275 CD6	XRVS 1350 CD6	XRYS 1220 CD7	XRYS 1260 CD7
FAD Rating	1252 cfm/435psi	1335 cfm/365psi	1174 cfm/510psi	1207cfm/510psi
Min./ Max. Working Pressure	276/465	232/392	305/510	305/510
Engine	CAT C-18	CAT C-18	CAT C-18	CAT C-18
Tier Rating	Available inT3 flex and iT4	Available inT3 flex and iT4	Available inT3 flex and iT4	Available inT3 flex and iT4
Engine Control	Electronic	Electronic	Electronic	Electronic
Aspiration	Turbocharged	Turbocharged	Turbocharged	Turbocharged
Horsepower	575	575	575	575
Number of Cylinders	6	6	6	6
Cooling System	Water	Water	Water	Water
Full Load Speed	1800	1800	1800	1800
Fuel Tank Capacity (Gal.)	258	258	258	258
Fuel Consumption @ 0% load (Gal/hr) ¹	10.6	9.6	13.22	12.9
Fuel Consumption @ 100% load (Gal/hr) ¹	27.2	26.5	27.75	27.1
¹ without FuelXpert™				
Compression Stages	2	2	2	2
Outlet Valve Configuration	1 x 2"	1 x 2"	1 x 2"	1 x 2"
Compressor Cooling System	Air/Oil	Air/Oil	Air/Oil	Air/Oil
Compressor Oil Capacity (Gal.)	21.7	21.7	21.7	21.7
Air Receiver Capacity (Gal.)	37.8	37.8	37.8	37.8
Sound Pressure Level @ 23 Ft.	76 dBa	76 dBa	76 dBa	76 dBa
Dimensions LxWxH (wheel mtd.)	233 x 86 x 104	233 x 86 x 104	234 x 86 x 104	233 x 86 x 104
Wheel Mtd Wet Weight (Lbs.) ²	17,855	17,855	17,855	17,855
Dimensions LxWxH (skid mtd.)	180 x 89 x 89	180 x 89 x 89	181 x 89 x 89	180 x 89 x 89
Skid Mtd Wet Weight (Lbs.) ²	16,655	16,655	16,655	16,655

²Please ask sales representative for all undercarriage configurations.