



Model Number	XAS 850 JD7 iT4	XATS 750 JD7 iT4	XAMS 1150 CD7 iT4	XATS 1050 CD7 iT4	XAHS 950 CD7 iT4
FAD Rating	850 cfm/100psi	774 cfm/150psi	1102 cfm/125psi	1020 cfm/150psi	938 cfm/175psi
Min./ Max. Working Pressure	58/125	58/171	58/145	58/170	58/194
Engine	Deere 6068HFC94 iT4	Deere 6068HFC94 iT4	CAT C9.3 Acert iT4	CAT C9.3 Acert iT4	CAT C9.3 Acert iT4
Engine Control	Electronic	Electronic	Electronic	Electronic	Electronic
Aspiration	Turbocharged	Turbocharged	Turbocharged	Turbocharged	Turbocharged
Horsepower	250	250	300	300	300
Number of Cylinders	6	6	6	6	6
Cooling System	Water	Water	Water	Water	Water
Full Load Speed	2000	2000	1800	1800	1800
Fuel Tank Capacity (Gal.)	78	78	210	210	210
Fuel Consumption @ 0% load (Gal/hr) ¹	6.8	6.8	8.3	8.3	8.1
Fuel Consumption @ 100% load (Gal/hr) ¹	13.4	13.6	15.5	15.6	15.5
¹ without FuelXpert™					
Compression Stages	1	1	1	1	1
Outlet Valve Configuration	1 x 2" / 2 x 3/4"	1 x 2" / 2 x 3/4"	1 x 2.5"	1 x 2.5"	1 x 2.5"
Compressor Cooling System	Air/Oil	Air/Oil	Air/Oil	Air/Oil	Air/Oil
Compressor Oil Capacity (Gal.)	13.75	13.75	16	16	16
Air Receiver Capacity (Gal.)	16.78	16.78	24	24	24
Sound Pressure Level @ 23 Ft.	76 dBa	76 dBa	76 dBa	76 dBa	76 dBa
Dimensions LxWxH (wheel mtd.)	190 x 79 x 84	190 x 79 x 84	192.9 x 84.7 x 98.4	192.9 x 84.7 x 98.4	192.9 x 84.7 x 98.4
Wheel Mtd Wet Weight (Lbs.) ²	7,760	7,760	12,809	12,809	12,809
Dimensions LxWxH (skid mtd.)	132 x 67 x 69.1	132 x 67 x 69.1	159.5 x 84 x 88.6	159.5 x 84 x 88.6	159.5 x 84 x 88.6
Skid Mtd Wet Weight (Lbs.) ²	6,685	6,685	11,387	11,387	11,387

²Please ask sales representative for all undercarriage configurations.