

85Z/86C COMPACT EXCAVATOR.

1. All dig end and dozer greasing intervals are best-in-class at 500 hours due to our graphite impregnated bronze bushes saving time and money.



2. Bucket rotation is a huge 200°, offering great spoil retention during truck loading. Choose an arm length to suit your application – from 5' 5" - 7' 5", providing total versatility.

3. The cab is incredibly spacious and its large door provides easy, safe access. Inside, you'll find 6% more space than our previous model.

4. Diesel by Kohler common rail Stage IIIB/Tier 4 final compliant engine doesn't need a diesel particulate filter (DPF), reducing servicing, increasing uptime and improving fuel efficiency.

6. We offer an angle dozer blade float option which enables easier ground levelling and efficient site clean-up.

5. Our 18"/24" steel tracks are pre-drilled to allow easy fitment of bolt on rubber pads. There is also the option of dedicated Road Liner Pads (GeoGrip), which enable individual segments to be replaced if damaged.



The heavy-duty boom cylinder guard provides excellent protection when loading.



The electro proportional high flow line has 10 selectable flow rates.



For safer lifting operations optional boom, dozer and dipper hose burst check valves are available.



For ultimate lift capacity and stability, opt for our 86c with its optional triple articulated boom (TAB) giving you a greater working range with extended reach, closer digging and higher dumping capability.

		85Z-I	86C-I	86C-I TAB
Operating weight standard arm	lbs	18298	18960	-
Gross engine power	hp	64.4	64.4	64.4
Standard arm length	ft-in	6' 7"	6' 11"	6' 11"
Dig depth - dozer down	ft-in	11' 11"	14' 4"	15' 2"
Ground level reach	ft-in	22' 2"	23' 3"	25' 3"
Dump height	ft-in	16' 3"	17' 8"	20' 8"
Fuel tank capacity	gal	30	30	30
Bucket breakout force	lbf	12837	12837	12837