AquaPak[™]1000S

1,000m³/d Containerised Seawater RO Desalination Plant

Modern Water's AQUAPAK-1000S desalination units are high specification, low cost, self-contained systems suitable for a variety of applications including potable or industrial water supply, temporary or emergency water supply, construction site water supply, the oil and gas industry as well as golf, resort or hotel complexes.

The AQUAPAK-1000S is supplied containerised in two 40' units that can be deployed and put into service in a short timeframe. It is manufactured using high quality components at an affordable price and is supplied and supported by Modern Water.

The AQUAPAK-1000S combines Ultra-Filtration (UF) and Reverse Osmosis (RO) as standard within the process train. Other process configuration options are available to tailor the standard unit to your requirements, this could include additional pre or post treatment, storage solutions, operator training or full operational support.

TECHNICAL DATA			
Capacity		1,000 m³/day	
Туре		2 × 40ft containers	
Dimensions		L 12.04m W 2.35m H 2.7m (each)	
Shipping weight		ca. 19T	
Operating weight		ca. 24T	
Connections (PN 10)		Power	
Connections (PN	10)	Power	
Connections (PN Feedwater	10) DN 125	Power Connection	380V, 50Hz, 3 Phase
,			380V, 50Hz, 3 Phase
Feedwater	DN 125		380V, 50Hz, 3 Phase
Feedwater RO permeate	DN 125 DN 80		380V, 50Hz, 3 Phase
Feedwater RO permeate RO concentrate	DN 125 DN 80 DN 100		

The standard unit includes:

- Pressure vessels loaded with RO membranes
- High pressure pump with energy recovery
- CIP system including CIP tank
- Chemical dosing systems including post RO treatment for disinfection and remineralisation
- Cartridge filters
- Instrumentation
- Control panel PLC
- UF membranes
- UF backwash system including pump and blower
- Self cleaning strainer
- Filtered water storage tank



Supplied & supported by: Modern Water

OPERATION SPECIFICATION

Maximum feedwater temperature	18 - 40 degC
Feedwater pressure	I - 3 bar
Recovery	35% - 40%
Hydrogen sulphide	< 0.1 mg/l
Turbidity	<5NTU
FeedwaterTDS	35,000 - 45,000 mg/l*
pH tolerance	4 - 10
Boron	< 5 mg/l
Chemical consumption (list)	NaOCl, Coag, HCl, Antiscalant, SBS, CaCl, NaHCO3
Nominal membrane rejection	99%

^{*} Based on standard seawater composition

Typical Applications

- Potable or industrial
- Small scale packaged plants or multi plant larger
- Water supply for construction
- Temporary water supply for breakdown, emergency or
- Water supply during

Key Benefits

- Ouick to install
- Environmentally friendly
- Cost effective
- Fully supported
- High quality product water that meets

Technical Support

- **Planning**
- Installation
- Training

Sales Contact

- Operation
- Maintenance visits / operational support
- Spares and consumables support

- ORP (RO feed) Low energy consumption

- Modular
- WHO guidelines for Drinking Water Quality

Process Options

permeate)

Key Instrumentation

pH (RO feed, post RO treatment)

Conductivity meter (RO feed, RO

Flow meter (UF feed, RO feed, RO

permeate, post RO treatment)

Pressure switch (RO feed, RO

Pressure sensor (UF feed, RO permeate)

FO and RO configurations

permeate, RO brine)

Purchase / Finance Options

tel: (UK) +44 (0)1483 696 000 tel: (US) +1 302 669 6900 www.modernwater.com info@modernwater.co.uk

^{*} Terms and conditions apply