

# AEGIS Controller

Process, Waste Water, Boiler and Cooling Tower Applications



ProMinent®

The **ProMinent® AEGIS** controller is the perfect economical solution for process, cooling, boiler and waste water treatment applications that provides the latest in controller technology.

## Standard Features

- Inhibitor feed using PPM setpoints
- Volumetric timer controls
- Relay mirroring
- Optional ethernet communications
- MODBUS
- Industrial and Commercial sales
- Plug and Play Upgrades
- ProMinent® thermal flow switch

## Benefits

- **Variable Frequency Pump Controls:** Accurate and precise chemical feed using pulse outputs. Can also select On/Off control if desired.
- **Data Logging:** Data history provides sensor minimum, maximum and average. Also records pump run times, pump feed volume, calculated drum levels, water meter volume, tower run time.
- **Exclusive Thermal Flow Switch:** This exclusive design does not require user adjustment or calibration. Operates on 1GPM flow rate with no moving parts.
- **Pump Integration:** Select from popular ProMinent® pump models built into the AEGIS programming for accurate ppm feed, tank level and feed volume.
- **Feed Inhibitor using ppm setpoints:** Accurate and precise inhibitor feed by simply inputting desired ppm level based on inhibitor chemistry. Use with make-up water meter.
- **Plug and Play Onsite Upgrades:** The AEGIS features Plug and Play technology allowing the user to perform simple onsite upgrades and scalability.
- **Program chemical feed based on drop tests:** Program chemical feed by entering results of system testing using ppm, ml or drop tests. Enter the new value and desired alarm setpoints for worry-free chemical feed and control.
- **Drum Level Alarms:** Provides low level alarms without the use of level sensors. The AEGIS calculates volume fed and subtracts from tank inventory.
- **Communications:** Ethernet, cellular, 3G Modem (EVDO).
- **View our live demo:** <http://controller.prominent.us:1008>

# AEGIS Controller

## Specifications

Specifications		
	Rating - Detail	Notes
<b>Analog-Digital I/O</b>		
Conductivity Sensor	Tower, Boiler, Condensate & Integral Flowswitch sensors	Default tower sensor includes 1 GPM integral flowswitch
Fixed Temperature Sensor Input	Thermal compensation for both pH and Conductivity	Displayed as °F, °C or °K
Fixed 4-20 mA Current Loop Input	Assignable to control any relay or variable frequency control	Single point calibration if 4 mA = 0
4 max. 4-20 mA Current	DC isolated, Manual & Auto modes, Interlocking, Alarm	Each optional current output uses a dual sensor card slot
7 max. Manual-Inventory-Inputs	Track drop counts, inventory, tank level, ppm	Alarmed delay prevents premature system ppm alarms
<b>Communications User Interface</b>		
Keypad-LCD	5 Key tactile feedback, Universal Characters 2 line, Backlit	Scan rate 100 mS nominal
10 Base T, TCP/IP Ethernet LAN (optional)	HTML micro web server with user definable IP address	Static IP Browser shows controller in real time
<b>Controls for ON/OFF &amp; Variable Frequency</b>		
Sequential Volume Setpoints	Feed a fixed volume for every make-up volume	Meter only, fault tolerant feed controls
Blocking	Any of 8 controls may block any other control	Prevents incompatible concurrent controls
Interlocking	Up to 4 contact sets can be 'AND'ed or 'OR'ed	Relays & Frequency controls OFF when contact set opens
9 Biocide Event Controls	Each of 9 controls includes 28 timed events	Each control selectable for 1, 7 & 28 day cycles
<b>System</b>		
Electrical	120/240 VAC, 50/60 Hz, Single Phase	Field Selectable
Fusing for 5 AC powered loads	5 Amps @ 120VAC or 2.5 Amps @ 230VAC	Alarm on open AC load fuse
Surge Suppression	Relay 2-5 N.O. contacts snubbed @ 0.1uF, 150 ohm	Varistor on AC line input
Accessory Power	15-22 VDC, Unregulated, thermally fused @ 50 mA	Auto-recovery on fault cleared
Enclosure	Non-metallic, NEMA 4X	7.5"W x 11.3"H x 5.5"D (190mm W x 287mm H x 140mm D)