



Model Number	XAS 300 JDU	XAS 375 JD6	XATS 375 JD6	XAVS 375 JD6	XAS 750 JD7 iT4
FAD Rating	300 cfm/100psi	375 cfm/100psi	375 cfm/150psi	375 cfm/200psi	750 cfm/100 psi
Min./ Max. Working Pressure	48/125	58/175	58/175	58/203	100/125
Engine	Deere 4024TF285	Deere 4045HF285	Deere 4045HF285	Deere 4045HF285	Deere 6068HFC94 iT4
Engine Control	Electronic	Electronic	Electronic	Electronic	Electronic
Aspiration	Turbocharged	Turbocharged	Turbocharged	Turbocharged	Turbocharged
Horsepower	80	115	125	125	200
Number of Cylinders	4	4	4	4	6
Cooling System	Water	Water	Water	Water	Water
Full Load Speed	2600	2400	2400	2400	2000
Fuel Tank Capacity (Gal.)	25	38	38	38	78
Fuel Consumption @ 0% load (Gal/hr) ¹	1.67	1.46	1.46	1.46	3
Fuel Consumption @ 100% load (Gal/hr) ¹ ¹ without FuelXpert™	4	4.3	4.7	5.7	9.2
Compression Stages	1	1	1	1	1
Outlet Valve Configuration	2 x 3/4"	1 x 1.5" / 2 x 3/4"	1 x 1.5" / 2 x 3/4"	1 x 1.5" / 2 x 3/4"	1 x 1.5" / 2 x 3/4"
Compressor Cooling System	Air/Oil	Air/Oil	Air/Oil	Air/Oil	Air/Oil
Compressor Oil Capacity (Gal.)	4.5	8	8	8	13.75
Air Receiver Capacity (Gal.)	4.5	11.1	11.1	11.1	16.78
Sound Pressure Level @ 23 Ft.	76 dBa	76 dBa	76 dBa	76 dBa	76 dBa
Dimensions LxWxH (wheel mtd.)	n/a	145 x 72 x 71	145 x 72 x 71	145 x 72 x 71	190 x 79 x 84
Wheel Mtd Wet Weight (Lbs.) ²	n/a	3,860	3,860	3,860	7,760
Dimensions LxWxH (skid mtd.)	84 x 34 x 55	104 x 55 x 68	104 x 55 x 68	104 x 55 x 68	132 x 67 x 69.1
Skid Mtd Wet Weight (Lbs.) ²	2,400	3,920	3,920	3,920	6,685

²Please ask sales representative for all undercarriage configurations.