

# CARBON STEEL GAUGES (OFFSET PATTERN DESIGN)

## CARBON STEEL GAUGE VALVE WITH STAINLESS STEEL TRIM

### AUTOMATIC

\*For Steam Pressures up to 300 PSI @ 422°F

- For Liquid Level Pressures up to:  
600 PSI @ 100°F  
345 PSI @ 400°F
- Graphite washer for:  
5/8" glass - 39/64" x 1-1/16" x 3/8"  
3/4" glass - 47/64" x 1-1/8" x 3/8"
- Rods 2-1/2" shorter than centers
- Glass 1-3/8" shorter than centers

Also available in Stainless Steel construction.

- 1/2" NPT Vent and Drain

MODEL		Size of NPT Connection	Size of Glass O.D.
Hand Wheel	Lever		
EFI 203J	EFI 204J	1/2"	5/8"
EFI 205J	EFI 206J	3/4"	3/4"



## CARBON STEEL GAUGE VALVE WITH STAINLESS STEEL TRIM

### AUTOMATIC

\*For Steam Pressures up to 300 PSI @ 422°F

- For Liquid Level Pressures up to:  
600 PSI @ 100°F  
345 PSI @ 400°F
- Graphite washer for:  
5/8" glass - 39/64" x 1-1/16" x 3/8"  
3/4" glass - 47/64" x 1-1/8" x 3/8"
- Rods 2-1/2" shorter than centers
- Glass 1-3/8" shorter than centers

Also available in Stainless Steel construction.

- 1/2" NPT Vent and Drain

MODEL		Size of NPT Connection	Size of Glass O.D.
Hand Wheel	Lever		
EFI 243J	EFI 244J	1/2"	5/8"
EFI 245J	EFI 246J	3/4"	3/4"



**WARNING:** For use with PROCESS SATURATED STEAM APPLICATIONS ONLY.

Carbon Steel Gauge Valves ARE NOT TO BE USED WITH SUPERHEATED STEAM.

**NOTE:** Important...Specify if valves are to be used for steam service. Steam and Liquid Level pressure ratings stated are for tubular glass use only.

★ Operating pressures and temperatures are subject to the limitations of the tubular gauge glass and washer composition...consult with Ernst Flow Industries for gauge glass ratings.

All valves on this page conform to AISI or ASTM specifications.