



Model Number	XAS 70 KD7	XAS 90 KD7	XAS 185 JD7 iT4	XAS 185 JD7 PE iT4	XAS 185 JDU7 iT4
FAD Rating	71 cfm/102 psi	88 cfm/102psi	185 cfm/100psi	185 cfm/100psi	185 cfm/100psi
Min./ Max. Working Pressure	58/128	58/128	58/125	58/125	58/125
Engine	Kubota D905	Kubota D1105	Deere 4024TF281	Deere 4024TF281	Deere 4024TF281
Engine Control	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Aspiration	Natural	Natural	Turbocharged	Turbocharged	Turbocharged
Horsepower	25	26	49	49	49
Number of Cylinders	3	3	4	4	4
Cooling System	Water	Water	Water	Water	Water
Full Load Speed	3600	3000	2750	2750	2750
Fuel Tank Capacity (Gal.)	8.46	8.46	25	25	27
Fuel Consumption @ 0% load (Gal/hr) ¹	0.07	0.07	1	1	1
Fuel Consumption @ 100% load (Gal/hr) ¹	1.5	1.5	2.9	2.9	2.6
Compression Stages	1	1	1	1	1
Outlet Valve Configuration	2 x 3/4"	2 x 3/4"	2 x 3/4"	2 x 3/4"	2 x 3/4"
Compressor Cooling System	Air/Oil	Air/Oil	Air/Oil	Air/Oil	Air/Oil
Compressor Oil Capacity (Gal.)	1.45	1.45	2	2	2.5
Air Receiver Capacity (Gal.)	2.47	2.47	3.8	3.8	3.14
Sound Pressure Level @ 23 Ft.	70 dBa	70 dBa	76 dBa	76 dBa	76 dBa
Dimensions LxWxH (wheel mtd.)	101 x 51 x 45	101 x 51 x 45	125 x 60 x 57	127 x 64 x 61	n/a
Wheel Mtd Wet Weight (Lbs.) ²	1,213	1,213	2,400	2,330	n/a
Dimensions LxWxH (skid mtd.)	62 x 40 x 34	62 x 40 x 34	77 x 41 x 54	81 x 45 x 65	84 x 34 x 57
Skid Mtd Wet Weight (Lbs.) ²	1,047	1,047	2,200	2,130	2,060

¹Please ask sales representative for all undercarriage configurations.