

8040/8045 COMPACT EXCAVATOR.



1. Load-sensed, flow-on-demand hydraulic system that automatically controls flow and pressure, providing the hydraulic oil to a service only when you need to use it.

3. Double-acting auxiliary pipework to the arm for powering attachments.



5. Fully adjustable seating position and control pod, with an efficient heating system or optional air conditioning allow you to obtain the most comfortable temperature.



2. Removable floor plates to access hose connection point under cab floor makes replacing hoses simpler.



4. 16" rubber tracks make good contact with the ground for best traction and a smooth ride.



Superb digging and tracking performance via the load-sensed hydraulic system.



ZTS offers more maneuverability (especially in confined spaces).



Optimum track footprint for good all-round stability and least-effort spin turning.

The JCB 8040 ZTS and 8045 ZTS feature a 44.4HP engine, making these machines very powerful for this class of excavator.



		8040 ZTS	8045 ZTS
Operating weight standard arm	lbs	9480	10472
Gross engine power	hp	48.7	48.7
Standard arm length	ft-in	5' 0"	5' 8"
Dig depth - dozer down	ft-in	11' 7"	12' 3"
Ground level reach	ft-in	18' 5"	19' 2"
Dump height	ft-in	12' 7"	13' 1"
Fuel tank capacity	gal	13	13
Bucket breakout force	lbf	8340	9487