

EVID90PEVID90P SD PTZ Camera

\$1,349.00

U.S.List Price

UPC: 027242273597

Overview

The EVI-D90P (PAL version) features 28x optical zoom, and utilizes the RS-232C/RS-422 VISCATM protocol interface, which can allow for easy connectivity to many peripheral system devices. In addition, the CCD sensor offers more sensitivity than previous EVI SD cameras. With high speed pan/tilt/zoom functionality, this easy-to-use camera is an attractive addition to the EVI P/T/Z camera lineup. Best of all, this new camera is ceiling mountable, allowing for more flexible design-in options in many applications.

Highlights

- * $\,$ Utilizes RS-232C/RS-422 VISCA protocol interface, which can allow for easy connectivity to peripheral devices
- * $\,$ New CCD and CMOS sensors offer more sensitivity than previous EVI SD cameras
- * Ceiling mountable, which allows for more flexible design-in options in many applications

Specifications

| Camera Specifications | Detail |
|--------------------------|--|
| Image Device | 1/4-type CCD |
| Lens | f= -4.1mm (Wide) to 73.8mm (Tele) F1.4 to F3.0 28x optical zoom 12x digital zoom |
| Minimum Object Distance | 10 mm (wide) - 1,500 mm (tele) *Default: 290 mm |
| Shutter Speed | 1 to 1/10,000 s |
| Gain | Auto/Manual/Max. AE Gain Limit (-3 dB to +28 dB, 2 dB steps) |
| White Balance | Auto, ATW, Indoor, Outdoor, One-push, Manual |
| Pan Angle/Speed | Angle: +/- 170° Speed: 100°/sec |
| Tilt Angle/Speed | Angle: +90°/-20° Speed: 90°/sec |
| Horizontal Viewing Angle | 48° (Wide) to 2.8° (Tele) |
| | |

Video Output

Preset Positions

Detail

| Specifications | | _ |
|------------------------|---|--------------------------------|
| Minimum Illumination | 0.65 lx (F1.35, 50 IRE) | |
| S/N Ratio | More than 50 dB | |
| Video Output | VBS, Y/C | |
| Signal System | PAL | |
| General Specifications | Detail | |
| Dimensions (W x H x D) | 145 x 164 x 164 mm (5 3/4 x 6 1/2 x 6 1/2 inches) | |
| Weight | 1440 g (3 lbs., 3 oz.) | |
| Power Requirements | DC 12V | |
| Power Consumption | 6 W | |
| Operating Temperature | 0° C to 40° C (32° F to 104° F) | |
| Storage Temperature | -20° C to +60° C (-4° F to +140°) | |
| | | |
| | | |
| Accessories | | |
| Supplied Accessories | | |
| Model: | Description: | U.S.List Price |
| | AC Adaptor | Pricing available upon request |
| | AC Power Cable | Pricing available upon request |

| Model: | Description: | U.S.List Price |
|--------|--------------------------|--------------------------------|
| | AC Adaptor | Pricing available upon request |
| | AC Power Cable | Pricing available upon request |
| | IR Remote Commander Unit | Pricing available upon request |
| | Ceiling bracket | Pricing available upon request |
| | RS-422 connector plug | Pricing available upon request |
| | Operating Instructions | Pricing available upon request |
| | | • |

Optional Accessories

| Model: | Description: | U.S.List Price |
|---------|---|----------------|
| RMBR300 | Remote Control Unit for the BRC-300 / H700 / Z700 / Z330 / H900 | \$1,575.00 |

Resources

Product Brochure

| Description: | Release Date | Type/Size | |
|--------------------------------|--------------|--------------|--------------|
| rmbr300.pdf | 08/25/2004 | pdf / 1,937K | Download now |
| CPITV4S Controller Brochure | | pdf / 1,318K | Download now |

Brochure

| Description: | Release Date | Type/Size | | |
|--------------------|--------------|------------|--------------|--|
| EVI New Generation | 01/01/2012 | pdf / 233K | Download now | |

User Manual

| Description: | Release Date | Type/Size | |
|------------------|--------------|--------------|--------------|
| EVI-D80/D90 User | | pdf / 1,381K | Download now |
| Manual | | | |