



The Javelin S870 is a proximity card reader without keypad for integrated access control. The attractive, contemporary black and silver finish is designed to complement any office or building environment.

The Javelin S870 reads I25KHz HID proximity cards.

The Javelin S870 is designed for use with the Symmetry range of door controllers and is compatible with all versions of Symmetry software.

The Javelin S870 uses secure, bi-directional, pseudo-random supervised MCLP communications to the door controller. Both the card reader and cable are supervised, and an alarm will be generated if the card reader is tampered with or communications lost.

Wiegand communication is also supported between the card reader and controller.

#### **KEY FEATURES**

- Proximity access control card reader for a wide range of security applications
- Designed to fit most standard electrical back boxes
- Maximum read range of 4" (102mm) dependent on card
- Reads I25KHz HID proximity cards
- Secure, bi-directional, Pseudo-Random supervised MCLP communications
- Wiegand output
- Integrated Door Pre-held warning buzzer
- Multi-tone audio sounder for access granted or denied
- LED feedback for verification of card accepted or rejected
- Three color LED alert status indication

### **SPECIFICATIONS**

### **Model Types**

 Javelin S870 - HID 125KHz proximity card reader with integrated

## **Communicating Distances**

- All Symmetry door controllers to Symmetry S870 (MCLP) = 3000ft/1000m
- All Symmetry door controllers to Symmetry S870
- (Wiegand) = 500ft/I50m

#### **Dimensions inches (mm)**

- Width = 3.5" (85mm)
- Height = 4.4" (113mm)
- Depth = 0.9" (23mm)

## **Operating Environment**

- -I3°F to +I58°F (-25°C to +70°C)
- 15% to 90% Humidity, non-condensing

## **Power Requirements**

- Nominal I2VDC (9-I4V)
- Maximum current consumption I20mA

### **APPROVALS**

# Radio regulatory approvals

- FCC CFR47 Part I5C
- EN 302291

#### **EMC** Type Testing

■ EN 301489

#### Access control product testing

- IP44: R & TTE Directive 1999/5/E
- UL 294

#### **PURCHASING INFORMATION**

• 870 – Card only proximity reader







