

DESCRIPTION:


The IS-IPDVF-HID is an IP video door station for the IS Series, with a built in HID® ProxPoint® Plus card reader.

The video door station will connect via CAT-5e/CAT-6 wire to a local area network (LAN). Maximum wire distance from the door station to the LAN is 328' (standard network wire distance rules apply).

Wiring and power for the card reader are separate from the intercom wiring. The card reader is to be connected to a host controller of any type that is compatible with the HID® ProxPoint® Plus proximity card reader. Flush mount with supplied back box or surface mount with SBX-ISDVFP.

FEATURES:

- IP Video door station for IS Series
- Stainless steel faceplate
- Directory strip
- HID® ProxPoint® Plus proximity card reader built in
- Tamper resistant screws



IS-IPDVF-HID

Stainless Steel Flush Mount IP Video Door Station with HID® Proximity Reader

FEATURE CALL-OUT DEFINITIONS:

- [1] Camera
- [2] Microphone
- [3] White LED illuminator
- [4] Speaker
- [5] Directory card
- [6] Call status indicator
- [7] Call button
- [8] HID Proximity reader

SPECIFICATIONS:

- Power Source: 24V DC or 802.3af PoE
- Bandwidth: 320k ~ 8Mbps
- Communication: Open voice hands-free
- Camera: 1/4" color CMOS
- Min. illumination: 5 Lux
- Wiring: CAT-5e or CAT-6
- Door release: 24V AC/DC, 500mA (N/O, COM, N/C)
- Operating Temp: -22° - 140°F (-30° - 60°C)
- Dimensions: 12-3/8" H x 7" W x 1-7/8" D

FEATURE CALL-OUTS:

