

# aptiQ\_

## MT20 Multi-technology enrollment reader with ENGAGE™ technology

#### Overview

The aptiQ<sup>™</sup> MT20 USB multi-technology enrollment reader with ENGAGE<sup>™</sup> technology is designed to simplify your enrollment process. The MT20 simplifies the enrollment of proximity, smart or mobile credentials in an access control system by using a computer's USB connection. The MT20 does not require software to operate when using a USB connection and will function on any operating system. When using the ENGAGE Web Application, the MT20 will automatically output the data in the expected format. The USB connection emulates a keyboard and will keystroke the facility code and badge ID from the credential to the cursor's location on the screen.

The MT20 is compatible with aptiQ smart credentials (MIFARE<sup>®</sup> Classic and MIFARE DESFire<sup>™</sup> EV1), aptiQmobile<sup>™</sup> credentials and most proximity credentials.



### Features and benefits

- Use your computer and the ENGAGE web app to easily enroll credentials in your access control system
- Recognizes aptiQ smart credentials (MIFARE<sup>®</sup> Classic and MIFARE DESFire<sup>™</sup> EV1), aptiQmobile credentials and most proximity credentials
- Limited Lifetime Warranty



	T
Model	MT20
Reader type	USB
Software and operating system requirements	N/A - USB
Bit formats recognized	26A, 32X, 34N, 34S, 35C, 37X, 37H, 40X
Technologies supported	Schlage Proximity XceedID™ Proximity HID® Proximity GE/CASI ProxLite® AWID® Proximity LenelProx®
	Schlage MIFARE® Secure Sector XceedID™ MIFARE® Secure Sector aptiQ™ Smart Cards using MIFARE DESFire™ EV1 with PACSA DESFire® CSN HID iClass® CSN Inside Contactless PicoTag® CSN ST Microelectronics® CSN Texas Instruments Tag-It® Serial Number Phillips I-Code® CSN
Physical dimensions (l x w x h)	5.56" x 2.00" x .695"
Operating temperatures	0 to 40 C
Weight	4.1 oz
Power supply	Connect to powered USB port or via USB power supply
Interface	USB
Current requirement	160 mA
Default configuration	CE-401-073, for use with ENGAGE web applicaton
Octal output	CE-401-061, for use with SMS Express
FC/BID output	CE-401-060 (SUSB89 default,) for use as keystroke emulator
BID only	CE-401-069, for use as keystroke emulator

Allegion, the Allegion logo, Schlage, aptiQ, the aptiQ logo, aptiQmobile and XceedID, are trademarks of Allegion plc, its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners.

#### **About Allegion**

Allegion (NYSE: ALLE) is a global pioneer in safety and security, with leading brands like CISA<sup>®</sup>, Interflex<sup>®</sup>, LCN<sup>®</sup>, Schlage<sup>®</sup> and Von Duprin<sup>®</sup>. Focusing on security around the door and adjacent areas, Allegion produces a range of solutions for homes, businesses, schools and other institutions. Allegion is a \$2 billion company, with products sold in almost 130 countries. For more, visit **www.allegion.com.** 



© 2015 Allegion 010523, Rev. 8/15 www.allegion.com/us