

FIRE HOSE, NOZZLES, BRASS, & HOSE VALVES

Pre-tested under UL supervision, this **UL LABELED SINGLE JACKET FIRE HOSE** features fully rubber lined 100% polyester construction. Every length carries the **UL®** mark and has a proof test pressure of 500 psi and a service test of 250 psi. Brass NST coupled.

NOTE: Recommended for industrial fire protection.


	SIZE	COUPLED
50' x 1 1/2" UL Hose	1 13/16"	15 lb
75' x 1 1/2" UL Hose	1 13/16"	20 lb
100' x 1 1/2" UL Hose	1 13/16"	27 lb
50' x 2 1/2" UL Hose	2 13/16"	27 lb



DOUBLE JACKET FIRE HOSE features two jackets of 100% polyester rubber-lined material for added protection against cuts, rips, and abrasion. It has a proof test pressure of 800 psi and a service test of 400 psi. Meets NFPA 1961.

NOTE: Recommended for industrial fire protection.

DESCRIPTION	BOWL SIZE	WEIGHT COUPLED
Brass	1 15/16"	20 lb
50' x 1 1/2" DJ Hose, Alum	1 15/16"	18 lb
100' x 1 1/2" DJ Hose, Brass	1 15/16"	35 lb
100' x 1 1/2" DJ Hose, Alum	1 15/16"	32 lb
50' x 2 1/2" DJ Hose, Brass	3"	37 lb
50' x 2 1/2" DJ Hose, Alum	3"	34 lb



This **YELLOW COATED FIRE HOSE** is constructed to the same specifications as the standard **Double Jacket Hose**. Every section of **Coated Hose** is independently and completely impregnated with an abrasion-resistant, water-repellent polymer for outstanding performance under tough conditions. Aluminum NST coupled.

NOTE: Recommended for industrial fire protection.

BOWL SIZE	WEIGHT COUPLED
1 15/16"	21 lb
2 1/8"	25 lb
3"	39 lb



RUBBER COVERED FIRE HOSE is the choice of professionals nationwide. Abrasion-resistant, it features a heat-free nitrile synthetic one-piece cover and liner that is impervious to water, oil, gas, and most chemicals. Lightweight, it is virtually kink-resistant for easy handling, and it never needs drying. It has a proof test pressure of 500 psi and a service test of 250 psi. Aluminum NST coupled. Meets NFPA 1961. Imported.

