




## Carbon Dioxide

Carbon Dioxide is the trusted non-conductive clean agent and is most effective for dealing with electronic equipment fires. CO2 is suitable for use on Class B and Class C fires.

**Typical Uses:** For protecting sensitive electronic equipment in offices, classrooms, churches, parking garages, and hotel/motel assembly halls and guest areas. For protecting sensitive electronic equipment in businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.

Recommended for use on sensitive electronic equipment.

Third Party Approvals For Peace Of Mind



Canadian Part Numbers are shown in parentheses.

Model	5CD	10CD	15CD	20CD
<b>Pt. #</b>	45100 (45191)	45600 (45691)	46100 (46191)	46600 (46691)
<b>Agent Capacity</b>	5 lb. (2.27 kg)	10 lb. (4.54 kg)	15 lb. (6.8 kg)	20 lb. (9.07 kg)
<b>UL/ULC Rating</b>	5-B:C	10-B:C	10-B:C	10-B:C
<b>Temperature Range</b>	-22° to 120°F (-30° to 49°C)			
<b>Discharge Time</b>	9 sec	9 sec	15 sec	20 sec
<b>Discharge Range ft (m)</b>	4-8 (1.2-2.4)	4-8 (1.2-2.4)	4-8 (1.2-2.4)	4-8 (1.2-2.4)
<b>Mounting Type</b>	Wall	Wall	Wall	Wall
<b>USCG Approval</b>	Type B:C Size I	Type B:C Size I	Type B:C Size II	Type B:C Size II
<b>Ship Weight</b>	13.75 lb. (6.3 kg)	27.75 lb. (12.6 kg)	37.75 lb. (17.1 kg)	49 lb. (22.2 kg)
<b>Unit Height</b>	17.375 in (44.1 cm)	19.75 in (50.2 cm)	26.375 in (67 cm)	26.875 in (68.2 cm)
<b>Unit Width</b>	8.25 in (21 cm)	12 in (30.5 cm)	12 in (30.5 cm)	13 in (33 cm)
<b>Unit Diameter</b>	5.25 in (13.3 cm)	6.89 in (17.5 cm)	6.89 in (17.5 cm)	8 in (20.3 cm)