


2nd Class Pyranometer



OVERVIEW

Economical and Reliable for Routine Global Radiation Measurements

The 5600-0605 is a second class pyranometer (as defined by the World Meteorological Organization, WMO); compliant with all ISO 9060 performance criteria.



SPECIFICATIONS

Specifications subject to change without notice

Spectral Range	305 - 2800 nm (50% points)
Sensitivity	10 - 35 μ V/W/m ²
Impedance	79 - 200 Ohms
Response Time	95% in 18 seconds
Non-linearity	< \pm 2.5% (<1000 W/m ²)
Operating Temp	-40 to +80°C
Temperature Dependence	\pm 6% (-10 to +40°C)
Expected Accuracy	\pm 10% for daily sums
Tilt Error	< \pm 2.5% (<1000 W/m ²)
Weight	343 grams
Maximum Irradiance	2000 W/m ²
Directional Error	< \pm 25 W/m ² (Beam 1000 W/m ²)
Cable Length	5m
Dimensions	
Weight	0.756 lb. (343 grams)
ORDERING	
5600-0605	Pyranometer 2nd Class, 5m cable
Accessories	
6661-1098-1	Mounting Kit, Pyranometer (CAFI mounting bracket for Albedometer & CLFI leveling fixture also available)

FEATURES

- ▶ Ruggedized, weather proof construction
- ▶ Sealed and potted low maintenance design
- ▶ Excellent long term stability of sensitivity
- ▶ Good cosine/directional response
- ▶ Built-in lifetime desiccant drying cartridge
- ▶ Thermopile sensor (not silicon cell)
- ▶ Flat spectral sensitivity
- ▶ Temperature compensation
- ▶ Output is a millivolt signal.
- ▶ Each sensor has its own calibration certificate.

APPLICATIONS

- ▶ Global radiation
- ▶ Reflected solar radiation
- ▶ Albedometer