

Available in configurations with three or four mounting assemblies.

Picture is a representation of actual product

The ITCM Series utilizes several Rice Lake Weighing Systems components to provide an unmatched level of performance in tank and hopper weighing applications and mechanical scale conversions. The ITCM SS incorporates clevis and unique rod-end ball joint assemblies to reduce the overall length to less than half of the traditional tension cell mounts, while providing correct load alignment. In addition, the load cell is completely electrically isolated from stray currents, which are a major cause of load cell failure. To complete the design, a grounding strap connects the two clevis assemblies to further provide safety to your load cells.

Module with RL20000 ST s-beam load cell.

Important: Read "Load Cell Mounting Hardware Safety Guidelines"

Standard Features

- Capacities (per module): 100 lb-5,000 lb (45.4 kg-2,268.0 kg)
- · Clevis mounts with nylon insulating washers
- · PTFE-lined rod-end ball joints
- · Load cell is completely isolated from stray currents
- Grounding strap provides alternative path to ground
- · Complete package for ease of installation
- Provides correct load cell loading even in difficult installations
- Lower overall height compared to other isolated tension assemblies

Applications

- · Suspended hoppers and tanks
- · Mechanical scale conversions
- Use as a single module or in multiples

Complete kit includes:

- Three or four ITCM assemblies with RL20000 ST NTEP Certified s-beam load cells
- One JB4SS NEMA Type 4X stainless steel signal trim junction box
- 25ft of our hostile environment EL147HE SURVIVOR® load cell cable


Load Cell Certifications





Load Rating Dimensions - Inches (mm)*

Loua Kam	.9 5	11101100	(,,,,,,	
Load Cell Capacity	A	В	С	D
lb/in				
100 lb	2.00	1.81	3/8-16 UNC 1/2-13 UNC	7.00 (ref)
250 lb	2.00	1.81	3/8-16 UNC 1/2-13 UNC	7.00 (ref)
500 lb	2.68	2.68	1/2-13 UNC 5/8-11 UNC	9.50 (ref)
750 lb	2.68	2.68	1/2-13 UNC 5/8-11 UNC	9.50 (ref)
1,000 lb	2.68	2.68	1/2-13 UNC 5/8-11 UNC	9.50 (ref)
2,500 lb	2.68	2.68	5/8-11 UNC 3/4-10 UNC	9.50 (ref)
3,000 lb	3.37	3.37	3/4-10 UNC	10.75 (ref)
5,000 lb	3.37	3.37	3/4-10 UNC	12.00 (ref)
kg/mm				
(45.4 kg)	(50.8)	(46.0)	3/8-16 UNC 1/2-13 UNC	(177.8)
(113.4 kg)	(50.8)	(46.0)	3/8-16 UNC 1/2-13 UNC	(177.8)
(226.8 kg)	(68.1)	(68.1)	1/2-13 UNC 5/8-11 UNC	(241.3)
(340.2 kg)	(68.1)	(68.1)	1/2-13 UNC 5/8-11 UNC	(241.3)
(453.6 kg)	(68.1)	(68.1)	1/2-13 UNC 5/8-11 UNC	(241.3)
(1,134.0 kg)	(68.1)	(68.1)	5/8-11 UNC 3/4-10 UNC	(241.3)
(1,360.8 kg)	(85.6)	(85.6)	3/4-10 UNC	(273.0)
(2,268.0 kg)	(85.6)	(85.6)	3/4-10 UNC	(304.8)



Order Information

Single N	Nodule	Part # (C)	Price
100 lb	45.4 ka	46765 (3/8-16 UNC)	\$750.00
10010	45.4 kg	46766 (1/2-13 UNC)	\$750.00
250 lb	113.4 kg	46767 (3/8-16 UNC)	\$750.00
23010	113.4 kg	46768 (1/2-13 UNC)	\$750.00
500 lb	226.8 kg	46769 (1/2-13 UNC)	\$750.00
J001b	220.0 kg	46770 (5/8-11 UNC)	\$750.00
750 lb	340.2 kg	46771 (1/2-13 UNC)	\$750.00
7 30 10	340.2 kg	46772 (5/8-11 UNC)	\$750.00
1.000 lb	453.6 kg	46773 (1/2-13 UNC)	\$750.00
1,00010	400.0 kg	46774 (5/8-11 UNC)	\$750.00
2.500 lb	2,500 lb 1,134.0 kg	46775 (5/8-11 UNC)	\$750.00
2,30010	1,134.0 kg	46776 (3/4-10 UNC)	\$750.00
3,000 lb	1,360.8 kg	46777 (3/4-10 UNC)	\$800.00
5,000 lb	2,268.0 kg	46778 (3/4-10 UNC)	\$1,390.00

	3-Modu	le Kit	Part # (C)	Price
	100 lb	45.4 kg	46735 (3/8-16 UNC)	\$2,460.00
	10010	45.4 kg	46736 (1/2-13 UNC)	\$2,460.00
	250 lb	113.4kg	46737 (3/8-16 UNC)	\$2,460.00
	23010	113.4 Kg	46738 (1/2-13 UNC)	\$2,460.00
	500 lb	226.8 kg	46739 (1/2-13 UNC)	\$2,460.00
	00010	220.0 Kg	46740 (5/8-11 UNC)	\$2,460.00
	750 lb	340.2 kg	46741 (1/2-13 UNC)	\$2,460.00
	73010	340.2 Kg	46742 (5/8-11 UNC)	\$2,460.00
	1 000 lb	453.6 kg	46743 (1/2-13 UNC)	\$2,460.00
	1,00010	455.0 Kg	46744 (5/8-11 UNC)	\$2,460.00
	2,500 lb 1,134.0 kg	46745 (5/8-11 UNC)	\$2,460.00	
		1,134.0 Kg	46746 (3/4-10 UNC)	\$2,460.00
	3,000 lb	1,360.8 kg	46747 (3/4-10 UNC)	\$2,610.00
	5,000 lb	2,268.0 kg	46748 (3/4-10 UNC)	\$4,455.00

4-Modu	le Kit	Part # (C)	Price
100 lb	4E 41ca	46751 (3/8-16 UNC)	\$3,115.00
100 lb	45.4 kg	46752 (1/2-13 UNC)	\$3,115.00
OEO Ib	113.4 kg	46753 (3/8-16 UNC)	\$3,115.00
250 lb	113.4 Kg	46754 (1/2-13 UNC)	\$3,115.00
500 lb	206.01/4	46755 (1/2-13 UNC)	\$3,115.00
ฉบบเ	226.8 kg	46756 (5/8-11 UNC)	\$3,115.00
	340.2kg	46757 (1/2-13 UNC)	\$3,115.00
750 lb	340.2 kg	46758 (5/8-11 UNC)	\$3,115.00
1,000 lb	453.6 kg	46759 (1/2-13 UNC)	\$3,115.00
1,00010	455.6 Kg	46760 (5/8-11 UNC)	\$3,115.00
2,500 lb	1,134.0 kg	46761 (5/8-11 UNC)	\$3,115.00
2,50010	1,134.0 Kg	46762 (3/4-10 UNC)	\$3,115.00
3,000 lb	1,360.8 kg	46763 (3/4-10 UNC)	\$3,315.00
5,000 lb	2,268.0 kg	46764 (3/4-10 UNC)	\$5,775.00

^{*} Load rating is per module