



### Standard Features

- Internal calibration weight
- Auto environmental compensation
- IP54 splash-proof operator keyboard
- RS-232C bidirectional interface
- WinCT® communication tools software
- GLP/GMP/ISO compliant to either AD-8121 printer or computer.
- Transmits date, time, ID number, serial number and calibration data
- Auto re-zero function
- Interval time setting; built-in time and date
- Rechargeable battery option for portability
- Data memory function
- Multiple weighing modes: Counting, Percentage and Comparator Modes
- Super Hybrid Sensor Technology (SHS)
- Vacuum Fluorescent Display (VFD)
- Optional glass breeze break
- Underhook weighing

### Specifications

	GX-200 <sup>^</sup>	GX-400 <sup>^</sup>	GX-600 <sup>^</sup>	GX-800 <sup>^</sup>	GX-1000 <sup>^</sup>	
Part #	97685	97686	97687	97688	97689	
List Price	\$1,950.00	\$2,430.00	\$2,880.00	\$3,050.00	\$3,240.00	
Capacity	210g	410g	610g	810g	1100g	
Resolution	0.001 g	0.001 g	0.001 g	0.001 g	0.001 g	
Modes	Animal Weighing, Comparator Function, ACAI Counting Function, Percentage Function, Density Determination					
Repeatability	0.001 g					
Linearity	±0.002 g		±0.003 g			
Stabilization Time	Approx 1 second (typical in FAST mode)			Approx. 1.5 seconds		
Display Refresh	5 times per second (stable) / 10 times per second (unstable)					
Operating temperature	41° F to 104° F (5° C to 40° C) RH less than 85% (No condensation)					
Pan Size	5.04 x 5.04 in (128 x 128 mm)					
Physical Dimension	(W x D x H) 8.26 x 12.48 x 3.38 in (210 x 317 x 86 mm)					
Weighing Chamber	3.6 in H (91.3 mm H)					
Weight (Approx.)	2.15 lb (4.6 kg)					
Power	120/240 VAC adapter Approx 11 VA					
Warranty	Five-year Limited Warranty					
Return Policy	A&D Weighing Standard Policy - restock fee may apply					
UNIT OF MEASURE	Decimal Ounce	7.40755 x 0.00005 oz	14.46230 x 0.00005 oz	21.51710 x 0.00005 oz	28.57190 x 0.00005 oz	38.80135 x 0.00005 oz
	Decimal Pound	0.462970 x 0.000005 lb	0.903895 x 0.000005 lb	1.344820 x 0.000005 lb	1.785744 x 0.000005 lb	2.425084 x 0.000005 lb
	Troy Ounce	6.75165 x 0.00005 ozt	13.18180 x 0.00005 ozt	19.61195 x 0.00005 ozt	26.04210 x 0.00005 ozt	35.36582 x 0.00005 ozt
	Pennyweight	135.033 x 0.001 dwt	263.636 x 0.001 dwt	392.239 x 0.001 dwt	520.842 x 0.001 dwt	707.316 x 0.001 dwt
	Carat	1,050.000 x 0.00 5 ct	2,050.000x 0.005 ct	3,050.000 x 0.005 ct	4,050.000 x 0.005 ct	5,500.000 x 0.005 ct
	Momme	56.0000 x 0.0005 mom	109.3335 x 0.0005 mom	162.6665 x 0.0005 mom	215 x 0.0005 mom	270 x 0.0005 mom
	Grain Unit	3,240.80 x 0.02 GN	6,327.26 x 0.02 GN	9,413.74 x 0.02 GN	12,500.21 x 0.02 GN	16,975.6 x 0.02 GN
	Pound x Ounce	7.4 lb 1 oz	14 lb 46 oz	1 lb 5.52 oz	1 lb 12.80 oz	2 lb 4 oz

<sup>^</sup> Weighing Chamber

## Specifications

	GX-2000	GX-4000	GX-6100	GX-6000	GX-8000	
Part#	97690	97691	97692	97693	97694	
List Price	\$1,850.00	\$2,620.00	\$2,925.00	\$2,250.00	\$2,460.00	
Capacity	2,100g	4,100g	6,100g	6,100g	8,100g	
Resolution	0.01g	0.01g	0.01g	0.1g	0.1g	
Operating Modes	Animal Weighing, Comparator Function, ACAI Counting Function, Percentage Function, Density Determination					
Repeatability	0.01g			0.1g		
Linearity	±0.02g		±0.03g		±0.1g	
Stabilization Time	Approx. 1 sec (typical in FAST mode)		Approx. 1.5 seconds		Approx. 1 second	
Display Refresh	5 times per second (stable) / 10 times per second (unstable)					
Operating temperature	41°F to 104°F (5°C to 40°C) RH less than 85% (No condensation)					
Pan Size	6.50 in x 6.50 in (165 x 165 mm)					
Physical Dimension	(W x D x H) 8.26 x 12.48 x 3.38 in (210 x 317 x 86 mm)					
Weighing Chamber	3.6 in H (91.4 mm H)					
Weight (Approx.)	Approx 2.05 lb (5.1 kg)					
Power	120/240V by AC adapter Approx 11 VA					
Warranty	Five-year Limited Warranty					
Return Policy	A&D Weighing Standard Policy - restock fee may apply					
UNIT OF MEASURE	Decimal Ounce	74.0755 x 0.0005 oz	144.6230 x 0.0005 oz	215.1710 x 0.0005 oz	215.170 x 0.0005 oz	285.720 x 0.0005 oz
	Decimal Pound	4.62970 x 0.00005 lb	9.03895 x 0.00005 lb	13.44820 x 0.00005 lb	13.4480 x 0.0005 lb	17.8575 x 0.0005 lb
	Troy Ounce	67.5165 x 0.0005 ozt	131.8180 x 0.0005 ozt	196.1195 x 0.0005 ozt	196.120 x 0.0005 ozt	260.420 x 0.0005 ozt
	Pennyweight	1,350.33 x 0.01 dwt	2,636.36 x 0.01 dwt	3,922.39 x 0.01 dwt	3,922.4 x 0.1 dwt	5,208.4 x 0.1 dwt
	Carat	10,500.00 x 0.05 ct	20,500.00 x 0.05 ct	30,500.00 x 0.05 ct	30,500.0 x 0.5 ct	40,500.0 x 0.5 ct
	Momme	560.000 x 0.005 mom	1,093.335 x 0.005 mom	1,626.665 x 0.005 mom	1,626.65 x 0.05 mom	2,160.00 x 0.05 mom
	Grain Unit	32,408.0 x 0.2 GN	63,272.6 x 0.2 GN	94,137.4 x 0.2 GN	94,136 x 2 GN	125,002 x 2 GN
	Pound x Ounce	4 lb 10.08 oz	9 lb 0.62 oz	13 lb 7.17 oz	13 lb 7.17 oz	17 lb 13.72 oz

## Part Number/Price

Part #	Model #	Description	Price
97685	GX-200	210g x 0.001g	\$1,950.00
97686	GX-400	410g x 0.001g	\$2,430.00
97687	GX-600	610g x 0.001g	\$2,880.00
97688	GX-800	810g x 0.001g	\$3,050.00
97689	GX-1000	1,100g x 0.001g	\$3,240.00
97690	GX-2000	2,100g x 0.01g	\$1,850.00
97691	GX-4000	4,100g x 0.01g	\$2,620.00
97692	GX-6100	6,100g x 0.01g	\$2,925.00
97693	GX-6000	6,100g x 0.1g	\$2,250.00
97694	GX-8000	8,100g x 0.1g	\$2,460.00

## Options/Accessories

Part #	A&D Model #	Description	Price
102891	GX-02	USB option	\$155.00
97695	GX-04	Comparator output; factory installed only	\$365.00
97696	GX-06	Analog output; factory installed only	\$840.00
97697	GX-10	Glass breeze break for GX-200/400/600/800/1000	\$282.00
97698	GX-11	Glass breeze break for GX-2000/4000/6000/6100/8000	\$300.00
97699	GX-12	Animal weighing pan for GX-400/600/2000/4000/6100/6000/8000	\$185.00
97700	GX-13	Density determination kit for GX-200/400/600	\$640.00
97607	AD-1682	Rechargeable battery pack (external)	\$678.00
97608	AD-8920A	Universal remote display	\$270.00
97605	AD-100-2	Anti-theft device	\$73.00
97612	SW:128	Foot switch	\$75.00
97703	AX:073003691-S	Protective in-use cover for GX-200/400/600	\$22.00
97704	AX:073003692-S	Protective in-use cover for GX-2000/4000/6100/6000/8000	\$20.00
97649	TB:648	AC adapter (120V/220V)	\$43.00
151247	AD-1688	Data logger	\$304.00
158785	AD-8121B	Impact dot matrix statistical printer, cable included	\$891.00