

Standard Features

- IPX8 protection rating
- Front and rear dual display, 0.8in (20.5mm)
- Removable stainless steel platform cover
- Fast 0.5 second stabilization time
- SmarText™ interface
- Knife-proof keypad
- AC adapter and battery included

APPROVALS



Specifications

	V22XWE3T	V22XWE6T	V22XWE15T
Part#	102771	102772	102773
List Price	\$470.00	\$470.00	\$470.00
Capacity	3 kg	6 kg	15 kg
Resolution	0.5 g	1 g	2 g
Weigh Units	Kilograms, Pounds, Grams, Ounces, Pound and Ounce		
Operating Modes	Weigh, Checkweigh		
Construction	ABS plastic housing, stainless steel pan		
Protection Rating	IPX8		
Safe Overload	150% of capacity		
Stabilization Time	< 1 second		
Operating Temperature	14° F to 104° F (-10° C to 40° C)		
Pan Size	7.5x 9.5 in (242 x 190 mm)		
Dimensions	(W x D x H) 10.1 x 11.3 x 4.9 in (256 x 288 x 124 mm)		
Weight (Approx.)	8.6 lb (3.9 kg)		
Calibration	Digital external calibration		
Power	Universal AC adapter, 12VDC 0.7A internal rechargeable lead acid battery		
Battery Life	50 hours with 1 hour recharge time		
Warranty	One-year Limited Warranty		
Return Policy	OHAUS Standard Policy - restock fee may apply		

[^]Weighing Chamber

Part Number/Price

Part #	Model #	Description	Price
102771	V22XWE3T	3 kg x 0.5 g	\$470.00
102772	V22XWE6T	6 kg x 1 g	\$470.00
102773	V22XWE15T	15 kg x 2 g	\$470.00

Options/Accessories

Part #	Model #	Description	Price
33451	3369-10	Polypropylene Maxi-Scoop™ 10 dia x 2.5 in deep (25.4 dia x 6.4 cm deep) with pouring spout, weight 145 g	\$33.00
97250	80250400	Stainless steel scoop 11.9 x 7.4 x 1.7 in (30 x 18.7 x 4.3 cm)	\$59.00
100292	80250954	Stainless steel scoop 17.2 x 11 x 3.4 in (44 x 28 x 8.5 cm)	\$74.00
156237	46001812	Universal AC adapter	\$46.00
156235	46001780	Universal plug set	\$14.00