# DIGI® Bench Scale and Indicator Package



# **Standard Features**

- Large 0.8 in (20.3 mm) six-digit red LED or LCD display
- 115-230 VAC
- EPD and printer port for connecting to a PC or printer
- · Programmable print output strings
- Available in 150 lb/60 kg, 300 lb/150 kg, 500 lb/300 kg capacities
- Selectable unit of measure lb/kg/g/oz
- Carbon steel platform, stainless steel platter (STL)

## **APPROVALS**



Measurement Canada Approved

# Part Number/Price


Part #	Capacity	Platform Dimension	Est. Weight	Price
83303	150 lb (60 kg x 0.05 lb) (0.02 kg)	17 x 21 x 4.5 in	57 lb	\$940.00
83304	300 lb (150 kg x 0.1 lb) (0.05 kg)	17 x 21 x 4.5 in	57 lb	\$940.00
83305†	500 lb (300 kg x 0.1 lb) (0.1 kg)	17 x 21 x 4.5 in	57 lb	\$940.00


† Measurement Canada Approved

#### Options/Accessories

Part #	Description	Price
73381	4 in (100 mm) castors (four swivels, two with brakes)	

Drawing Dimensions					
Α	21 in	D	3.94 in		
В	24.6 in	E	23.9 in		
С	17 in	F	32.6 in		





# **Specifications**

#### Power:

Line voltages: 115-230

#### Frequency:

 $50\ \text{or}\ 60\,\text{Hz}$ 

### **Serial Output:**

EDP port: Full duplex RS-232

Printer port: Output-only RS-232 or active 20 mA

Both ports: 9600, 4800, 2400, 1200, 600, 300 bps; 7 or 8 data bits;

even, odd or no parity

#### Display:

0.8 in (20 mm), six-digit super red light emitting diode (LED) display, seven-segment digits

#### **Status Annunciators:**

Designators for: center of zero, stand still, gross, net center of zero, standstill, lb, kg, oz, g Battery, setpoint 1 and 2, HI-0K-LO, Hold

#### Keyboard:

Five-key flat membrane panel, tactile feel

#### **Operating Temperature:**

Legal: 14° F to 104° F (-10° C to 40° C) Industrial: 14° F to 122° F (-10° C to 50° C)

### Rating/Material:

Enclosure: heavy gauge ABS

#### Warranty:

One-year limited warranty

### **Scale Approvals:**

NTEP CC 02-111, Class III 5,000 d Measurement Canada AM-5393, Class III 5,000 d (500 lb/300 kg only)

#### **Indicator Approval:**

NTEP CC 03-059, Class III/IIIL 10,000 d Measurement Canada AM-5517, Class III/IIIHD