

DR300 Pocket Colorimeter

Applications

- Drinking Water
- Wastewater
- Power
- Industrial Water
- Field Use
- Beverage
- Food QC Lab



Proven past. Innovative future.

The DR300 maintains the Pocket Colorimeter legacy of reliability while providing state-of-the-art data transfer capability and connection to Claros*. Reduce data collection hassles, eliminate transcription errors, and ensure stronger compliance traceability.

Connected*

Optional Bluetooth connectivity allows you to safely transfer measurement data to your existing database or to Claros – Hach®'s Water Intelligence System – reducing errors and saving time by eliminating manual data entry.

Reliable

Rugged, waterproof (IP67) design withstands whatever conditions you encounter in the field (drops, extreme temperatures, rain and dirt) and still delivers years of dependable, accurate measurements.

Simple

Simple, intuitive operation reduces potential manual error, ensuring accurate measurement data you can trust, time after time. Larger display with improved backlight makes reading measurements in all conditions even easier.

**Claros connectivity currently available only in US, Canada and EU.*

Technical Data*

Source Lamp	Light emitting diode (LED)
Detector	Silicon photodiode
Enclosure Rating	IP67, waterproof at 1 m for 30 minutes
Wavelength	As specified by model, ± 2 nm
Spectral Bandwidth	15 nm filter bandwidth
Absorbance	0 - 2.5 Abs
Sample Cell Compatibility	1 cm (10 mL), 25 mm (10 mL)

Operating Conditions	0 - 50 °C (32 - 122 °F); 0 - 90% relative humidity (non-condensing)
Display	LCD with backlight
Power Supply	Four AAA alkaline batteries; approximate life is 5000 tests
Data Logger	Last 50 measurements
Weight	0.25 kg (0.55 lbs.)
Dimensions (H x W x D)	34 mm x 69 mm x 157 mm

*Subject to change without notice.

Parameters

Parameter	Range	Measurement Method
Aluminium	0.02 - 0.80 mg/L Al	Aluminon
Ammonia	0.01 - 0.80 mg/L NH ₃ -N	Salicylate
Bromine	0.05 - 4.50 mg/L Br ₂ 0.2 - 10.0 mg/L Br ₂	DPD
Chlorine, free ¹⁾ + total ^{1), 2)}	0.02 - 2.00 mg/L Cl ₂ 0.1 - 8.0 mg/L Cl ₂	DPD
Chlorine, free ¹⁾ + total ^{1), 2)} , MR	0.05 - 4.00 mg/L Cl ₂ 0.1 - 10.0 mg/L Cl ₂	DPD
Chlorine, pH	0.1 - 10.0 mg/L Cl ₂ 6.0 - 8.5 pH	DPD Phenol Red
Chlorine dioxide	0.05 - 5.00 mg/L ClO ₂	DPD/Glycine
Iron, Ferrover ²⁾	0.02 - 5.00 mg/L Fe	Ferrover
Iron, TPTZ	0.01 - 1.70 mg/L Fe	TPTZ
Manganese, HR ²⁾	0.2 - 20.0 mg/L Mn	Periodate Oxidation
Molybdenum	0.02 - 3.00 mg/L Mo 0.1 - 12.0 mg/L Mo	Ternary Complex
Monochloramine/ Free Ammonia	0.04 - 4.50 mg/L Monochloramine as Cl ₂ 0.02 - 0.50 mg/L Free Ammonia as NH ₃ -N	Indophenol
Nitrate	0.4 - 30.0 mg/L NO ₃ -N	Cadmium Reduction
Oxygen, dissolved	0.2 - 10.0 mg/L O ₂	HRDO
Ozone	0.01 - 0.25 mg/L O ₃ 0.01 - 0.75 mg/L O ₃	Indigo Trisulfonate
Phosphate ^{1), 2)}	0.02 - 3.00 mg/L PO ₄	Phosver 3
Zinc ²⁾	0.02 - 3.00 mg/L Zn	Zincon

¹⁾Method is USEPA accepted or approved for drinking water (additional steps may be required)

²⁾Method is USEPA accepted or approved for wastewater (additional steps may be required)

Note: Phenol Red colorimetric pH measurement is not accepted for regulatory reporting

Order Information

DR300 Pocket Colorimeters

The DR300 Pocket Colorimeter includes manual, sample cells, and a carrying case. Reagents can be purchased by contacting Hach or your Hach distributor.

- LPV445.97.00110** DR300 Pocket Colorimeter, Chlorine, Free + Total
- LPV445.97.01110** DR300 Pocket Colorimeter, Bromine
- LPV445.97.02110** DR300 Pocket Colorimeter, Nitrate
- LPV445.97.03110** DR300 Pocket Colorimeter, Dissolved Oxygen
- LPV445.97.04110** DR300 Pocket Colorimeter, Ozone
- LPV445.97.06110** DR300 Pocket Colorimeter, Phosphate
- LPV445.97.09110** DR300 Pocket Colorimeter, Zinc
- LPV445.97.10110** DR300 Pocket Colorimeter, Molybdenum, LR/HR
- LPV445.97.12110** DR300 Pocket Colorimeter, Chlorine & pH
- LPV445.97.15110** DR300 Pocket Colorimeter, Manganese, HR
- LPV445.97.16110** DR300 Pocket Colorimeter, Iron, TPTZ
- LPV445.97.22110** DR300 Pocket Colorimeter, Iron, Ferover
- LPV445.97.25110** DR300 Pocket Colorimeter, Aluminium
- LPV445.97.26110** DR300 Pocket Colorimeter, Monochloramine/Free Ammonium
- LPV445.97.40110** DR300 Pocket Colorimeter, Ammonium
- LPV445.97.51110** DR300 Pocket Colorimeter, Chlorine Dioxide
- LPV445.97.62110** DR300 Pocket Colorimeter, Chlorine, Free + Total, MR

Wavelength-specific DR300 Pocket Colorimeters

Program custom methods and calibrations on two channels.

- LPV445.97.50110** DR300 Pocket Colorimeter, 500 nm
- LPV445.97.52110** DR300 Pocket Colorimeter, 528 nm
- LPV445.97.60110** DR300 Pocket Colorimeter, 600 nm
- LPV445.97.65110** DR300 Pocket Colorimeter, 655 nm



Order Information

Accessories

2635300	SpecCheck secondary gel standard kit, LR Chlorine, DPD, 0-2.0 mg/L Cl ₂
2893300	SpecCheck secondary gel standard kit, Chlorine, DPD, 0-8.0 mg/L Cl ₂
2507500	SpecCheck secondary gel standard kit, Monochloramine/Free Ammonia, 0-4.50 mg/L Cl ₂ , 0-0.50 mg/L NH ₃ -N
2708000	SpecCheck secondary gel standard kit, Ozone, 0-0.75 mg/L O ₃
4674300	Batteries, AAA, Alkaline, 1.5 V, pk/4
4660200	Multitest kit case (22 x 17 x 15 cm), blue polypropylene
2427606	Sample cell, 1 inch round glass, 6 pcs
4864302	Sample cell, 1 inch round polystyrene, 2 pcs
2126102	Sample cell, 1cm round, pk/2 (unmatched, caps not included)

SpecCheck Ampule Standards are colored gels that simulate the color produced by the analytical procedure, for simple checks on instrument response. Each set includes a blank and three concentrations.

Be confident with Hach Service

Service Agreement: Hach provides on-site and in-factory repair, preventive maintenance, and calibration programs for your instruments to ensure reliability and instrument up-time. We have services to fit your specific needs.

DOC052.53.25023.Nov18

Hach World Headquarters: Loveland, Colorado USA

United States: 800-227-4224 tel 970-669-2932 fax orders@hach.com

Outside United States: 970-669-3050 tel 970-461-3939 fax int@hach.com

hach.com

Printed in U.S.A.

©Hach Company, 2019. All rights reserved.

In the interest of improving and updating its equipment, Hach Company reserves the right to alter specifications to equipment at any time.



Be Right™