iDimension® 100



iDimension 100 is designed for use on a workstation, table or bench in retail, office and shipping environments. This is the first Rice Lake Weighing Systems iDimension series product that provides all the necessary hardware for an out-of-the-box solution.

Standard Features

- Dimensions parcels in less than 2/10ths of a second
- Includes USB operator display (no PC interface required) for:
 - Operator configuration and zero height feature
 - Displays dimensions, status and weight if scale is directly attached
- · Requires virtually no special alignment or special handling while placing an object under the work area
- Low resolution overhead image available in .jpg or .bmp format, used for verification, tracking and claim protection
- Converts irregular shapes like cylinders, spheres, tubes, polybags and uneven shapes to 0.5 in NTEP Certified cubed dimensions
- Dimensions flats, less than 1.2 in height, with the use of a connected scale or flat detection located on the iDimension 100's base plate
- · Automatic or manual operator modes:
 - Automatic operating mode is the standard out of the box configuration which allows you to move the parcel under the work area without the press of a button
 - Manual operating mode is for use with custom or 3rd party software interface that can be triggered by an attached bar code scanner, software function or demo display when interfaced to a PC
- Interfaces with most NTEP Certified shipping scales and Rice Lake BenchPro™ Series
- Quick assembly: Includes all necessary tools and components for a complete out-of-the-box solution and immediate use with minimal operator training
- No additional installation of software required on your PC. When connected to a network, the embedded firmware provides access to additional displays and configuration parameters
- Connect to a PC and communicate directly over the network via static IP or DCHP.
 Use our open web service interface to take advantage of additional built in features like;
 a low resolution image of each dimension weight and more
- Contact the factory for an up-to-date listing of 3rd party shipping and inventory management systems compatible with the iDimension Series
- UPS Worldship® ready Simply connect the iDimension Series to a USB Hub. Connect your compatible scale and cable assemblies from the USB hub to the PC's RS-232 or USB port, cables purchased separately.

Specifications

Physical Dimensions:

Length: 25 in (63.5 cm) Width: 14.25 in (36 cm) Height: 63.8 in (162 cm) Weight: 28.5 lb (13 kg)

Power Requirements:

Single power source 110-240V external power supply, US power cord

Object Colors:

All opaque packaging; some variances may occur with glossy surfaces or shrink wrap

Measurement Surfaces:

Level tables, scales, roller balls and roller conveyors. The background should have a contrasting color for items to be dimensioned. Avoid polished or glossy surfaces like stainless steel weight platters for best performance

Operating Temperature:

41°F to 104°F (5°C to 40°C)

Humidity:

Non-condensing

Mechanical Environment Class:

M1

Electromagnetic Class:

E1

I/O Ports:

(1) USB type A port (interface to scale) (1) 10/100/100BASE-T Ethernet port (interface to PC/Network)

Package Contents:

iDimension 100, assembly, tools, calibration object, USB display and US power cord

Warranty:

One-year limited warranty

Approvals:

NTEP CE

FCC

OIML

MID

NTEP Certified Measurement Ranges - Cube

| | Min (In) | Max (In) | Division (in) |
|--------|----------|----------|---------------|
| Length | 5.6 | 48 | 0.2 |
| Width | 5.6 | 28 | 0.2 |
| Height | 2.4 | 28 | 0.2 |

NTEP Certified Measurement Ranges - Irregular

| | Min (In) | Max (In) | Division (in) |
|--------|----------|----------|---------------|
| Length | 6 | 48 | 0.5 |
| Width | 6 | 28 | 0.5 |
| Height | 6 | 28 | 0.5 |

Note: Minimum and maximum NTEP Certified capabilities do not reflect non-NTEP Certified performance specifications. Contact factory for more assistance.

OIML/MID Certified Measurement Range - Cube

| | Min (CM) | Max (CM) | Division (CM) | | |
|--------|----------|----------|---------------|--|--|
| Length | 12 | 80 | 0.5 | | |
| Width | 10 | 60 | 0.5 | | |
| Height | 5 | 70 | 0.5 | | |
| 0R | | | | | |
| Length | 12 | 120 | 0.5 | | |
| Width | 10 | 75 | 0.5 | | |
| Height | 5 | 30 | 0.5 | | |

Part Numbers/Price

| Part # | Description | Est. Weight | Price | | |
|---------------------|--|-------------|------------|--|--|
| 170654 | iDimension 100 | 44 lb | \$7,495.00 | | |
| 181154 | iDimension system (UPS Worldship Compatible), includes scale & USB hub kit | | \$8,425.00 | | |
| Options/Accessories | | | | | |
| 184585 | BP 1214-75S 150 x 0.05 lb USB shipping scale with mild steel shroud | - | \$645.00 | | |
| 180771 | Kit, USB Hub* | - | \$385.00 | | |
| 176307 | QuickScan QD2131 bar code scanner with USB cable | 4 lb | \$258.00 | | |
| 179081 | Kit, Cable Assy. PC Interface, RS-232 | _ | \$95.00 | | |
| 179083 | Kit, Cable Assy. PC Interface, USB | - | \$105.00 | | |

^{*}USB hub kit and scale required for UPS WorldShip Compatibility