Specifications

Interface:

Built-in USB and serial interface; built-in USB and Ethernet, or built-in USB and Wireless LAN

Data Buffer:

Receive buffer: Selectable as 45 bytes or 4 KB using the DIP switch

Paper Dimensions:

80 mm: 3.13 in x 3.27 in diameter or 58 mm: 2.26 in x 3.27 in diameter

Weight:

1.6 kg (3.53 lb)

Color:

Gray

Paper Thickness:

55-80 µm

Print Speed:

300 mm/s {11.81 in/s}

Safety Standards:

EMI: FCC/ICES-003 Class A

Safety standards: UL60950-1/CSA C22.2 No.60950-1

Power:

24 VDC ±7%

Power Consumption:

Approx. 1.8A (mean)

Temperature:

Operating : 31° F to 113° F (5° C to 45° C) Storage: 14° F to 122° F (-10° C to 50° C)

Reliability:

MTBF: 360,000 hours MCBF: 70 million lines Overall Dimensions:

(W x D x H): 5.71 x 7.68 x 5.83 in (145 x 195 x

148 mm)

Warranty: One-year warranty



Standard Features

- · High-speed printing of both text and graphics (up to 300 mm/second)
- True grayscale image printing
- · Best-in-class reliability
- · Convenient drop-in paper loading, auto cutter and status LEDs
- ENERGY STAR® qualified
- Accommodates 58 mm or 80 mm paper roll
- · Paper saving print features
- Improved cover protects from dust and debris
- OS support for Microsoft[®] Windows[®] 7, Vista, XP, 2000; Mac OS X v10.4, v10.5, v10.6 (Power PC/Intel Processor) and Linux

Part Number/Price

Part #	Description	Price
117233	TM-T88V, RS-232 and USB, PS-180 Power supply	\$580.00
117234	TM-T88V, USB and Wireless Ethernet, 802.11 B PS-180 Power supply	\$825.00

Options/Accessories

Part #	Description	Price
23112	Power supply, PS-180	\$110.00
69917	One-ply thermal, (W) 3.125 in (75.44 mm, 2.97 in dia.) 7/16 core 230 ft	\$5.00
83007	Parallel Option connect-it cartridge	\$62.00
15568	25-Pin D-sub male to 25-Pin D-sub male RS-232 serial interface cabl	\$65.00
15547	Blunt end, 25-Pin D-sub male RS-232 serial interface (Rice Lake indicators)	\$65.00
Consult	Custom RS-232 serial cable	Consult
79074	USB-A (male) to USB-B (male) cable	\$30.00
167545	TM88IV and V printhead	\$125.00