

# Minebea Intec Midrics® 1 and 2 Series

Digital Weight Indicator

## Specifications

### Load Cell Connection:

Excitation voltage 8.4 V  
4 or 6 conductor

### Power Requirements:

100 - 240 VAC (-15/10) 50-60 Hz, Max 17 W/23 VA

### Power Cord:

3 m

### Housing:

304 stainless steel enclosure, IP65

### Dimensions:

(W x D x H): 9 1/3 x 6 1/2 x 3 3/4 in (238 x 165 x 94 mm)

### Operating Temperature:

14° F to 104° F (-10° C to 40° C)

### Net Weight:

5 lb (2.3 kg)

### Warranty:

Two-year limited warranty

### Approvals:

NTEP Class III



## Standard Features

- Backlit 14-segment, 20 millimeter LCD display
- 304 stainless steel enclosure, IP65 rated
- Wall-mount bracket
- Time and date
- RS-232

## Midrics 2 Additional Features

- Numerical keyboard
- Applications:**
- Weighing
  - Counting
  - Checkweighing
  - Sorting (3 or 5 classes)
  - Totalizing
  - Net-total
  - Animal weighing
  - Weighing in percent
  - Neutral measurement

## Options

- RS-232
- 4-20 mA

## Part Number/Price

RLWS PN	Minebea PN	Description	Price
155855	MIS1UR-V1	Midrics 1, wall bracket	\$615.00
155857	MIS1U-L9	Midrics 1, wall bracket, internal battery pack	\$1,073.00
155856	MIS2UR-V2	Midrics 2, wall bracket	\$695.00
155859	MIS2U-L9	Midrics 2, wall bracket, internal battery pack	\$1,190.00

## Options/Accessories

RLWS PN	Minebea PN	Description	Price
103044	YDA01M-20MA	Analog current output, 0-20 mA, 4-20 mA, 0-10 V (16-bit)	\$443.00
155805	YCC01-USBM2	Connecting cable from RS-232 to USB connector, 2 m	\$254.00
155806	YCC02-D25F6	Connecting cable for accessories 25-Pin D-SUB female	\$254.00
Consult	YAS03-M1	Panel mount option	Consult

# Minebea Intec Combics 1

## Digital Weight Indicators



### Application Note:

Combics 1 indicator is designed for use with both Combics and IF series platforms. However, various accessories may differ and are application dependent.

### Standard Features

- IP protection rating, IP44, IP69K
- Amber backlit LCD display, .8 in
- External calibration routine
- RS-232C
- On/Off, Zero, Tare, Print/Data Key
- Function keys for: Gross/net toggle; three-way unit toggle; 10X higher resolution toggle
- Automatic tare feature
- One scale connection

### Part Number/Price

RLWS PN	Minebea PN	Description	Est. Weight	Price
102396	CAISL1-U	IP44 protection rated	7.5 lb	\$1,074.00
102398	CAIS1-U	IP69K protection rated	7.5 lb	\$1,409.00
115668	CAISL1-UV1	IP44, IS base controller	7.5 lb	\$1,562.00
115671	CAIS1-UV1	IP69K, IS base controller	7.5 lb	\$1,714.00

### Options/Accessories

RLWS PN	Minebea PN	Description	Price
105607	YDH02CISUS	Wall mount bracket	\$75.00
171727	YDH12CWSUS	Bench mount bracket	\$75.00
156440	YDH01CWSUS	Post mount assembly for 10 x 10 in platforms, 13 in high	\$190.00
156441	YDH02CWSUS	Post mount assembly for 12 x 12 in platforms, 19 in high	\$205.00
156442	YDH03CWSUS	Post mount assembly for 18 x 18 in platforms, 29 in high	\$235.00
103049	YAS02CI	24 V industrial power supply	\$249.00
162640	YD002C-ETH	Ethernet TCP/IP	\$770.00
155826	YD002C-A0	Analog output, 0-20 mA, 4-20 mA, 0-10 V	\$770.00
<b>Cables</b>			
155804	YCC05-001M2	RS-232 9/25-Pin D-Sub female, 1.5 m, IP44	\$92.00
155805	YCC01-USBM2	RS-232 to USB connector, 2 m IP44	\$254.00
155806	YCC02-D25F6	RS-232 open to 25 D-Sub female	\$254.00

### Specifications

#### Load Cell Connection:

4 or 6 wire

#### Excitation Voltage:

9V

#### Power Requirements:

120-240 VAC, 17 W/23 VA maximum

#### Housing:

AISI 304 stainless steel

#### Dimensions:

(W x D x H): 11.9 x 7.4 x 3.5 in

#### Operating Temperature:

14° F to 104° F (-10° C to 40° C)

#### Net Weight:

5 lb

#### Warranty:

Two-year limited warranty

Accessories: One-year limited warranty

# Minebea Intec Combics 2

## Digital Weight Indicators

### Specifications

- Load Cell Connection:**  
4 or 6 wire
- Excitation Voltage:**  
9 V
- Power Requirements:**  
120-240 VAC, 17 W / 23 VA maximum
- Housing:**  
AISI 304 stainless steel
- Dimensions:**  
(W x D x H): 11.9 x 7.4 x 3.5 in
- Operating Temperature:**  
14° F to 104° F (-10° C to 40° C)
- Net Weight:**  
5 lb
- Warranty:**  
Two-year limited warranty on indicator  
Accessories: One-year limited warranty



*Application Note:*  
Combics 2 and Combics 3 indicators are designed for use with both Combics and IF series platforms. However, various accessories may differ and are application dependent.

*Applications Software Pre-installed:*  
Counting, checkweighing, differential weighing, percentage weighing, gross-net-tare, sorting, net-total, animal weighing, averaging, totalizing

### Standard Features

- Choice of IP protection rating (IP44, IP69K)
- Amber backlit LCD display, .8in, 13 segment
- External calibration routine
- RS-232C
- On/Off, Zero, Tare, Print/Data Keys
- Function keys for: Gross/net toggle; three-way unit toggle; 10X higher resolution toggle
- Numeric keypad with two IDs for entering identifier codes and preset tare
- Info key for quick and easy display of tare input and ID codes
- Date/time fully integrated
- GMP compliant printable record
- NICE Label Express FlexiPrint compatible
- Platform toggling and four function keys
- Three built-in LED checkweighing lights
- Bar graph weighing range indicator
- Application data and totalization memory stored in battery-backed RAM
- Optional barcode scanner for preset tare, reference weight and ID entry
- Stored customer specific data records
- Optional two scale connections, analog or digital

### Part Number/Price

RLWS PN	Minebea PN	Description	Est. Weight	Price
102402	CAISL2-U	IP44 protection rated	7.5 lb	\$1,336.00
102404	CAIS2-U	IP69K protection rated	7.5 lb	\$1,679.00
115670	CAISL2-UV1	IP44, IS base controller	7.5 lb	\$1,818.00
115673	CAIS2-UV1	IP69K, IS base controller	7.5 lb	\$2,071.00

### Options/Accessories

RLWS PN	Minebea PN	Description	Price
105607	YDH02CISUS	Wall mount bracket	\$75.00
171727	YDH12CWSUS	Bench mount bracket	\$75.00
156440	YDH01CWSUS	Post mount assembly for 10 x 10 in platforms, 13 in high	\$190.00
156441	YDH02CWSUS	Post mount assembly for 12 x 12 in platforms, 19 in high	\$205.00
156442	YDH03CWSUS	Post mount assembly for 18 x 18 in platforms, 29 in high	\$235.00
103049	YAS02C1	24 V industrial power supply	\$249.00
162640	YD002C-ETH	Ethernet TCP/IP	\$770.00
155826	YD002C-A0	Analog output, 0-20 mA, 4-20 mA, 0-10 V	\$770.00
<b>Cables</b>			
155804	YCC05-001M2	RS-232 9/25-Pin D-Sub female, 1.5 m, IP44	\$92.00
155805	YCC01-USBM2	RS-232 to USB connector, 2 m IP44	\$254.00
155806	YCC02-D25F6	RS-232 open to 25 D-Sub female	\$254.00

# Minebea Intec Combics 3

Digital Weight Indicators

*Combics 2 and Combics 3 indicators are designed for use with both Combics and IF series platforms. However, various accessories may differ and are application dependent.*

*Applications Software Pre-installed:*

*Counting, checkweighing, differential weighing, percentage weighing, gross-net-tare, sorting, net-total, animal weighing*

*Custom Applications Packages:*

*Single component batching BASIC*

*Single component batching PRO*



## Standard Features

- IP protection rating (IP44, IP69K)
- Amber backlit LCD display
- On/Off Zero, Tare, Print/Data Keys
- Function keys for: Gross/net toggle; three-way unit toggle; 10X higher resolution toggle
- Keypad with two IDs for entering identifier codes and preset tare
- Info key for quick and easy display of tare input and ID codes
- Date/time fully integrated
- GMP/GLP printable record
- Platform toggling and four function keys
- Three built-in LED checkweighing lights
- Bar graph weighing range indicator
- Application data and totalization memory stored in battery-backed RAM
- Optional barcode scanner for preset tare, reference weight and ID entry
- Stored customer-specific data records
- Key for toggling between weighing applications, and five soft keys with text-supported user guidance
- Input functions for entering up to four alphanumeric ID texts

## Part Number/Price

RLWS PN	Minebea PN	Description	Est. Weight	Price
102405	CAISL3-U	IP44 protection rated	7.5 lb	\$1,787.00
Consult	CAISL3-UV1	IP44, IS base controller	7.5 lb	\$2,121.00
102407	CAIS3-U	IP69K protection rated	7.5 lb	\$2,121.00
115674	CAIS3-UV1	IP69K, IS base controller	7.5 lb	\$2,447.00

## Options/Accessories

RLWS PN	Minebea PN	Description	Price
105607	YDH02CISUS	Wall mount bracket	\$75.00
171727	YDH12CWSUS	Bench mount bracket	\$75.00
156440	YDH01CWSUS	Post mount assembly for 10 x 10 in platforms, 13 in high	\$190.00
156441	YDH02CWSUS	Post mount assembly for 12 x 12 in platforms, 19 in high	\$205.00
156442	YDH03CWSUS	Post mount assembly for 18 x 18 in platforms, 29 in high	\$235.00
103049	YAS02C1	2 V industrial power supply	\$249.00
155826	YD002C-A0	Analog output, 0-20 mA, 4-20 mA, 0-10 V	\$770.00
162640	YD002C-ETH	Ethernet TCP-IP	\$770.00
<b>Cables</b>			
155804	YCC05-001M2	RS-232 9/25-Pin D-Sub female, 1.5 m, IP44	\$92.00
155805	YCC01-USBM2	RS-232 to USB connector, 2 m IP44	\$254.00
155806	YCC02-D25F6	RS-232 open to 25 D-Sub female	\$254.00

## Specifications

### Load Cell Connection:

4 or 6 wire

### Excitation Voltage:

9V

### Power Requirements:

120-240 VAC, 17 W / 23 VA maximum

### Housing:

AISI 304 stainless steel

### Dimensions:

(W x D x H): 11.9 x 7.4 x 3.5 in

### Operating Temperature:

14° F to 104° F (-10° C to 40° C)

### Net Weight:

5 lb

### Warranty:

Two-year limited warranty

Accessories: One-year limited warranty