

# NEW CAPACITIES AVAILABLE

SARTORIUS

**Cubis®**

Ultra-Micro/Micro Balances

Capacity: 1.1 g-5.1 g    Readability: 0.0001 mg-0.005 mg

BALANCES



The modular system offers you a choice of display and control units, weighing modules and draft shields

## Standard Features

- Module design
- User configurable and custom designed to meet changing applications
- Meets advanced Pharma compliance including user/password management for security, audit trail function logs, and integrated alibi memory
- Q-guide enables tasks and work
- Electrically conductive coating on glass panels of draft shield
- RS-232 and USB communication
- Choice of Display
- MSE-Large, 19mm LCD display segments and easy menu system
- MSU-Monochrome graphic display, positive click on keys to activate functions, Ethernet, and SD card reader
- MSA-TFT color touchscreen, Ethernet, and SD card reader

## Specifications

	2.7S-000-DM^	2.7S-000-DF^	6.6S-000-DM^	6.6S-000-DF^	3.6P-000-DM^	66S-000-DH	66P-000-DH	36S-000-DH	36P-000-DH
<b>MSE*</b>	Part # 126044	126046	126048	126049	126052	-	-	-	-
	List Price \$33,610.00	\$34,530.00	\$26,215.00	\$27,135.00	\$19,990.00	-	-	-	-
<b>MSU**</b>	Part # 126043	126045	126047	126050	126051	-	-	-	-
	List Price \$34,740.00	\$35,660.00	\$27,345.00	\$28,265.00	\$21,120.00	-	-	-	-
<b>MSA***</b>	Part # 126034	126039	126040	126041	126042	186390	186391	186392	186394
	List Price \$35,370.00	\$36,290.00	\$27,975.00	\$28,895.00	\$21,750.00	\$34,435.00	\$31,565.00	\$29,835.00	\$25,795.00
Capacity	2.1 g	2.1 g	5.1 g	5.1 g	1.1 g/2.1 g/3.1 g	61 g	12 g/61 g	31 g	6 g/31 g
Resolution	0.0001 mg	0.0001 mg	0.001 mg	0.001 mg	0.001 mg/ 0.002 mg/0.005 mg	0.001 mg	0.001 mg/0.01 mg	0.001 mg	0.001/0.01 mg
Weighing Modes	Grams, Kilograms, Carats, Pounds, Ounces, Troy Ounces, Hong Kong Taels, Singapore Taels, Grains, Pennyweights, Milligrams, Parts per Pound, Chinese Taels, Momme, Austrian Carats, Tola, Baht, Mesghal								
Operating Modes (*)	Counting, Checkweighing, Percent Weighing, Unit Toggle, Animal Weighing, Net Total, Formulation, Statistics, Calculation, Timer, Backweighing, Density Determination, Memory (300), Diameter Determination								
Repeatability	0.25 µg		0.001 mg		0.003/0.004/0.005 mg	0.0015 mg/ 0.004 mg	0.002 mg/0.010 mg	0.0015 mg/ 0.002 mg	0.0015 mg/ 0.008 mg
Linearity	0.9 µg		4 µg		4 µg	0.020 mg	0.020 mg	0.015 mg	0.015 mg
Stabilization Time	7 seconds		5 seconds		5 seconds	3.5 seconds	3.5 seconds	3.5 seconds	3.5 seconds
Operating Temperature	41° F to 104° F (5° C to 40° C)								
Weighing Chamber (DE)	2.75 in (70 mm) H	0.6 in (15 mm) H	2.75 in (70 mm) H	0.6 in (15 mm) H	2.75 in (70 mm) H	7.13 in (181 mm)	7.13 in (181 mm)	7.13 in (181 mm)	7.13 in (181 mm)
Pan Size	Ø 0.8 in (20 mm)	Ø 1.9 in (50 mm) dia	Ø 1.2 in (30 mm)	Ø 1.9 in (50 mm)	Ø 1.2 in (30 mm)	1.18 in/1.97 in (30 mm/50 mm)	1.18 in/1.97 in (30 mm/50 mm)	1.18 in (30 mm)	1.18 in (30 mm)
Dimensions	192 mm x 323 mm x 88 mm								
Weight (Approx.)	17 lb								
Est. Ship Weight	28 lb				40 lb				
Calibration Weight	2 g		5 g		3 g	50 g (E2)	50 g (E2)	20 g (E2)	20 g (E2)
Power	100 - 240V Power Supply								
Warranty	Two-year Limited Warranty								
Return Policy	Sartorius Standard Policy - restock fee may apply								

^Weighing Chamber

\* MSE Large LCD display and easy-to-use menu system

\*\* MSU Monochrome graphic display, positive click on keys to activate functions, Ethernet and SD card reader

\*\*\* MSA TFT color touchscreen, Ethernet and SD card reader

DF-SS manual draft shield for weighing filters

www.ricelake.com | Phone: 800-472-6703

RICELAKE

## Part Number/Price

Part #	Model #	Description	Price
126044*	MSE2.7S-000-DM	2.1 g x 0.0001 mg	\$33,610.00
126043**	MSU2.7S-000-DM	2.1 g x 0.0001 mg	\$34,740.00
126034***	MSA2.7S-000-DM	2.1 g x 0.0001 mg	\$35,370.00
126046*	MSE2.7S-000-DF	2.1 g x 0.0001 mg	\$34,530.00
126045**	MSU2.7S-000-DF	2.1 g x 0.0001 mg	\$35,660.00
126039***	MSA2.7S-000-DF	2.1 g x 0.0001 mg	\$36,290.00
126048*	MSE6.6S-000-DM	6.1 g x 0.001 mg	\$26,215.00
126047**	MSU6.6S-000-DM	6.1 g x 0.001 mg	\$27,345.00
126040***	MSA6.6S-000-DM	6.1 g x 0.001 mg	\$27,975.00
126049*	MSE6.6S-000-DF	6.1 g x 0.001 mg	\$27,135.00
126050**	MSU6.6S-000-DF	6.1 g x 0.001 mg	\$28,265.00
126041***	MSA6.6S-000-DF	6.1 g x 0.001 mg	\$28,895.00
186390***	MSA66S-000-DH	61 g x 0.001 mg	\$34,435.00
186391***	MSA66P-000-DH	12 g/61 g x 0.001 mg/0.01 mg	\$31,565.00
186392***	MSA36S-000-DH	31 g x 0.001 mg	\$29,835.00
186394***	MSA36P-000-DH	6 g/31 g x 0.001 mg/0.01 mg	\$25,795.00
126052*	MSE3.6P-000-DM	1.1 g/2.1 g/3.1 g x 0.001 mg/0.002 mg/0.005 mg	\$19,990.00
126051**	MSU3.6P-000-DM	1.1 g/2.1 g/3.1 g x 0.001 mg/0.002 mg/0.005 mg	\$21,120.00
126042***	MSA3.6P-000-DM	1.1 g/2.1 g/3.1 g x 0.001 mg/0.002 mg/0.005 mg	\$21,750.00

## Options/Accessories

Part #	Model #	Description	Price
112261	YDP20-OCE	Data printer with statistics and time/date functions (included cable fits RS-232)	\$1,120.00
31103	6906937	Paper for data printer, 5 pack	\$49.00
31106	6906918	Replacement ribbon for data printer	\$54.00
Consult	IB	Bluetooth® wireless interface (factory installed)	Consult
Consult	IP	Additional RS-232, 9-Pin connection with PS2 port (factory installed)	Consult
152036	—	Multi-range power supply, does not include line cord	\$102.00
156908	6900900	Power cord, 220 V (EU)	\$41.00

\*Large LCD display and easy-to-use menu system

\*\*Monochrome graphic display, positive click on keys to activate functions, Ethernet and SD card reader

\*\*\*TFT color touchscreen, Ethernet and SD card reader