

Datalogic® PowerScan® RF PM9300 Series

Specifications

Dimensions:

Scanner (H x L x W): 8.4 x 4.5 x 2.8 in
(212 x 109 x 71 mm)
Base Station (H x L x W): 10.5 x 3.5 x 2.5 in
(266.7 x 88.9 x 63.5 mm) (width is 4.2 in/106.68 mm
including mounting knobs.)

Weight:

Scanner: 14.2 oz (405 g)
Base Station: 16 oz (454 g)

Display:

LCD: 6 lines x 21 characters

Light Source:

VLD between 630-380 nm

Base Station:

US: 110V ±10%, 60 Hz

Communications:

Host: RS232 with DB9 S, P/S and 12 ft cable
KBW (keyboard wedge) with P/S and 6 M Din,
coiled cable 12 ft
USB, 12 ft coiled cable

Frequency Range: (varies by country)

915 MHz

Operating Temperature:

-4° F to 122° F (-20° C to 50° C)

Storage Temperature:

-40° F to 158° F (-40° C to 70° C)

Ingress Protection Rating:

Scanner: IP65
Base station: IP64

Humidity:

0-95%

Drop Resistance:

2 m

Battery Type:

Li-Ion 2150 mAh

Electrical:

Complies to C-CSA-US
(60950 Canada and USA)

Warranty:

Three-year limited warranty



Standard Features

- IP65 rating
- Wireless operation
- Operates up to 10 hours on a single charge
- Scanner and base station are IP64
- Datalogic green spot for good read feedback
- Polycarbonate molded with rubber
- Multi-point operation allows for multiple scanner communications to a single base station

Part Number/Price

Part #	Description	Weight	Price
182778	PowerScan RF scanner with battery, SR, 910 MHz for RS-232 keyboard wedge wand emulation interfaces (requires cable and base station)	4 lb	\$1,050.00
182779	PowerScan RF base station, 910 MHz for RS-232, keyboard wedge/wand	5 lb	\$455.00
82281	PowerScan Quick Scan US, AC power adapter	3 lb	\$30.00

Options/Accessories

Part #	Description	Price
104969	Cable, wedge, Y, six-pin mini DIN, five-pin D/N, universal adapter cable	\$50.00
108217	Cable, RS-232, nine-pin D-sub, 8 ft	\$70.00