# MSI-9750A CellScale<sup>™</sup> RF Portable Indicator



# **Standard Features**

- · Compatible with MSI-6260CS, MSI-9300 and MSI-9000 CellScale
- 1.4 x 2.6 in (36 x 67 mm), eight line, 21 character LCD display
- 2.4 GHz spread spectrum transceiver
- Power supply: six cell NiMH battery pack
- · Charger board: SMD NiMH fast charge (charges battery pack in two hours or less)
- RS-232 data I/0
- · Real time clock
- NEMA Type 3, IP54 enclosure
- AC adaptor/battery charger; 90-264 VAC, 47-63 Hz (NA plug standard)

# Part Number/Price

Part #	MSI Part #	Description	Capacity	Resolution	Est. Weight	Price
138486	502541-0001	MSI-9750 RF portable indicator	N/A	N/A	2.2 lb (1 kg)	\$1,830.00

# **Options/Accessories**

Part #	MSI Part #	Description	Est. Weight	Price				
Accessories								
143709	12431	Replacement NiMH battery pack	1 lb (0.45 kg)	\$121.00				
139484	503441-0001	AC adaptor/battery charger input, 90–264 VAC, 47–63 Hz (NA plug standard)	1 lb (0.45 kg)	\$100.00				
143912	12674	Battery charger, 12 VDC auto plug	1 lb (0.45 kg)	Consult				
139485	503441-0002	AC adaptor/battery charger, EU plug	1 lb (0.45 kg)	Consult				

# **Specifications**

### Enclosure:

NEMA Type 3, IP54, Rugged Molded PVC, O-ring gasketed.

#### Dimensions:

4.6 in x 10.3 in x 2.4 in (117 x 262 x 60.5 mm)

#### Weight:

2.2 lb (1 kg)

## Keypad:

24 keys–11 key alphanumeric, seven control keys and six user programmable keys. Password protected with lock feature

#### Display:

1.4 in x 2.6 in (36 mm x 67 mm) backlight LCD capable of 8 lines, 21 characters each. Backlight selectable On, Off or Automatic. Red/green LED battery charging indicator. Real time clock

#### Power:

**Approvals** 

Rechargeable six NiMH six cell battery pack

(AC adaptor/battery charger input included) AC adaptor/battery charger; 90-264 VAC, 47-63 Hz (NA

plug standard)

Charger board: SMD NiMH fast charge (charges battery pack in two hours or less

## **Operating Time:**

Up to eight hours typical use. Selectable automatic shut off for battery conservation

#### **Operating Temperature:**

-4° F to 158° F (-20° C to 70° C)

# Radio Link:

FHSS at 2.4 GHz (up to 64 network selections) Compatible with MSI-6260CS, MSI-9300 and MSI-9000 CellScale

## **Radio Effective Range:**

Typically 500 ft (150 m) indoors, 1,000 ft (300 m) outdoors with standard antennas

## **RFI/EMI Shielding:**

Exceeds NIST HB44 and CE standards

#### **Connectors:**

Charger Input: Standard 2.5 mm coaxial cable; RS-232 Data I/0: Standard DB-9 male

## Warranty:

One-year limited

# Approvals:

NTEP CC 05-077