

CW-90B

Light-capacity Bench Scales



Specifications

- Load Cell, NTEP Certified:**
Aluminum and environmentally sealed
- Output Impedance:**
350 Ω
- Maximum Overload:**
180 to 200% depending on capacity
- Overload Protection:**
Five-point, independently adjusted
- Cable Length:**
34 in or 10 ft
- Compensated Temperature Range:**
14° F to 104° F (-10° C to 40° C)
- Warranty:**
Two-year limited warranty
- Approvals:**
NTEP CC 95-072, Class III 5,000 d
Measurement Canada AM-5082, Class III 5,000 d

Standard Features

- 304 stainless steel construction
- Five-point overload protection
- Specially designed adjustable support feet provide exceptional traction and will not scratch surfaces
- Aluminum environmentally sealed load cell

APPROVALS



Measurement
Canada
Approved



Part Number/Price

Part #	Platform Capacity	Dimensions	Est. Weight	Price
10 ft cable	34 in cable			
112599	106137 5 lb (2.5 kg)	10 x 10 x 4.25 in	14 lb	\$640.00
112601	106138 10 lb (5 kg)	10 x 10 x 4.25 in	14 lb	\$640.00
112603	106139 25 lb (12.5 kg)	10 x 10 x 4.25 in	14 lb	\$640.00
112605	106140 25 lb (12.5 kg)	12 x 12 x 4.25 in	17 lb	\$720.00
112607	106141 50 lb (25 kg)	12 x 12 x 4.25 in	17 lb	\$720.00
112609	106142 100 lb (50 kg)	12 x 12 x 4.25 in	17 lb	\$720.00

Options/Accessories

Part #	Description	Price
N/A	Ball transfer and roller conveyor top	See end of section for details
112044	12 in column for IQ plus® 210, 320IS (without battery option), 320IS plus (without battery option), IQ plus® 390-DC, IQ plus® 590-DC, 420 plus®, CW-90, CW-90X and 480 Legend	\$135.00
112045**	18 in column for IQ plus® 210, 320IS (without battery option), 320IS plus (without battery option), IQ plus® 390-DC, IQ plus® 590-DC, 420 plus®, CW-90, CW-90X and 480 Legend	\$180.00

** Not recommended for use with scale bases smaller than 12 x 12 in

Drawing Dimensions

10 in x 10 in			
A	4.25 in (107.95 mm)	C	10.37 in (263.40 mm)
B	10.37 in (263.40 mm)		
12 in x 12 in			
A	4.25 in (107.95 mm)	C	12.37 in (314.20 mm)
B	12.37 in (314.20 mm)		

