

Secura
High Level

Standard Features

- Simple, color capacitive touch with swipe technology
- Monolithic and strain gauge technology
- Aluminum die-cast base, ABS housing
- Front level bubble
- Mini-USB
- Weigh below hook

Quintix and Secura Additional Features

- isoCAL/fully automatic, external calibration
- GLP conformance with built-in time and date
- Time and date

Secura Additional Features

- Internal calibration
- Opto-electronic leveling system
- Sqmin safety program
- Analytical draft support ring

Specifications

Practum	612-1S	1102-1S	2102-1S	n/a	n/a	5101-1S	5100-1S
Part Number	153987	153988	153989	N/A	N/A	153991	153990
List Price	\$1,065.00	\$1,180.00	\$1,235.00	N/A	N/A	\$1,255.00	\$970.00
Quintix	612-1S	1102-1S	2102-1S	3102-1S	5102-1S	5101-1S	5100-1S
Part Number	153998	153999	154000	154001	154003	154004	154002
List Price	\$1,690.00	\$1,915.00	\$2,135.00	\$2,365.00	\$2,930.00	\$1,690.00	\$1,350.00
Secura	N/A	1102-1S	2102-1S	3102-1S	5102-1S	N/A	N/A
Part Number	N/A	154010	154011	154012	154013	N/A	N/A
List Price	N/A	\$2,230.00	\$2,650.00	\$2,865.00	\$3,290.00	N/A	N/A
Capacity	610g	1,100g	2,100g	3,100g	5,100g	5,100g	5,100g
Resolution	0.01g	0.01g	0.01g	0.01g	0.01g	0.1g	1.0g
Repeatability	±10mg	±10mg	±10mg	±10mg	±10mg	0.1g	1.0g
Linearity ±	30mg (20mg Quintix & Secura)	30mg (20mg Quintix & Secura)	30mg (20mg Quintix & Secura)	20mg	20mg	0.3g (0.2g Quintix)	3.0g (2.0g Quintix)
External Calibration Weight	500g	1000g	2,000g		5,000g		
Weighing Modes	Gram, Kilogram, Carat, Pound, Ounce, Troy Ounce, Hong Kong, Tael, Singapore Tael, Taiwan Tael, Grain, Pennyweights, Milligram, Parts per Pound, China Teal, Mommies, Austrian Carat, Tola Baht, Mesghal and Newton						
Applications	Mass Unit Conversion, Counting, Percent Weighing, Averaging						
Display Type	LCD						
Operating Humidity	Less than 95% RH						
Operating Temperature	50° F to 86° F (10° C to 30° C)						
Operating Temperature	41° F to 104° F (5° C to 40° C)						
Stabilization Time (typical)	3 seconds						
Net Weight (kg/lb)	9 lb (4.5kg)						
Pan Size/Type	7 in (180 mm) diameter pan, stainless steel						
Dimensions (W x D x H)	14.1 x 8.5 x 12.6 in (360 x 216 x 320 mm)						
AC Power Requirements	AC adapter, 115V-240V						
Frequency	50-60 Hz						
Warranty	Two-year Limited Warranty						

Part Number/Price

Part Number	Model	Description	Price
153987	Practum 612-1S	610 g x 0.01 g	\$1,065.00
153998	Quintix 612-1S	610 g x 0.01 g	\$1,690.00
153988	Practum 1102-1S	1,100 g x 0.01 g	\$1,180.00
153999	Quintix 1102-1S	1,100 g x 0.01 g	\$1,915.00
154010	Secura 1102-1S	1,100 g x 0.01 g	\$2,230.00
153989	Practum 2102-1S	2,110 g x 0.01 g	\$1,235.00
154000	Quintix 2102-1S	2,110 g x 0.01 g	\$2,135.00
154011	Secura 2102-1S	2,110 g x 0.01 g	\$2,650.00
154001	Quintix 3102-1S	3,100 g x 0.01 g	\$2,365.00
154012	Secura 3102-1S	3,100 g x 0.01 g	\$2,865.00
154003	Quintix 5102-1S	5,100 g x 0.01 g	\$2,930.00
154013	Secura 5102-1S	5,100 g x 0.01 g	\$3,290.00
153991	Practum 5101-1S	5,100 g x 0.1 g	\$1,255.00
154004	Quintix 5101-1S	5,100 g x 0.1 g	\$1,690.00
153990	Practum 5100-1S	5,100 g x 1.0 g	\$970.00
154002	Quintix 5100-1S	5,100 g x 1.0 g	\$1,350.00

Options/Accessories

Part #	Model #	Description	Price
154749	6971790	AC adapter, 110-240V, six power plugs	\$108.00
155847	YCC04-D09	Adapter cable, USB to RS-232	\$53.00