Body Composition Analyzers



Standard Features

- Multi frequency full body composition obtained from bioelectrical impedance analysis (BIA) through scale
 base electrodes and handheld electrodes
- Column height: 29 in
- User configurable mode: Adult, Athlete, Wrestler and Goal Setter
- Built-in thermal printer
- USB terminal and RS-232 port for computer interface
- Includes AC adaptor and two rolls of thermal printer paper
- Client tracking software available on www.ricelake.com

Part Number/Price

Part #	Model	Capacity	Est. Weight	Price
151116	D1000-3	440 lb x 0.2 lb (200 kg x 0.1 kg) English firmware	33 lb (15 kg)	\$3,394.00

Options/Accessories

Part #	Description	Price
152984	Column kit	\$400.00
75947	Replacement paper, 85 ft long, direct thermal	\$6.00

Specifications

Capacity:

440 lb x 0.2 lb (200 kg x 0.1 kg)

Platform Dimensions: (W x D) 12 x 14 in

Power Supply: 12 VAC adaptor

Frequency: 5, 50, 250 kHz

Test Duration: Within 60 seconds

Height Range: 3 ft to 7 ft 11.5 in x 0.5 in increments (90 cm to 249 cm x 1 cm)

Body Fat Range: 1 to 75% x 0.1% increments

BMR:

1 kcal increments Impedance Measurement Range: 150–900 ohms

Operating Temperature: 50° F to 104° F (14° C to 40° C)

Warranty:

Two-year limited warranty

Approvals: FDA, 510 K

Shown with optional column kit

Body Composition Analyzers

Specifications

Capacity:

440 lb x 0.2 lb (200 kg x 0.1 kg)

Platform Dimensions: (W x D) 12 x 14 in

Power Supply: 12 VAC adaptor

Frequency: 50 K Hz

Test Duration: Within 60 seconds

Height Range: 3 ft to 7 ft 11.5 in x 0.5 in increments (90 cm to 249 cm x 1 cm)

Body Fat Range: 1 to 75% x 0.1% increments

BMR:

1 kcal increments Impedance Measurement Range: 150–900 ohms

Operating Temperature: 50° F to 104° F (14° C to 40° C)

Warranty: Two-year limited warranty

Approvals: FDA, 510K



Standard Features

- Single frequency lower body composition obtained from bioelectrical impedance analysis (BIA) through scale base electrodes
- User configurable mode: Adult and Athlete Mode, Wrestler, Goal Setter and Weight Only
- Built-in thermal printer
- USB terminal and RS-232 port for computer interface
- · Includes AC adaptor and two rolls of thermal printer paper
- Client tracking software available on www.ricelake.com

Part Number/Price

P	art #	Model	Capacity	Est. Weight	Price
1	51115	D1000-1	440 lb x 0.2 lb (200 kg X 0.1 kg) English firmware	33 lb (15 kg)	\$2,673.00

Options/Accessories

Part #	Description	Price
152984	Column kit	\$400.00
75947	Replacement paper, 85 ft. long, direct thermal	\$6.00

Body Composition Analyzers



Standard Features

- Single frequency upper body composition obtained from bioelectrical impedance analysis (BIA) through handheld electrodes
- User configurable mode: Adult and Athlete Mode, Wrestler, Goal Setter and Weight Only
- Built-in thermal printer
- USB terminal and RS-232 port for computer interface
- · Includes AC adaptor and two rolls of thermal printer paper
- · Client tracking software available on www.ricelake.com

Part Number/Price

	-			
Part #	Model	Capacity	Est. Weight	Price
151114	D1000-2	440 lb x 0.2 lb (200 kg x 0.1 kg) English firmware	33 lb (15 kg)	\$2,673.00

Options/Accessories

-		
Part #	Description	Price
152984	Column kit	\$400.00
75947	Replacement paper, 85 ft. long, direct thermal	\$6.00

Specifications

Capacity:

440 lb x 0.2 lb (200 kg x 0.1 kg)

Platform Dimensions: (W x D) 12 x 14 in

Power Supply:

12 VAC adaptor Frequency:

50 K Hz **Test Duration:**

Within 60 seconds

Height Range: 3 ft to 7 ft 11.5 in x 0.5 in increments (90 cm to 249 cm x 1 cm)

Body Fat Range: 1 to 75% x 0.1% increments

BMR:

1 kcal increments Impedance Measurement Range: 150–900 ohms

Operating Temperature:

50° F to 104° F (14° C to 40° C)

Warranty:

Two-year limited warranty

Approvals: FDA, 510 K