

S SERIES

S25C



20/25/30/32c

IC-CUSHION LPG
4000 / 5000 / 6000 / 6500 lbs.
(2000 / 2500 / 3000 / 3200 kg)

STANDARD SPECIFICATIONS

20/25/30/32

Manufacturer's Designation		S20C	S25C	S30C	S32C
Load Capacity / Rated Load	lbs(kg)	4000 (2000)	5000 (2500)	6000 (3000)	6500 (3200)
Height Overhead Guard	in(mm)	82.9 (2105)	82.9 (2105)	82.9 (2105)	82.9 (2105)
Width	in(mm)	41.7 (1060)	41.7 (1060)	43.9 (1114)	45.5 (1155)
Right Angle Stack (Add Load Length and Clearance)	in(mm)	95.6 (2429)	97.2 (2470)	99.1 (2518)	100.8 (2561)
Outside Turning Radius	in(mm)	79.5 (2020)	81.1 (2061)	83.0 (2109)	84.5 (2147)
Travel speed Loaded & Unloaded	mph (kph)	11.2 (18.1) / 11.5 (18.5)	11.2 (18.1) / 11.5 (18.5)	11.1 (17.9) / 11.4 (18.4)	11.2 (18.0) / 11.5 (18.6)
Power Unit	HP(KW) @rpm	FORD 2.5 69.7 (52) @ 2500	FORD 2.5 69.7 (52) @ 2500	FORD 2.5 69.7 (52) @ 2500	FORD 2.5 69.7 (52) @ 2500

Standard Features

- FORD 2.5L Balanced Engine • EPA Compliant • Standard, Triple, Hi-Lo and Quad Uprights • Full Range of Lift Heights • High Visibility "Silent Staging" Uprights • Two-Pedal Inch-Brake System • Single Speed Transmission • Force-Cooled Wet Disc Brakes • Automatically-Applied Parking Brake • Hood Mounted Control Levers • LED Headlights OHG Mounted • Speed Limiter • Traction Disable Seat Switch • Operator Presence System • Raised Air Intake • Copper Open Core Radiator • High Capacity Cooling System • 5" Color LCD Digital Display • Automatic Engine Shutdown System • Low Fuel Warning Light • Power Steering • Tilt Steering Wheel • Grab Bar Handle with Horn Button • Steering Wheel Spinner Knob • Full Suspension Vinyl Seat with Hip Restraints • Orange Seatbelt • Drink Holder • Convenience Console

For more information on this model and the full line of CLARK Forklifts, find your local CLARK Dealer at www.clarkmhc.com.

