

HUSKEY™

Maneuverable In Tight Spots

MODEL	C4-25	
TYPE	Electric	
SPEED (MAX MPH)	9	14.5 km/hr
RANGE (MILES)	30	48.3 km
DRAW BAR PULL (lbs)	300 lbs.	136 kg
TOWING CAPACITY (lbs)	15,000	6,804 kg
BATTERY COMPARTMENT	32" L x 16.5" W x 24" H	
	81.28 cm x 41.9 cm x 60.96 cm	
VOLTAGE	48 volt	
TURNING RADIUS (INCHES)	69	175 cm

Based on standard configuration
Vehicles may be shown with optional equipment.



Tough and Dependable Product Solutions

The Huskey™ Electric Tow Tractor was designed to provide reliable service in rugged applications. The four wheel design of this vehicle ensures maximum safety without compromising any maneuverability.

Huskey utilizes a 48 volt GT drive system equipped with a solid state controller and a drive train incorporating a 16.3 hp DC SEM motor attached to an automotive differential to provide rugged and reliable service for years to come.

Ergonomics and operator safety are other key design features. Tilt steering wheel, spring-loaded adjustable operator seat, and improved visibility while maneuvering in tight spots makes the Huskey one of the most modern tow tractors manufactured.

Equipped for a standard lift out battery box or optional left side extract (LSX) battery system, the Huskey can be utilized 24 hours a day.

With a smooth ride and effortless operation provided by front and rear suspension, the Huskey is the operator's choice. Other standard equipment including headlight, turn signals, hazard lights, and reverse lights, makes the Huskey one of the best narrow aisle tow tractor values in the industry.

With over 150,000 vehicles in service and over 50 years of experience in the industry, Taylor-Dunn products are the best way to go about your business.



- 48v Electric Tow Tractor
- 69" Turning Radius, narrow aisle design
- 15,000 lb. towing capacity
- Lift out or slide out battery compartment



TAYLOR-DUNN®
Commercial and Industrial Vehicles Since 1949

The best way to go about your business

PERSONNEL CARRIERS



Aristocrat



Roadmaster

BURDEN CARRIERS



Taylortruck



Loadmaster



Model B Series



Electruck



Maintenance Expediter



Stepsaver



Stockchaser

TOW TRACTORS



Towmaster



Mule







Pullmaster



Model E



Huskey



HUSKEY™ - STANDARD SPECIFICATIONS

Product Line	C4-25
Unit Weight Lbs (Kgs)	1650 lbs.(less battery) (748 kg)
Towing Capacity	15,000 lbs. (6800 kg)
Draw Bar Pull:	300 lbs. (normal) (136 kg); 2,000 lbs. (ultimate) (907 kg)
Battery Compartment Size (cm):	32"w x 16.5"l x 24"h (81 w x 24 l x 61h)
Battery Weight Range	Minimum 1,000 lbs., Maximum 1,400 lbs.
System Voltage	48V DC
Drive Axle	GT Automotive Type, Differential
Transmission	Oil Bath, Helical Gears
Motor	16.3 HP DC Separately Excited
Tires	4.80 x 8 Pneumatic Load Range "C", Split Rims
Brakes	4 Wheel, Hydraulic Disc, Hand Operated Parking Brake
Steering	24:1 Ratio Automotive Type, Tilt Steering Column
Frame	3/16 inch Thick Steel Chassis
Suspension	Coil Springs Front and Rear, with Shock Absorbers
Color	Two Tone Red Cowl and Battery Lid, Grey Chassis
Seat	Adjustable, Spring Loaded
Controller	Solid State, Hi-Low Speed
Instrumentation	Battery Status Indicator, Hour Meter, DC-DC Converter, Seat Interlock Switch, Electrical Disconnect Switch
Light Accessories	Headlight, Taillights, Brake Lights, Reverse Lights, Turn Signals
Conformance	Type E OSHA 1910.178, ANSI B56.9-1987

Specifications based on standard vehicle configuration on smooth level surface with unit unloaded.

MODEL C4-25 OPTIONAL FEATURES

- Maintenance-free batteries
- Cab with sliding doors
- 24 volt or 36 volt drive train
- Left side battery extract frame

Shown with Optional Left Side Battery Extraction System (LSX)



TAYLOR-DUNN CORPORATION
 Commercial and Industrial Vehicles Since 1949



2114 West Ball Road, Anaheim, CA 92804 • (714) 956-4040 • FAX (714) 956-3130
 Toll Free (800) 688-8680 Visit our website: www.taylor-dunn.com

Specifications, standard equipment, accessories and modifications subject to change without notice.