

## Smooth consistent sound, Great articulation, Superior comfort

**ATH-M50** professional studio monitor headphones provide an exceptionally accurate response combined with long-wearing listening comfort. Designed especially for professional monitoring and mixing, these studiophones feature an efficient collapsible design for space-saving portability and storage. Circumaural ear pieces swivel 180° for easy one-ear monitoring, and luxuriously padded ear cushions create an outstanding seal for maximum isolation. The adjustable headband is generously padded for the ultimate comfort during long mixing sessions. A coiled cable at the left earpiece terminates to a gold-plated mini-plug with included screw-on 1/4" adapter.

A-T's sophisticated driver technology and superior components deliver exceptional power handling and very high SPL capabilities while maintaining clarity of sound throughout an extended range, with deep resonating bass and outstanding vocal projection. The headphones feature proprietary 45 mm large-aperture drivers with neodymium magnet systems for ultra-efficient signal transfer.

- · Exceptional audio quality for professional monitoring and mixing
- Collapsible design ideal for easy portability and convenient storage
- Proprietary 45 mm large-aperture drivers with neodymium magnet systems for ultra-efficient signal transfer
- Closed-back cushioned earcup design creates an outstanding seal for maximum isolation
- Adjustable padded headband for comfort during long mixing/recording sessions
- Single-sided coiled cable terminates to gold-plated mini-plug with screw-on <sup>1</sup>/<sub>4</sub>" adapter

## SPECIFICATIONS\*

ТҮРЕ	Closed-back dynamic
DRIVER DIAMETER	45 mm
MAGNET	Neodymium
VOICE COIL	CCAW (copper-clad aluminum wire)

FREQUENCY RESPONSE 15 - 28,000 Hz

MAXIMUM INPUT POWER 1,600 mW at 1 kHz

**SENSITIVITY** 99 dB

IMPEDANCE 38 ohms

WEIGHT 284 g (10 oz) without cable and connector

CABLE 1.2–3.0 m (3.9'–9.8') coiled, OFC litz wire

CONNECTOR 3.5 mm ('/e") gold-plated stereo mini-plug

ACCESSORIES INCLUDED Screw-on 6.3 mm (1/4") adapter, protective pouch

\* Specifications are subject to change without notice.





