WMS wall mount shelf

h. The WMS provides a secure yet inexpensive way to mount non-rack mountable equipment to a wall. With a vented bottom for air circulation and conduit knockouts for cable passage, this 16-gauge steel fully welded unit has a 200 pound capacity. Finished in rugged black powder coat, the WMS can also be used to house our ER or ERK series of racks. Overall dimensions: 16.75° W x 20.875° D x 14° H

UTVS-3 vented shelf

i. This 16-gauge steel shelf, finished in black powder coat will handle up to 60 pounds of equipment. It occupies 3 rack spaces and is either 14" (UTVS-3-14) or 17" deep. Slotted bottom allows for ventilation and slotted rear return for cable management.

ADS-3 adjustable shelf

he

k

osed oth

j. This three space, 16-gauge steel shelf has three position adjustable ears allowing user to move equipment from flush with rack rail to eight inches forward of rail. Finished in durable black baked enamel. Overall dimensions: 19" W x 17" D x 5-1/4" H

Model	Depth	Height	Usable Width	Capacity	
WMS	16-3/4″	14″	20-3/4″	150lbs.	
UTVS-3-14	14″	5-1/4"	17-1/4″	80lbs.	
UTVS-3-18	18″	5-1/4"	17-1/4″	80lbs.	
ADS-3	17-1/2″	5-1/4"	16-3/4″	80lbs.	
VCS-2	18″	3-1/2"	17-1/4″	80lbs.	
TR-2	14-1/4″	3-1/2"	17-1/4″	50lbs.	
TR-3	14-1/4″	5-1/4"	17-1/4″	80lbs.	
TR-4	14-1/4″	7"	17-1/4″	100lbs.	

VCS-2 cantilevered shelf

k. Occupying two rack spaces, this 16-gauge steel shelf allows user to bring equipment well forward of the rack face. Vented for air circulation, this shelf is 18" deep and will support up to 50 pounds. VCS-2 features built in cable management and is finished in black powder coat.



h

TR trap shelf

n. Available in 2, 3 and 4 space versions, this versatile shelf is constructed of 16-gauge cold, rolled steel and finished in durable black baked enamel. Comes complete with 2 fully adjustable hold down bars that "trap" equipment. Bars are padded to protect the finish on your gear. Returns on the front and rear edges of shelf provide additional lateral strength.



Model	Usable Depth	Height	Usable Width	Capacity
WDS-14	14"	5-1/4"	18-5/8″	80lbs.
WDS-17	17″	5-1/4″	18-5/8″	80lbs.

WDS wide shelf

I. Intended for use with components wider than standard 17-3/8" inside rack measurement. Unit mounts to the 1-1/2" rack rail mounting face or into millwork. Available in 14" or 17" depths. Occupies three rack spaces. Finished in durable black baked enamel.



ROTRS shelf

www.raxxess.com

Ψ

m. Intended for use with components wider than standard 17-3/8" inside rack measurement. Unit mounts to the 1-1/2" rack rail mounting face or into millwork. Available in 14" or 17" depths. Occupies three rack spaces.



