Accessories

System Accessories

ACT-1

120 VAC - 12-Volt DC triggered outlet with resettable circuit breaker. Switches up to 10 amps.

*3.75" W x 2" H x 5" D (9.5 x 5.1 x 12.7 cm)*

Order #
9500-115592

Shipping Weight
12.5oz (.4kg)
Min. Advertised Price
$**89**.⁰⁰

LFP-1.2

Low Frequency Protection Module. Protects impedance matching devices from subsonic frequencies and DC clipping. Color-coded detachable 14-gauge snap connectors.

3.75" W x 1.5" H x 2.5" D (9.6 x 3.81 x 6.4 cm)

Order #
9500-520938

Shipping Weight
6oz (.2kg)
Min. Advertised Price
$**69**.⁰⁰

ADP-1.2

Speaker to line-level adapter. Recommended for use with CAA66 and CAM6.6 to obtain line level outputs for zones without pre-amp outputs. Color-coded detachable 14-gauge snap connectors.

3.375" W x 1" H x 2.5" D (8.6 x 2.6 x 6.4 cm)

Order #
9500-200891

Shipping Weight
6oz (.2kg)
Min. Advertised Price
$**39**.⁰⁰

Data and Speaker Cable

AW162CL3

2 conductor, 16 gauge speaker cable, unshielded, 26/30 strands bare copper, .024 nominal PVC jacket, temp. rating 75° C, UL type CL3, LIGHT BLUE JACKET. 1000 foot pull-box only.

Order #
9000-119316

Call for Pricing

AW164C5

4 pair twisted, 24 gauge, CAT-5E cable, solid copper, PVC jacket, telephone/data grade/ISDN. Zipcord with 4 conductor, 16 gauge speaker cable. 500 foot spool. PINK jacket.

Order #
9000-121838

Call for Pricing

AW164CL3

4 conductor, 16 gauge speaker cable, unshielded, 26/30 strands bare copper, .024 nominal PVC jacket, temp. rating 75° C, UL Type CL3, YELLOW JACKET. 500 foot pull-box only.

Order #
9000-460067

Call for Pricing

AW2260AB

4 conductor, 22 gauge signal/data cable, 2 pair twisted w/shield, 19/34 tinned copper, PVC jacket, temp. Rating 75° C, UL Type CL3, WHITE JACKET. 1000 foot pull-box only. Conducts sensitive IR signals and shields them from outside noise.

Order #
9000-115240

Call for Pricing

AWCAT5

8 conductor, 24 gauge CAT-5E cable, 4 pair twisted, solid copper, PVC jacket, telephone/data grade/ISDN, GRAY JACKET. 1000 Foot pull-box only.

Order #
9000-119323

Call for Pricing

SRM-2.1

Speaker relay module* to be used to share speakers between controllers and home theater. Add 12-VDC automatic A/B switching, speaker level, between CA amplifier and local amplifier. ***Wall plates not included with keypads.**

1.3125" W x 2.5" H x 1.875" D (33.5 x 63.5 x 48 mm)

Order #	Color
1200-115585	White
1200-114021	Almond

Shipping Weight
8oz (.2kg)
Min. Advertised Price
$**99**.⁰⁰

Russound