



CS Series

CS-64 (6 W)

CS-64U (6 W) UL Listed

WIDE-RANGE PAGING SPEAKERS

- Wide-range paging speakers for voice paging, background music and tone signaling distribution
- Weather-resistant to withstand demanding environmental conditions
- UL Listed models: UL 1480 (UEAY, outdoor use)
- Moisture-resistant speaker component (4.72")
- Frequency Response:
CS-64/U: 130 to 13k Hz
- Sensitivity (1 W, 1 m):
CS-64/U: 96 dB SPL
- Built-in multi-tap 70.7/100 V transformer



- Screwdriver-adjustable power taps
- Lightweight, sealed enclosure prevents moisture damage
- Cable strain-relief
- Polyurethane resin paint resists the fading effects of ultraviolet light
- IEC IP-64 standards compliant for dust and moisture-resistance
- Wide temperature range: -4° F to 131° F
- Protective stainless-steel mesh grille prevents speaker damage
- Stainless-steel mounting bracket included
- Five year warranty

CS-304 (30 W)

CS-304U (30 W) UL Listed

WIDE-RANGE PAGING SPEAKERS

- Wide-range paging speakers for voice paging, background music and tone signaling distribution
- Weather-resistant to withstand demanding environmental conditions
- UL Listed models: UL 1480 (UEAY, outdoor use)
- Constant directivity coverage
- Moisture-resistant speaker component (4.72")
- Frequency Response:
CS-304/U: 120 to 15k Hz
- Sensitivity (1 W, 1 m):
CS-304/U: 98 dB SPL
- Built-in multi-tap 70.7/100 V transformer
- Screwdriver-adjustable power taps
- Lightweight, sealed enclosure prevents moisture damage
- Cable strain-relief
- Polyurethane resin paint resists the fading effects of ultraviolet light
- IEC IP-64 standards compliant for dust and moisture-resistance
- Wide temperature range: -4° F to 131° F
- Protective stainless-steel mesh grille prevents speaker damage
- Stainless-steel mounting bracket included
- Five year warranty



CS-154 (15 W)

CS-154U (15 W) UL Listed

WIDE-RANGE PAGING SPEAKERS

- Wide-range paging speakers for voice paging, background music and tone signaling distribution
- Weather-resistant to withstand demanding environmental conditions
- UL Listed models: UL 1480 (UEAY, outdoor use)
- Constant directivity coverage
- Moisture-resistant speaker component (4.72")
- Frequency Response:
CS-154/U: 150 to 15k Hz
- Sensitivity (1 W, 1 m):
CS-154/U: 97 dB SPL
- Built-in multi-tap 70.7/100 V transformer
- Screwdriver-adjustable power taps
- Lightweight, sealed enclosure prevents moisture damage
- Cable strain-relief
- Polyurethane resin paint resists the fading effects of ultraviolet light
- IEC IP-64 standards compliant for dust and moisture-resistance
- Wide temperature range: -4° F to 131° F
- Protective stainless-steel mesh grille prevents speaker damage
- Stainless-steel mounting bracket included
- Five year warranty

