



PAGING HORNS

SC Series

SC-610 (8 ohm)

SC-610T

PAGING HORN SPEAKERS

- Paging horn speaker for voice and tone signaling distribution
- Weather-resistant for demanding environmental conditions
- Double re-entrant horn with compression driver
- Usable as a microphone for intercom talk-back applications
- Built-in 25/70.7 V transformer ("T" models) with 8 and 16 ohm models also available
- Screwdriver-adjustable power taps
- Lightweight, sealed, aluminum enclosure
- Cable strain-relief
- IEC IP-65 standards compliant for dust and moisture-resistance
- Wide temperature range: -4°F to 131°F
- Phenolic loudspeaker diaphragm prevents deformation
- Stainless-steel mounting bracket included
- Optional swivel-mount bracket, model YS-151S
- Five year warranty
- Dispersion Angle: 70° H x 100° V
- Frequency Response: 315 to 12.5k Hz
- Sensitivity (1 W, 1 m): 110 dB SPL
- Continuous Power Handling: 10 W



SC-615 (8 ohm)

SC-615T

PAGING HORN SPEAKERS

- Paging horn speakers for voice and tone signaling distribution
- Weather-resistant for demanding environmental conditions
- Double re-entrant horn with compression driver
- Usable as a microphone for intercom talk-back applications
- Built-in 25/70.7 V transformer ("T" models) with 8 and 16 ohm models also available
- Screwdriver-adjustable power taps
- Lightweight, sealed, aluminum enclosure
- Cable strain-relief
- IEC IP-65 standards compliant for dust and moisture-resistance
- Wide temperature range: -4°F to 131°F
- Phenolic loudspeaker diaphragm prevents deformation
- Stainless-steel mounting bracket included
- Optional swivel-mount bracket, model YS-151S
- Five year warranty
- Dispersion Angle: 70° H x 90° V
- Frequency Response: 280 to 12.5k Hz
- Sensitivity (1 W, 1 m): 112 dB SPL
- Continuous Power Handling: 15 W



SC-630 (8 ohm)

SC-630T

SC-650 (16 ohm)*

PAGING HORN SPEAKERS

- Paging horn speakers for voice and tone signaling distribution
- Weather-resistant for demanding environmental conditions
- Double re-entrant horn with compression driver
- Usable as a microphone for intercom talk-back applications
- Built-in 25/70.7 V transformer ("T" models) with 8 and 16 ohm models also available
- Screwdriver-adjustable power taps
- Lightweight, sealed, aluminum enclosure
- Cable strain-relief
- IEC IP-65 standards compliant for dust and moisture-resistance
- Wide temperature range: -4°F to 131°F
- Phenolic loudspeaker diaphragm prevents deformation
- Stainless-steel mounting bracket included
- Optional swivel-mount bracket, model YS-151S
- Five year warranty



- Dispersion Angle: SC-630/T: 55° H x 70° V
SC-650: 55° H x 45° V
- Frequency Response: SC-630/T: 250 to 10k Hz
SC-650: 250 to 6k Hz
- Sensitivity (1 W, 1 m): SC-630/T: 113 dB SPL
SC-650: 108 dB SPL
- Continuous Power Handling: SC-630/T: 30 W
SC-650: 50 W

*Model SC-650 not shown

