



**C-1616 FEATURES:**

- 2 or 4 wire per line (field programmable)
- Simplex/full duplex per line (field programmable)
- Programmable squelch control per line
- TX monitor
- Supervisory control
- Two alert tone cadence (keypad programmable)
- Crossmute per line (hardwire)
- TX notch filter
- Wildcard group groupings (function tones)

**C-1616 CONTROLS:**

- Select/unselect status for each line
- 16-function tone button selection
- TX all button
- RX all button
- Mute button
- Alert button
- AUX relay button
- Intercom
- PTT button
- 16-digit DTMF keypad
- Supervisory button
- TX detect LED for selected audio
- Line activity monitor LED for each line

# Six-line Analog Tone Remote Control Console

model: **C-1616**



The C-1616 is designed for easy field programmability. The modular design offers selection and control of up to six base stations and 16 frequencies. The C-1616 comes standard with two channels. Additional channels may be added by installing another two-line module—sold separately.

Its unique vacuum florescent display provides channel alpha/numeric indication, and features clock and audio-level meter. Multiple consoles can be easily programmed by using the serial port located on the back of each console. Unlike other manufacturers' equipment, the C-1616 requires no additional programming. Optional: handset/headset, gooseneck mic, desk mic and footswitch.

**C-2002 FEATURES:**

- Selective call indication
- Parallel console update
- Alert tone
- Time duration of the PTT
- Audio delay
- Function tones (programmable)
- Up to 99 frequency control
- 2 or 4 wire (field programmable), local and E&M
- Simplex/full duplex (field programmable)
- Programmable squelch control
- Crossmute (hardwire)
- TX monitor
- Supervisory control
- TX and RX notch filter
- Programmable TX delay

**C-2002 CONTROLS:**

- Monitor, Intercom, PTT
- Alert tone
- ALT button
- Mute, release and select (per line)
- Supervisory control
- 16-digit DTMF keypad
- Volume control (select and unselect)
- Parallel TX LED detect
- Frequency selection
- Three simultaneous microphones

# Two-line Radio Control Console

model: **C-2002**



Compact but still loaded with features and reliability, the C-2002 offers cross-mute and supervisory capability, along with programmable squelch control, which eliminates the unwanted noise generally associated when monitoring a line. The C-2002 can control two base stations and select up to 99 frequencies. This DSP-designed console can be programmed by using the DTMF keypad on the front of the console. Used with our mating DSP-223 series adapter panels, the C-2002 meets all the needs and requirements for controlling remote base stations. The console comes with a handset and panel mic. Optional: headset, desk mic, footswitch and wall mount kit.