



UNITED BRASS WORKS, INC.
714 S. Main St., Randleman, NC 27317
Tel: 800-334-3035 Fax: 800-498-4696 www.ubw.com



Model 35VNC Air Cylinder

Operated Normally Closed Globe Valve

200 WOG Body Rating @ 180 ° Max

100% Pressure Tested • Threaded Ends

40 PSI Operating Pressure for Standard Configuration

80PSI Air Pressure Required

For other options, consult factory.

MATERIAL LIST

NO.	DESCRIPTION	MATERIAL
1	35ANC - Cap	Brass
2	35UC - Cylinder	Brass
3	VC125SNC - Spring	Steel
4	700215 - Jam Nut	Brass
5	186814 - O-Ring 214ILV	FKM (Viton)
6	850323 - O-Ring 110N	Buna
7	186816 - O-Ring 110IL	FKM (Viton)
8	702025 - O-Ring 025VT	FKM (Viton)
9	125J - Body	Bronze
10	125VD - Disc	FKM (Viton)
11	35BLV - Stem & Disc Assembly	Brass
12	36P - Piston	Brass

	1"	1 ½"	2"
A	3.13	4.00	4.66
B	4.53	5.38	6.19
Ship Wgt. (lbs.)	2.26	4.38	6.20

