# **Cylinder Safety Products**



# **Cylinder Stands**



#### Model 704

Heavy duty cast aluminum **Model 704** stand adjusts to hold cylinders from 6" to  $9^{1}/_{4}$ ", hinges open for installation without lifting the cylinder or disturbing connections.

Model 703

**Model 703** cast aluminum stand hinges open and has four thumb screws to tightly grip cylinders from 8" to 9".





### Model 701

**Model 701** cylinder stand has a flat bottom support so it can't "ride up" on the cylinder. Adjustable nylon strap keeps cylinder safely in place against upper support bar; lower support bar stops cylinder shift. Thick PVC coating prevents marring of the cylinder surface.

### **Cylinder Wall Brackets**





### Model 715 and 717

Troemner wall-mount cylinder brackets are made of cast aluminum, contoured to allow cylinders to fit firmly along the support edge. One-inch nylon strap, 54" long, has a nickelplated non-slip spring catch and buckle for fast, easy adjustment. Recessed screw holes at each side of the bracket allow easy wall-mounting. For cylinders up to 14" diameter.

## **Cylinder Bench Clamps**

Rugged cast aluminum clamps safely secure gas cylinders to bench, table or other flat surface up to  $2^{1}/_{2}$ " thick with at least  $1^{1}/_{2}$ " overhang. One-inch wide nylon strap features a non-slip spring catch and buckle for easy adjustment around cylinders from 4" through 14" diameter.



### Model 711

**Model 711** bench clamp has a large tightening handle and a nylon pad to prevent damage to the bench or table surface. Two chamfered mounting screw holes are provided for permanent attachment to the surface.

#### Model 716

**Model 716** bench clamp is similar to model 711, but includes a sturdy safety chain for extra security.





### Model 712

**Model 712** bench clamp has two screw clamps for extra-firm mounting of tanks up to 14" diameter.

# Portable Cylinder Support

#### Model 713

A sturdy cylinder stand and a convenient cylinder dolly all in one! It's designed in two interlocking halves and can be installed without lifting the tank. Built-in rubber wheels for easy mobility. Adjustable for cylinders from 7" to  $9^{1}/_{4}$ " diameter.

