



# Boiler Controls

McDonnell & Miller


## Low Water Cut-Offs – Electronic For Hot Water Boilers

**NOW WITH SELF-CLEANING PROBE!**

### RB-120 Low Water Cut-Offs



- For residential and (where codes allow) commercial applications
- Electro-mechanical operation
- Automatic reset feature resumes operation after a power outage when water is on probe
- No blow down required
- 6,000 ohms probe sensitivity
- Maximum ambient temperature 120°F (49°C)
- Maximum water temperature 250°F (121°C)
- Maximum water pressure 160 psi (11.2 kg/cm<sup>2</sup>)



Boiler Controls

### Electrical Ratings

Voltage	Power Consumption	Load Switching
120 VAC	15 VA	5.8 A at 120 VAC

### Dimensions, in. (mm)

A	B	C	D	E	F	G NPT
6 <sup>3</sup> / <sub>8</sub> (162)	5 <sup>1</sup> / <sub>8</sub> (130)	2 <sup>9</sup> / <sub>16</sub> (65)	1 <sup>5</sup> / <sub>8</sub> (41)	1 <sup>3</sup> / <sub>8</sub> (35)	3 <sup>4</sup> / <sub>4</sub> (20)	7 <sup>7</sup> / <sub>8</sub>

### Ordering Information

Model Number	Part Number	Description	Weight lbs. (kg)
RB-120	144675	Low water cut-off	3.8 (1.7)