

Swimming Pool Pump, Single Phase

Dripproof, C-Face

Applications: For use on commercial pool pump systems.

- Features:**
- UL "1081" Design
 - NEMA pool motor Service Factors
 - External ground lugs
 - Double sealed ball bearings
 - PSC design
 - Fixed CW rotation, viewed opposite shaft end
 - Automatic reset thermal protector
 - Class F insulation
 - 50 degrees C ambient
 - 56C = Keyed shaft, shaft slinger, C-face round body
 - 56J = Threaded shaft, shaft slinger, C-face round body
 - 304 stainless steel shaft on all models
 - UL Recognized and CSA Certified



HP	RPM	VOLTS	FRAME	CAT NO.	MODEL NO.	LIST PRICE	MULT. SYMB.	SERVICE FACTOR	F.L. AMPS	APPROX. WGT. LBS.	"AG" DIM.	FOOT NOTES
1/2	3600	115/230	56C	J070 *	56A34DB11011	\$211	F1	1.95	11.6/5.8	24	9.69	d,DS
	3600	115/230	56J	J071 *	56A34DB11001	\$211	F1	1.95	11.6/5.8	26	9.69	d,DS
3/4	3600	115/230	56C	J072 *	56A34DB11004	\$251	F1	1.95	13.0/6.5	25	9.69	d,DS
	3600	115/230	56J	J073 *	56A34DB11013	\$251	F1	1.95	13.0/6.5	25	9.69	d,DS
1	3600	115/230	56C	J074 *	56A34DB11003	\$278	F1	1.5	13.0/6.5	32	10.67	d,DS
	3600	115/230	56J	J075 *	56A34DB11012	\$278	F1	1.5	13.0/6.5	32	10.67	d,DS
1 1/2	3600	230	56C	J076	56A34DB11002	\$331	F1	1.4	8.8	38	11.65	DS
	3600	230	56J	J077 *	56A34DB11014	\$331	F1	1.4	8.8	38	11.65	d,DS
2	3600	230	56C	J078 *	56A34DB11015	\$396	F1	1.15	9.5	38	11.65	d,DS
	3600	230	56J	J079 *	56A34DB11010	\$396	F1	1.15	9.5	38	11.65	d,DS

* Stock Model

Swimming Pool Pump, Single Phase

Dripproof, Square Flange

Applications: For use on commercial pool pump systems.

- Features:**
- UL "1081" Design
 - NEMA pool motor Service Factors
 - External ground lugs
 - Double sealed ball bearings
 - PSC design
 - Fixed CW rotation, viewed opposite shaft end
 - Automatic reset thermal protector
 - Class F insulation
 - 50 degrees C ambient
 - 56Y = Threaded shaft, shaft slinger, special square flange mount
 - 304 stainless steel shaft on all models
 - UL Recognized and CSA Certified



HP	RPM	VOLTS	FRAME	CAT NO.	MODEL NO.	LIST PRICE	MULT. SYMB.	SERVICE FACTOR	F.L. AMPS	APPROX. WGT. LBS.	"AG" DIM.	FOOT NOTES
1/2	3600	115/230	56Y	J080 *	56A34DB11009	\$211	F1	1.95	11.6/5.8	24	9.69	d,DS
3/4	3600	115/230	56Y	J081 *	56A34DB11008	\$251	F1	1.95	13.0/6.5	25	9.69	d,DS
1	3600	115/230	56Y	J082 *	56A34DB11007	\$278	F1	1.5	13.0/6.5	32	10.67	d,DS
1 1/2	3600	230	56Y	J083 *	56A34DB11006	\$331	F1	1.4	8.8	38	11.65	d,DS
2	3600	230	56Y	J084 *	56A34DB11005	\$396	F1	1.15	9.5	38	11.65	d,DS

* Stock Model

Footnotes:

d Will become build-up item when current stock is gone
 DS Sourced