



# C FACE MOTORS • SINGLE PHASE

LESS BASE • CAPACITOR START • GENERAL PURPOSE



## DRIP-PROOF • C FACE LESS BASE • SINGLE PHASE

HP	RPM 60 Hz	NEMA Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Voltage	Over- load Prot.	F.L. Amps 230V	"C" Dim. (Inches)
1/6	1725	...	...	...	...	...	...	...	...	...
1/4	1725	...	...	...	...	...	...	...	...	...
	1725	S56C	100023	\$271	A	17	115/208-230	None	2.7	9.24
	1725	S56C	101521	295	A	17	115/208-230	Auto.	2.7	9.24
1/3	3450	S56C	100354	239	A	17	115/208-230	None	2.8	8.99
	3450	S56C	100355	251	A	17	115/208-230	Auto.	2.8	8.99
	1725	...	...	...	...	...	...	...	...	...
	1725	S56C	100024	316	A	17	115/208-230	None	3.3	9.24
	1725	S56C	100018	341	A	18	115/208-230	Man.	3.3	9.24
	1725	S56C	101522	334	A	17	115/208-230	Auto.	3.3	9.24
1/2	3450	S56C	100356	251	A	19	115/208-230	None	3.4	9.99
	3450	S56C	100054	270	A	18	115/208-230	Auto.	3.4	9.99
	1725	...	...	...	...	...	...	...	...	...
	1725	S56C	100025	358	A	19	115/208-230	None	4.4	9.99
	1725	S56C	100019	385	A	21	115/208-230	Man.	4.4	9.99
	1725	S56C	100020	378	A	20	115/208-230	Auto.	4.4	9.99
	1140	56C	110381	651	A	32	115/208-230	None	5.0	11.38
3/4	3450	S56C	100357	323	A	24	115/208-230	None	4.9	10.49
	3450	S56C	100055	355	A	24	115/208-230	Auto.	4.9	10.49
	1725	S56C	100026	432	A	24	115/208-230	None	5.4	10.99
	1725	S56C	100021	466	A	24	115/208-230	Man.	5.4	10.99
	1725	S56C	101523	461	A	26	115/208-230	Auto.	5.4	10.99
	1140	56C	110382	725	A	46	115/208-230	None	6.4	12.88
1	3450	56C	110384	345	A	28	115/208-230	None	6.0	10.88
	3450	56C	113337	385	A	28	115/208-230	Auto.	6.0	10.84
	1725	56C	110220	459	A	30	115/208-230	None	6.4	10.88
	1725	56C	110036	484	A	27	115/208-230	Man.	6.4	10.88
	1725	143TC	121002	497	B	31	115/208-230	None	6.4	11.28
1 1/2	3450	56C	110387	476	A	28	115/208-230	None	8.2	10.84
	3450	56C	113336	504	A	28	115/208-230	Auto.	8.2	10.84
	3450	...	...	...	...	...	...	...	...	...
	1725	56C	110388☆	555	A	38	115/208-230	None	8.6	11.84
	1725	56C	110037☆	582	A	39	115/208-230	Man.	8.6	11.84
	1725	...	...	...	...	...	...	...	...	...
2	3450	56C	110390	624	A	37	115/208-230	None	10.0	11.84
	3450	56C	113335	651	A	36	115/208-230	Auto.	10.0	11.84
	3450	145TC	121184	635	B	37	115/208-230	None	10.0	12.28
	1725	...	...	...	...	...	...	...	...	...
	1725	145TC	120073☆	630	B	49	115/208-230	None	10.5	13.28
	1725	...	...	...	...	...	...	...	...	...
3	3450	56C	113334	663	A	36	230	Auto.	15.0	11.84
	3450	...	...	...	...	...	...	...	...	...
	1740	184TC	131544	732	B	73	115/208-230	None	16.9	14.19
5	3450	184TC	131777☆	980	B	70	208-230	None	22.2	14.69
	1740	184TC	131539☆	1020	B	81	230	None	21.0	14.69

Motors in this column have NEMA Service Factors - see page 308 for details.

- ☆ Capacitor start/capacitor run design for reduced amperage, others are capacitor start/induction run.
- ☆ These totally enclosed single phase motors have 1.15 Service Factors.
- These motors are totally enclosed, non-ventilated — Others are fan cooled.
- † Class F insulated.
- Shaft extension has keyway and flat 180° apart for ease of mounting. Useable shaft is 1 1/2" long by 1/2" diameter, 1/8" keyway.

## TEFC • C FACE LESS BASE • SINGLE PHASE

NEMA Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Voltage	Over- load Prot.	F.L. Amps 230V	"C" Dim. (Inches)
48CZ➤	102661	\$278	A	14	115/208-230	None	2.0	9.19
48CZ➤	101765	317	A	18	115/208-230	None	2.7	9.19
S56C	102868●	315	A	22	115/208-230	None	2.3	9.80
S56C	102866	315	A	18	115/208-230	None	2.7	9.44
S56C	102870	270	A	20	115/208-230	None	2.8	9.44
S56C	102873●	270	A	24	115/208-230	None	1.9	9.30
48CZ➤	102663	328	A	19	115/208-230	None	3.3	9.69
S56C	101766	341	A	22	115/208-230	None	3.3	9.94
S56C	102867●	339	A	23	115/208-230	None	2.6	10.30
S56C	102869●	357	A	25	115/208-230	Man.	2.6	10.30
S56C	102864	305	A	22	115/208-230	None	3.5	9.94
S56C	102872	324	A	25	115/208-230	Man.	3.5	9.94
48CZ➤	102665	383	A	22	115/208-230	None	4.0	10.44
S56C	102862	392	A	21	115/208-230	None	4.0	10.69
S56C	102865	414	A	22	115/208-230	Man.	4.0	10.69
S56C	102871	409	A	24	115/208-230	Auto.	4.0	10.69
56C	110411	690	A	37	115/208-230	None	4.9	12.81
56C	110413	357	A	26	115/208-230	None	5.0	11.31
56C	110412	371	A	28	115/208-230	Man.	5.0	11.31
56C	110057	466	A	25	115/208-230	None	5.4	11.31
56C	110040	491	A	26	115/208-230	Man.	5.4	11.31
56C	110308	484	A	28	115/208-230	Auto.	5.4	11.31
56C	110414☆	777	A	42	115/208-230	None	5.3	13.31
56C	110416	418	A	28	115/208-230	None	6.0	11.81
56C	110415	458	A	28	115/208-230	Man.	6.0	11.81
56C	110058	536	A	33	115/208-230	None	6.4	11.81
56C	110041	560	A	29	115/208-230	Man.	6.4	11.81
143TC	121001	608	B	32	115/208-230	None	6.4	12.25
56C	110419	538	A	31	115/208-230	None	8.5	12.31
56C	110418	564	A	31	115/208-230	Man.	8.5	12.31
143TC	120101	608	B	36	115/208-230	None	8.5	12.75
56C	110420☆	604	A	37	115/208-230	None	8.6	12.81
56C	110042☆	630	A	40	115/208-230	Man.	8.6	12.81
145TC	120017☆	688	B	40	115/208-230	None	8.6	13.75
56C	110422	685	A	40	115/208-230	None	10.0	13.31
56C	110421	709	A	41	115/208-230	Man.	10.0	13.31
145TC	120102	710	B	43	115/208-230	None	10.0	13.75
56C	112136☆	809	A	41	115/230	None	9.2	13.31
145TC	120060☆	828	B	45	115/230	Man.	10.0	14.25
182TC	131516	1079	B	64	115/208-230	None	12.4	14.47
...	...	...	...	...	...	...	...	...
145TC	120824☆	794	B	56	230	Man.	13.0	14.25
184TC	131545	1269	B	82	115/208-230	None	16.8	16.47
184TC	131778☆	1275	B	81	208-230	None	19.8	16.97
184TC	131540☆	1323	B	104	230	None	23.0	17.47

Motors in this column have NEMA Service Factors except as noted by ☆, which have 1.15 Service Factors.

All 180 and 210 frame Rolled Steel motors have Class F Insulation.

# C FACE MOTORS • SINGLE PHASE

WITH BASE • CAPACITOR START • GENERAL PURPOSE



C Face Motors



## DRIP-PROOF • C FACE WITH BASE • SINGLE PHASE

HP	RPM 60 Hz	NEMA Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Voltage	Over- load Prot.	F.L. Amps 230V	"C" Dim. (Inches)
1/4	1725	...	...	...	...	...	...	...	...	...
1/3	3450	...	...	...	...	...	...	...	...	...
	1725	S56C	103023	\$324	A	18	115/208-230	None	3.3	9.24
	1725	S56C	103083	324	A	18	115/208-230	Man.	3.3	9.24
	...	...	...	...	...	...	...	...	...	...
1/2	3450	S56C	103024	294	A	20	115/208-230	None	3.4	9.99
	1725	S56C	101651	392	A	21	115/208-230	None	4.4	9.99
	1725	S56C	103084	392	A	21	115/208-230	Man.	4.4	9.99
3/4	3450	S56C	103025	345	A	24	115/208-230	None	4.9	10.49
	1725	S56C	101650	454	A	27	115/208-230	None	5.4	10.99
	1725	S56C	103086	454	A	27	115/208-230	Man.	5.4	10.99
1	3450	56C	116769	366	A	28	115/208-230	None	6.0	10.84
	3450	...	...	...	...	...	...	...	...	...
	1725	56C	113930	518	A	34	115/208-230	None	6.4	10.88
	1725	...	...	...	...	...	...	...	...	...
	1725	...	...	...	...	...	...	...	...	...
1 1/2	3450	56C	116770	492	A	35	115/208-230	None	6.2	11.34
	3450	56C	114214☆	500	A	35	115/208-230	Man.	6.2	11.34
	3450	...	...	...	...	...	...	...	...	...
	1725	56HC	113932☆□	559	A	39	115/208-230	None	8.6	11.84
	1725	56HC	113700☆□	661	A	38	115/208-230	Man.	7.2	11.84
	1725	...	...	...	...	...	...	...	...	...
2	3450	56C	116771	625	A	35	115/208-230	None	8.6	11.34
	3450	56C	114215☆	635	A	35	115/208-230	Man.	8.6	11.34
	3450	...	...	...	...	...	...	...	...	...
	3450	...	...	...	...	...	...	...	...	...
	1725	56HC	113281☆□	685	A	45	115/208-230	Man.	8.6	12.88
	1725	145TC	120992	599	B	45	115/230	None	10.5	13.28
	1725	...	...	...	...	...	...	...	...	...
3	3450	56HC	116707☆	693	A	41	230	Man.	15.0	12.38
	3450	...	...	...	...	...	...	...	...	...
	3450	182TC	132083☆	780	B	74	115/208-230	None	14.0	14.18
	1740	184TC	131629	833	B	70	115/208-230	Man.	16.9	14.19
	1740	184TC	131853☆	832	B	87	208-230	Man.	15.4	15.96
5	3450	56HC	116709☆	710	A	46	230	Man.	20.8	13.34
	3450	184TC	131781☆	984	B	70	208-230	None	22.2	14.19
	1740	184TC	131630☆	1023	B	77	208-230	Man.	21.0	14.69
7 1/2	3450	184TC	132043☆	1021	B	112	208-230	Tstat	31.0	16.69
10	3450	...	...	...	...	...	...	...	...	...
	1740	...	...	...	...	...	...	...	...	...

Motors in this column have NEMA Service Factors - see page 308 for details.

- ☆ Capacitor start/capacitor run design for reduced amperage, others are capacitor start/induction run.
- ❖ These totally enclosed single phase motors have 1.15 Service Factors.
- These motors are totally enclosed, non-ventilated — Others are fan cooled.
- Combination 56H base motors have mounting holes for NEMA 56 and NEMA 143-145T and standard NEMA 56C face and shaft.
- † Class F insulated.

All 180 and 210 frame Rolled Steel motors have Class F Insulation.

## TEFC • C FACE WITH BASE • SINGLE PHASE

NEMA Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Voltage	Over- load Prot.	F.L. Amps 230V	"C" Dim. (Inches)
S56C	102916	\$322	A	22	115/208-230	None	2.7	9.69
S56C	102929	320	A	22	115/208-230	None	2.8	9.69
S56C	102930	342	A	24	115/208-230	None	3.1	10.44
S56C	103082	342	A	24	115/208-230	Man.	3.1	10.31
S56C	102910●❖	342	A	25	115/208-230	None	2.6	10.31
S56C	102903	321	A	25	115/208-230	None	3.5	9.94
S56C	102907❖	411	A	22	115/208-230	None	4.0	10.69
S56C	103085	411	A	22	115/208-230	Man.	4.0	10.69
56C	112135	366	A	26	115/208-230	None	5.0	11.31
56C	110905❖	497	A	26	115/208-230	None	5.4	11.31
56C	116922	497	A	26	115/208-230	Man.	5.4	11.31
56C	110180	422	A	28	115/208-230	None	6.0	11.81
56C	115877	422	A	28	115/208-230	Man.	6.0	11.81
56C	110908❖	562	A	30	115/208-230	None	6.4	11.81
56C	115879	562	A	32	115/208-230	Man.	6.4	11.81
143TC	121680	562	B	32	115/208-230	None	6.4	12.25
...	...	...	...	...	...	...	...	...
56C	110909	546	A	34	115/208-230	None	8.5	12.31
56C	115024☆	573	A	35	115/208-230	Man.	6.2	12.31
56HC	110910☆❖□	668	A	39	115/208-230	None	8.6	12.81
56HC	116703☆	672	A	42	115/208-230	Man.	8.6	12.81
145TC	121681	668	B	40	115/208-230	None	8.6	13.75
56HC	113931❖□†	716	A	46	115/208-230	None	10.0	13.31
56HC	114995☆	682	A	42	115/208-230	Man.	9.2	13.31
56HC	115878❖†□	716	A	43	115/208-230	Man.	10.0	13.31
145TC	121008❖†	716	B	43	115/208-230	None	10.0	13.75
...	...	...	...	...	...	...	...	...
145TC	120274☆	902	B	49	115/230	None	9.2	14.25
145TC	121465☆	902	A	44	115/208-230	Man.	9.2	13.75
56HC	115048□☆	746	A	53	208-230	Man.	14.0	13.31
145TC	121060☆	802	B	51	230	Man.	13.0	14.25
...	...	...	...	...	...	...	...	...
184TC	131631	1273	B	84	115/208-230	Man.	16.8	16.47
184TC	131857☆	1273	B	104	230	Man.	13.7	17.61
...	...	...	...	...	...	...	...	...
184TC	131632☆❖	1280	B	103	230	Man.	19.8	16.97
184TC	131633☆	1333	B	86	230	Man.	23.0	16.97
213TC	140694☆	1502	B	120	208-230	None	32.0	19.07
215TC	140695☆	1792	B	138	208-230	None	41.5	20.57
215TC	140678☆	1735	B	152	230	None	40.0	20.71

Motors in this column have NEMA Service Factors except as denoted by ❖, which have 1.15 Service Factors.

### QUICK REFERENCE

WASHGUARD C FACE MOTORS	Page 30
BRAKEMOTORS	44
WATTSAVER® C FACE MOTORS	18



# C FACE MOTORS • THREE PHASE

## LESS BASE • GENERAL PURPOSE



### DRIP-PROOF • C FACE LESS BASE • THREE PHASE

HP	RPM 60 Hz	NEMA Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Voltage	FL Amps 230V	% FL Eff.	"C" Dim. (Inches)
1/6	1725	...	...	...	...	...	...	...	...	...
1/4	3450	...	...	...	...	...	...	...	...	...
	1725	...	...	...	...	...	...	...	...	...
	1725	...	...	...	...	...	...	...	...	...
	1725	S56C	103014	\$248	A	19	208-230/460	1.4	58.0	9.24
	1725	...	...	...	...	...	...	...	...	...
1/3	3450	S56C	100375	250	A	15	208-230/460	1.4	68.0	9.31
	1725	...	...	...	...	...	...	...	...	...
	1725	S56C	100048	273	A	17	208-230/460	1.6	64.3	9.49
	1725	...	...	...	...	...	...	...	...	...
	1725	S56C	102695	343	A	22	208-230/460	1.3	77.0	10.24
	1140	...	...	...	...	...	...	...	...	...
	1140	...	...	...	...	...	...	...	...	...
1/2	3450	...	...	...	...	...	...	...	...	...
	3450	S56C	100056	268	A	17	208-230/460	1.8	69.0	9.31
	3450	...	...	...	...	...	...	...	...	...
	1725	...	...	...	...	...	...	...	...	...
	1725	...	...	...	...	...	...	...	...	...
	1725	S56C	100049	316	A	21	208-230/460	2.0	68.0	9.99
	1725	...	...	...	...	...	...	...	...	...
	1725	S56C	102200	368	A	25	208-230/460	1.8	77.0	10.74
	1140	56C	110434	467	A	26	208-230/460	2.8	66.0	10.38
3/4	3450	S56C	100378	318	A	20	208-230/460	2.4	79.0	9.81
	1725	S56C	100050	351	A	24	208-230/460	2.8	75.0	10.49
	1725	56C	114934	394	A	29	208-230/460	2.4	81.5	10.86
	1140	56C	116728	506	A	35	208-230/460	3.4	75.5	10.88
	1140	143TC	120063	506	B	36	208-230/460	3.4	75.5	11.28
1	3450	56C	110111	366	A	22	208-230/460	3.2	77.0	9.88
	3450	...	...	...	...	...	...	...	...	...
	1725	56C	110043	384	A	22	208-230/460	4.2	78.5	10.38
	1725	56C	116740	572	A	32	208-230/460	3.4	85.5	11.68
	1725	143TC	120172	384	B	26	208-230/460	4.2	78.5	11.28
	1725	143TC	121064	572	B	32	208-230/460	3.4	85.5	12.12
	1140	...	...	...	...	...	...	...	...	...
	1140	...	...	...	...	...	...	...	...	...
	1140	145TC	120082	545	B	34	208-230/460	4.0	77.0	11.78
1 1/2	3450	56C	110437	424	A	27	208-230/460	4.2	81.5	10.84
	3450	...	...	...	...	...	...	...	...	...
	3450	143TC	121668	424	B	29	208-230/460	4.2	82.1	11.78
	1725	56C	110044	447	A	27	208-230/460	5.6	78.5	10.88
	1725	56C	116741	597	A	36	208-230/460	5.6	86.5	12.68
	1725	145TC	120081	422	B	34	208-230/460	5.6	78.5	11.78
	1725	143TC	121063	597	B	36	208-230/460	5.6	86.5	13.12
	1140	...	...	...	...	...	...	...	...	...
	1140	145TC	121669	575	B	39	208-230/460	5.7	77.0	12.28

W Premium efficiency WATTSaver® Motors. See page 15 for details.

### TEFC • C FACE LESS BASE • THREE PHASE

NEMA Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Voltage	FL Amps 230V	% FL Eff.	"C" Dim. (Inches)
48CZ	102662	\$257	A	15	208-230/460	.7	71.0	9.44
48CZ	101965	334	A	15	208-230/460	1.0	67.0	9.03
48CZ	101966	292	A	18	208-230/460	1.0	78.0	9.31
48CZ	101981	292	A	17	208-230/460	1.4	58.0	8.94
S56C	101648	285	A	17	208-230/460	1.0	78.0	9.56
S56C	101767	285	A	19	208-230/460	1.4	58.0	9.69
56C	110446	281	A	20	208-230/460	1.2	77.0	9.90
48CZ	102664	297	A	20	208-230/460	1.6	64.3	9.19
S56C	101769	308	A	20	208-230/460	1.6	64.3	9.69
S56C	102863	315	A	19	208-230/460	1.3	77.0	9.56
S56C	102696	430	A	22	208-230/460	1.3	77.0	10.19
48C	101291	480	A	20	208-230/460	1.8	73.0	9.56
56C	113311	480	A	22	208-230/460	1.6	65.0	10.81
48C	100449	328	A	23	208-230/460	1.6	67.0	10.06
56C	110144	328	A	25	208-230/460	1.6	82.5	10.40
56C	114176	328	A	19	208-230/460	2.0	72.0	10.31
48CZ	100486	374	A	24	208-230/460	1.6	78.0	10.31
48CZ	102666	359	A	24	208-230/460	2.0	73.0	9.69
S56C	102861	372	A	23	208-230/460	1.8	77.0	10.06
S56C	102860	359	A	19	208-230/460	2.0	73.0	10.19
S56C	101780	461	A	25	208-230/460	1.8	77.0	10.69
56C	110163	518	A	25	208-230/460	2.4	70.0	11.31
56C	110448	343	A	21	208-230/460	2.4	75.5	10.81
56C	110047	388	A	22	208-230/460	2.8	77.0	10.81
56C	114213	497	A	27	208-230/460	2.7	81.5	11.31
56C	112378	543	A	29	208-230/460	3.0	75.5	11.81
143TC	120097	543	B	33	208-230/460	3.0	75.5	12.25
56C	110112	404	A	21	208-230/460	3.2	77.0	10.81
56C	116748	545	A	29	208-230/460	2.8	80.0	11.31
56C	110048	414	A	24	208-230/460	3.8	77.0	11.31
56C	114638	691	A	34	208-230/460	3.4	85.5	12.81
143TC	120024	414	B	26	208-230/460	3.8	77.0	11.75
143TC	121067	691	B	36	208-230/460	3.4	85.5	13.25
56C	112379	532	A	32	208-230/460	4.0	77.0	12.31
56C	116749	726	A	47	208-230/460	3.8	82.5	13.75
145TC	120098	532	B	36	208-230/460	4.0	77.0	12.75
56C	110192	445	A	28	208-230/460	4.2	81.5	11.81
56C	116750	619	A	33	208-230/460	4.0	84.0	13.25
143TC	120105	440	B	33	208-230/460	4.2	80.3	12.75
56C	110125	439	A	29	208-230/460	5.0	78.5	11.81
56C	116743	729	A	41	208-230/460	4.8	86.5	13.31
145TC	120037	426	B	32	208-230/460	5.0	80.0	12.75
145TC	121066	729	B	41	208-230/460	4.8	86.5	13.75
56C	113634	607	A	39	208-230/460	5.7	77.0	13.31
145TC	120161	607	B	39	208-230/460	5.7	77.0	13.75

➤ Shaft extension has keyway and flat 180° apart for ease of mounting.  
Useable shaft is 1 1/2" long by 1/2" diameter, 1/8" keyway.

● These motors are totally enclosed, non-ventilated — Others are fan cooled.

CONTINUED ON NEXT PAGE

All three phase motors, 1 HP and above, are inverter rated. Refer to page 5 for speed ranges.

# C FACE MOTORS • THREE PHASE

LESS BASE • GENERAL PURPOSE



## DRIP PROOF • C FACE LESS BASE • THREE PHASE

HP	RPM 60 Hz	NEMA Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Voltage	FL Amps 230V	% FL Eff.	"C" Dim. (Inches)	
2	3450	56C	<b>113894</b>	\$491	A	31	208-230/460	5.6	82.5	11.34	
	3450	...	...	...	...	...	...	...	...	...	
	3450	143TC	<b>121670</b>	491	B	33	208-230/460	6.2	82.9	11.88	
	1725	56C	<b>115553</b>	478	A	32	208-230/460	6.2	78.5	11.19	
	1725	56C	<b>116742</b> [W]	671	A	41	208-230/460	5.8	86.5	13.18	
	1725	145TC	<b>120035</b>	463	B	33	208-230/460	6.2	78.5	12.28	
	1725	145TC	<b>121071</b> [W]	671	B	41	208-230/460	5.8	86.5	13.62	
	1140	184TC	<b>132059</b>	610	B	45	208-230/460	6.0	84.0	13.78	
	3	3450	56C	<b>114420</b>	522	A	37	208-230/460	7.6	84.0	11.84
		3450	145TC	<b>121187</b>	441	B	39	208-230/460	7.6	84.0	12.28
3450		...	...	...	...	...	...	...	...	...	
1725		...	...	...	...	...	...	...	...	...	
1725		145TC	<b>121405</b>	551	B	45	208-230/460	8.6	82.5	13.12	
1740		182TC	<b>131489</b>	513	B	43	208-230/460	8.0	80.0	11.69	
1760		182TC	<b>131518</b> [W]	719	B	75	208-230/460	7.8	89.5	14.20	
1140		213TC	<b>140765</b>	804	B	140	208-230/460	11.6	86.5	15.76	
5		3450	145TC	<b>121664</b>	527	B	45	208-230/460	12.4	85.5	13.75
		3450	182TC	<b>131779</b>	549	B	84	208-230/460	13.2	82.5	13.19
	1725	184TC	<b>131490</b>	565	B	62	208-230/460	14.2	84.0	12.69	
	1760	184TC	<b>131517</b> [W]	845	B	96	208-230/460	12.8	89.5	15.20	
	1140	215TC	<b>140766</b>	804	B	120	208-230/460	17.6	87.5	16.75	
	7½	3450	184TC	<b>131780</b>	725	B	73	208-230/460	18.4	84.0	14.19
3450		...	...	...	...	...	...	...	...	...	
3450		...	...	...	...	...	...	...	...	...	
1740		184TC	<b>131739</b>	798	B	108	230/460	20.0	87.0	14.70	
1740		...	...	...	...	...	...	...	...	...	
1750		S213TC	<b>131527</b>	798	B	88	230/460	20.0	87.0	15.69	
1760		213TC	<b>140580</b>	818	B	115	208-230/460	20.0	88.5	15.25	
1760		213TC	<b>140483</b> [W]	936	B	132	208-230/460	20.6	91.0	16.25	
10		3450	213TC	<b>140688</b>	983	B	85	208-230/460	25.0	85.5	16.53
		3450	...	...	...	...	...	...	...	...	...
	1740	215TC	<b>140108</b>	1007	B	132	208-230/460	28.0	89.5	16.75	
	1760	215TC	<b>140485</b> [W]	1058	B	144	208-230/460	26.8	91.9	17.25	
	1750	...	...	...	...	...	...	...	...	...	
	15	3450	215TC	<b>140689</b>	1336	B	100	208-230/460	38.0	86.5	18.03
3450		...	...	...	...	...	...	...	...	...	
1760		254TC	<b>151682</b>	1474	C	265	208-230/460	37.6	91.0	20.94	
20		3500	254TC	<b>151683</b>	1749	C	258	208-230/460	46.6	90.2	20.94
	1760	256TC	<b>151684</b>	1802	C	307	208-230/460	48.0	92.0	22.60	
	25	3525	256TC	<b>151685</b>	2035	C	292	208-230/460	57.0	91.0	22.60
1760		284TC	<b>151686</b>	2196	C	388	208-230/460	59.6	91.7	23.54	
30	3500	284TSC	<b>151687</b>	2338	C	373	208-230/460	70.4	91.0	22.17	
	1760	...	...	...	...	...	...	...	...	...	
40	1770	...	...	...	...	...	...	...	...	...	
	50	1770	...	...	...	...	...	...	...	...	...
60		1770	...	...	...	...	...	...	...	...	...

† Class F insulated.  
 ♣ These totally enclosed three phase motors have 1.0 service factors.  
 [W] Premium efficiency WATSAVER® Motors. See page 15 for details.  
 All 180 and 210 frame Rolled Steel motors have Class F Insulation.

## TEFC • C FACE LESS BASE • THREE PHASE

NEMA Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Voltage	FL Amps 230V	% FL Eff.	"C" Dim. (Inches)
56C	<b>111273</b>	\$506	A	36	208-230/460	5.6	82.5	12.31
56C	<b>116751</b> [W]	717	A	44	208-230/460	4.8	85.5	14.25
145TC	<b>120061</b>	506	B	34	208-230/460	5.6	82.5	12.75
56C	<b>110451</b>	467	A	34	208-230/460	6.2	81.5	12.81
56C	<b>116744</b> [W]	765	A	45	208-230/460	5.8	86.5	13.82
145TC	<b>120038</b>	456	B	35	208-230/460	6.2	81.5	12.75
145TC	<b>121065</b> [W]	765	B	45	208-230/460	5.8	86.5	14.26
184TC	<b>131525</b>	707	B	59	208-230/460	7.4	80.0	13.97
56C	<b>111630</b>	575	A	37	208-230/460	7.6	84.0	12.81
145TC	<b>120993</b>	575	B	38	208-230/460	7.6	84.0	13.25
182TC	<b>131513</b>	644	B	55	208-230/460	8.0	84.0	13.97
56C	<b>113890</b> ♣	623	A	43	208-230/460	8.6	82.5	13.81
145TC	<b>121035</b> ♣	604	B	44	208-230/460	8.6	82.5	14.25
182TC	<b>131491</b>	579	B	52	208-230/460	9.0	82.5	13.97
182TC	<b>131503</b> [W]	819	B	72	208-230/460	7.8	89.5	14.96
S213TC	<b>131642</b>	890	B	89	208-230/460	9.6	81.5	16.96
...	...	...	...	...	...	...	...	...
184TC	<b>131514</b>	722	B	68	208-230/460	12.4	85.5	13.97
184TC	<b>131492</b>	663	B	64	208-230/460	13.2	82.5	14.48
184TC	<b>131501</b> [W]	886	B	90	208-230/460	12.8	89.5	15.97
215TC	<b>140535</b>	1205	B	120	208-230/460	17.6	87.5	18.21
184TC	<b>131510</b>	865	B	89	208-230/460	18.4	86.5	14.97
S213TC	<b>131912</b>	899	B	91	208-230/460	18.4	86.5	15.46
213TC	<b>151345</b>	956	C	158	208-230/460	18.4	85.5	18.84
184TC	<b>131606</b>	852	B	66	208-230/460	19.6	87.0	16.47
213TC	<b>151346</b>	922	C	162	208-230/460	18.4	87.9	18.84
S213TC	<b>131528</b>	852	B	102	208-230/460	19.6	87.0	16.96
...	...	...	...	...	...	...	...	...
213TC	<b>140486</b> [W]	1029	B	144	208-230/460	21.4	91.7	18.70
215TC	<b>140690</b>	1066	B	105	208-230/460	24.0	86.5	20.57
215TC	<b>151347</b>	1127	C	172	208-230/460	23.8	86.2	20.34
215TC	<b>140109</b>	1021	B	141	208-230/460	26.0	89.5	18.71
215TC	<b>140484</b> [W]	1242	B	160	208-230/460	26.6	91.7	19.70
215TC	<b>151348</b>	1087	C	185	208-230/460	24.6	88.4	20.34
215TC	<b>140691</b>	1503	B	145	208-230/460	37.0	88.5	20.57
215TC	<b>151349</b>	1586	C	200	208-230/460	36.0	89.2	16.61
254TC	<b>151350</b>	1543	C	284	208-230/460	37.0	90.0	23.80
256TC	<b>151351</b>	2038	C	270	208-230/460	48.0	89.6	25.50
256TC	<b>151352</b>	1946	C	270	208-230/460	48.0	91.2	25.50
...	...	...	...	...	...	...	...	...
284TC	<b>151507</b>	2451	C	390	208-230/460	60.0	91.3	26.26
...	...	...	...	...	...	...	...	...
286TC	<b>151508</b>	2947	C	411	208-230/460	70.0	91.5	27.83
324TC	<b>151509</b>	3770	C	548	208-230/460	92.0	92.1	29.53
326TC	<b>151510</b>	4349	C	594	208-230/460	114.2	92.4	31.02
364TC	<b>151519</b>	6536	C	778	208-230/460	140.0	92.7	32.64

SHADED FRAME INDICATES CAST IRON CONSTRUCTION

All three phase motors, 1 HP and above, are inverter rated. Refer to page 5 for speed ranges.



# C FACE MOTORS • THREE PHASE

WITH BASE • GENERAL PURPOSE



## DRIP PROOF • C FACE WITH BASE • THREE PHASE

HP	RPM 60 Hz	NEMA Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Voltage	FL Amps 230V	% FL Eff.	"C" Dim. (Inches)
1/3	1725	S56C	<b>100599</b>	\$311	A	18	208-230/460	1.6	64.3	9.49
	1725	...	...	...	...	...	...	...	...	...
	1725	S56C	<b>103021</b> W	361	A	23	208-230/460	1.3	77.0	10.24
1/2	3450	S56C	<b>100600</b>	296	A	17	208-230/460	2.4	69.0	9.31
	3450	...	...	...	...	...	...	...	...	...
	1725	S56C	<b>100601</b>	352	A	20	208-230/460	2.0	68.0	9.99
	1725	...	...	...	...	...	...	...	...	...
	1725	S56C	<b>103022</b> W	381	A	26	208-230/460	1.8	77.0	10.74
3/4	3450	S56C	<b>102971</b>	335	A	21	208-230/460	2.4	79.0	9.85
	1725	S56C	<b>100602</b>	391	A	25	208-230/460	2.8	75.0	10.49
	1725	56C	<b>116762</b> W	404	A	30	208-230/460	2.4	81.5	10.86
	1140	...	...	...	...	...	...	...	...	...
	1140	...	...	...	...	...	...	...	...	...
1	3450	56C	<b>116784</b>	384	A	23	208-230/460	3.2	77.0	9.84
	1725	56C	<b>110901</b>	458	A	28	208-230/460	4.2	78.5	10.38
	1725	56C	<b>116763</b> W	577	A	33	208-230/460	3.4	85.5	11.68
	1740	...	...	...	...	...	...	...	...	...
	1725	143TC	<b>G121650</b>	453	B	34	208-230/460	3.1	82.5	11.28
1 1/2	3450	56C	<b>116785</b>	455	A	28	208-230/460	4.2	81.5	10.84
	3450	...	...	...	...	...	...	...	...	...
	3450	...	...	...	...	...	...	...	...	...
	1725	56C	<b>110902</b>	482	A	29	208-230/460	5.6	78.5	10.88
	1725	56C	<b>116764</b> W	599	A	37	208-230/460	5.6	86.5	12.68
	1725	143TC	<b>G121674</b> W	577	B	34	208-230/460	3.4	85.5	12.12
	1725	145TC	<b>G121651</b>	474	B	32	208-230/460	4.4	84.0	12.12
2	3450	56C	<b>114218</b>	563	A	34	208-230/460	5.6	82.5	11.40
	3450	...	...	...	...	...	...	...	...	...
	3450	...	...	...	...	...	...	...	...	...
	1725	56HC	<b>116630</b> □	506	A	32	208-230/460	6.2	78.5	11.38
	1725	56HC	<b>116765</b> W	676	A	42	208-230/460	5.8	86.5	13.18
	1725	145TC	<b>G120275</b>	508	B	35	208-230/460	5.6	84.0	12.62
	1725	145TC	<b>121676</b> W	676	B	42	208-230/460	5.8	86.5	13.62
3	3450	...	...	...	...	...	...	...	...	...
	3500	145TC	<b>G121072</b>	509	B	35	230/460	7.6	84.0	12.78
	3515	...	...	...	...	...	...	...	...	...
	3450	...	...	...	...	...	...	...	...	...
	3510	...	...	...	...	...	...	...	...	...
	1740	...	...	...	...	...	...	...	...	...
	1740	56HCZ	<b>116631</b> □	586	A	38	208-230/460	8.6	82.5	13.62
	1760	182TC	<b>G130325</b>	582	B	58	208-230/460	8.4	86.5	12.69
	1760	182TC	<b>132081</b> W	732	B	76	208-230/460	7.8	89.5	14.20
	1750	...	...	...	...	...	...	...	...	...

## TEFC • C FACE WITH BASE • THREE PHASE

NEMA Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Voltage	FL Amps 230V	% FL Eff.	"C" Dim. (Inches)
S56C	<b>102921</b> ●	\$343	A	18	208-230/460	1.3	77.0	9.56
S56C	<b>102922</b>	342	A	19	208-230/460	1.3	77.0	10.19
S56C	<b>102697</b> W	439	A	22	208-230/460	1.3	77.0	10.19
56C	<b>110182</b> ●	340	A	26	208-230/460	1.6	82.5	10.40
56C	<b>114142</b>	340	A	21	208-230/460	2.6	68.0	10.81
S56C	<b>102919</b> ●	397	A	22	208-230/460	2.0	77.0	10.06
S56C	<b>102917</b>	397	A	19	208-230/460	2.0	73.0	10.19
S56C	<b>102024</b> W	472	A	23	208-230/460	1.8	77.0	10.69
56C	<b>110914</b>	533	A	25	208-230/460	2.4	70.0	11.31
56C	<b>110915</b>	368	A	23	208-230/460	2.4	75.5	10.81
56C	<b>110916</b>	427	A	22	208-230/460	2.8	77.0	10.81
56C	<b>114624</b> W	507	A	25	208-230/460	2.7	81.5	11.31
56C	<b>116340</b>	558	A	29	208-230/460	3.0	75.5	11.81
143TC	<b>120485</b>	558	B	34	208-230/460	3.0	75.5	13.25
56C	<b>110181</b>	435	A	24	208-230/460	3.2	77.0	10.81
56C	<b>110912</b>	455	A	24	208-230/460	3.6	77.0	11.31
56C	<b>116745</b> W	715	A	34	208-230/460	3.4	85.5	12.81
145TC	<b>G121286</b>	501	B	35	208-230/460	3.8	82.5	13.25
143TC	<b>121179</b> W	715	B	34	208-230/460	3.4	85.5	13.25
145TC	<b>G120428</b>	608	B	35	208-230/460	3.6	80.0	13.25
56C	<b>110917</b>	488	A	29	208-230/460	4.2	81.5	11.81
143TC	<b>G121290</b>	525	B	27	208-230/460	4.0	82.5	13.25
143TC	<b>121672</b> W	645	B	33	208-230/460	3.6	84.0	13.25
56C	<b>110918</b>	480	A	30	208-230/460	5.0	78.5	11.81
56C	<b>116746</b> W	741	A	37	208-230/460	5.6	86.5	13.31
...	...	...	...	...	...	...	...	...
145TC	<b>G121287</b>	500	B	37	208-230/460	4.4	84.0	13.25
145TC	<b>121180</b> W	741	B	37	208-230/460	5.6	86.5	13.75
56HC	<b>114198</b> □	643	A	41	208-230/460	5.7	77.0	13.31
56HCZ	<b>116592</b> *	643	A	44	208-230/460	5.7	77.0	13.75
56C	<b>113927</b>	553	A	34	208-230/460	5.6	82.5	12.31
145TC	<b>G121510</b>	577	B	45	208-230/460	5.2	84.0	13.25
145TC	<b>121673</b> W	661	B	44	208-230/460	4.8	85.5	13.75
56HC	<b>116106</b> □	512	A	36	208-230/460	6.2	81.5	12.81
56HC	<b>116747</b> □W	775	A	43	208-230/460	5.8	86.5	13.82
145TC	<b>G120276</b>	524	B	45	208-230/460	5.6	84.0	13.75
145TC	<b>121181</b> W	775	B	43	208-230/460	5.8	86.5	14.26
184TC	<b>G131497</b>	769	B	76	208-230/460	7.2	86.5	15.47
56HC	<b>114615</b> ♣□	616	A	38	208-230/460	7.6	84.0	12.81
145TC	<b>G120991</b>	655	B	35	208-230/460	7.4	85.5	13.75
182TC	<b>G131899</b>	725	B	61	208-230/460	7.6	85.5	13.97
182TC	<b>132079</b> W	954	B	70	208-230/460	7.6	86.5	13.96
182TC	<b>G151564</b>	772	C	94	208-230/460	8.5	87.5	16.76
56HC	<b>116107</b> □	649	B	45	208-230/460	8.6	82.5	13.81
56HCZ	<b>116388</b> *	649	A	46	208-230/460	8.6	82.5	14.25
182TC	<b>G130326</b>	650	B	68	208-230/460	8.2	87.5	13.96
182TC	<b>131504</b> W	836	B	75	208-230/460	7.8	89.5	14.96
182TC	<b>G151565</b>	754	C	94	208-230/460	8.5	87.5	16.14
215TC	<b>G140602</b>	963	B	118	230/460	12.0	87.5	17.71

● These motors are totally enclosed, non-ventilated — Others are fan cooled.  
 ♣ These totally enclosed three phase motors have 1.0 service factors.  
 □ Combination 56H base motors have mounting holes for NEMA 56 and NEMA 143-145T and standard NEMA 56C face and shaft.  
 \* 56HCZ motors have mounting holes for NEMA 56 and NEMA 143-5T and a standard NEMA 143-5T shaft.  
 W Premium efficiency WATTSaver® Motors. See page 15 for details.

All 180 and 210 frame Rolled Steel motors have Class F Insulation.

SHADED FRAME INDICATES CAST IRON CONSTRUCTION

Catalog numbers in green are EPACT motors.

All three phase motors, 1 HP and above, are inverter rated. Refer to page 5 for speed ranges.

CONTINUED ON NEXT PAGE

# C FACE MOTORS • THREE PHASE



WITH BASE • GENERAL PURPOSE

C Face Motors

## DRIP PROOF • C FACE WITH BASE • THREE PHASE

HP	RPM 60 Hz	NEMA Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Voltage	F.L. Amps 230V	% F.L. Eff.	"C" Dim. (Inches)		
5	3490	145TC	<b>G121663</b>	\$538	B	45	208-230/460	12.4	85.5	13.75		
	3450	...	...	...	...	...	...	...	...	...		
	3450	...	...	...	...	...	...	...	...	...		
	3450	182TC	<b>G131249</b>	553	B	84	208-230/460	12.2	85.5	13.20		
	1760	184TC	<b>G130327</b>	636	B	80	208-230/460	13.2	87.5	13.69		
	1760	184TC	<b>132082</b> [W]	858	B	97	208-230/460	12.8	89.5	15.20		
	1750	...	...	...	...	...	...	...	...	...		
	1140	...	...	...	...	...	...	...	...	...		
	7½	3450	184TC	<b>G131250</b>	904	B	92	208-230/460	17.6	87.5	14.70	
		3450	...	...	...	...	...	...	...	...	...	
3450		...	...	...	...	...	...	...	...	...		
3510		...	...	...	...	...	...	...	...	...		
1740		213TC	<b>G140589</b>	804	B	100	208-230/460	20.0	88.5	15.75		
1760		213TC	<b>140767</b> [W]	943	B	132	208-230/460	20.6	91.0	16.25		
1760		213TC	<b>G150170</b>	796	C	157	208-230/460	19.6	88.5	16.38		
1170		...	...	...	...	...	...	...	...	...		
10		3450	213TC	<b>G140692</b>	1003	B	105	208-230/460	23.4	88.5	18.03	
		3510	...	...	...	...	...	...	...	...	...	
	3510	213TC	<b>G150171</b>	1056	C	180	208-230/460	27.6	88.5	16.38		
	1740	215TC	<b>G140146</b>	988	B	162	208-230/460	28.0	89.5	16.75		
	1760	215TC	<b>140768</b> [W]	1070	B	144	208-230/460	26.8	91.9	17.25		
	1760	215TC	<b>G150172</b>	1048	C	183	208-230/460	25.0	89.5	18.62		
	1170	...	...	...	...	...	...	...	...	...		
	15	3450	215TC	<b>G140693</b>	1387	B	130	208-230/460	34.0	90.2	19.28	
		3510	215TC	<b>G150173</b>	1459	C	191	208-230/460	35.0	89.5	18.62	
		3510	...	...	...	...	...	...	...	...	...	
3525		...	...	...	...	...	...	...	...	...		
1770		254TC	<b>G150175</b>	1496	C	266	208-230/460	37.6	91.0	21.32		
1770		...	...	...	...	...	...	...	...	...		
1170		...	...	...	...	...	...	...	...	...		
20		3525	254TC	<b>G150070</b>	1764	C	275	208-230/460	46.6	90.2	21.38	
		3525	...	...	...	...	...	...	...	...	...	
		1770	256TC	<b>G150071</b>	1821	C	325	208-230/460	49.0	91.0	23.03	
	1770	...	...	...	...	...	...	...	...	...		
	25	3525	256TC	<b>G151688</b>	2208	C	300	208-230/460	57.0	91.0	22.60	
		3550	...	...	...	...	...	...	...	...	...	
		3550	...	...	...	...	...	...	...	...	...	
		3550	...	...	...	...	...	...	...	...	...	
		1770	284TC	<b>G150073</b>	2269	C	390	208-230/460	59.6	91.7	23.54	
		1770	...	...	...	...	...	...	...	...	...	
30		3550	...	...	...	...	...	...	...	...	...	
		3550	...	...	...	...	...	...	...	...	...	
		1770	286TC	<b>G151377</b>	2599	C	430	208-230/460	72.0	92.4	25.00	
		1770	...	...	...	...	...	...	...	...	...	
	40	3550	...	...	...	...	...	...	...	...	...	
		1780	324TC	<b>G151378</b>	3294	C	491	208-230/460	96.0	91.0	26.02	
		1780	...	...	...	...	...	...	...	...	...	
		50	3550	...	...	...	...	...	...	...	...	...
			1780	326TC	<b>G151379</b>	3900	C	599	208-230/460	120.0	93.0	27.52
			1780	...	...	...	...	...	...	...	...	...
60			3570	...	...	...	...	...	...	...	...	...
			1780	364TC	<b>G151689</b>	4895	C	725	208-230/460	141.0	93.6	28.01
			1780	...	...	...	...	...	...	...	...	...
			75	3570	...	...	...	...	...	...	...	...
	1780			365TC	<b>G151690</b>	5946	C	771	208-230/460	177.0	94.1	31.18
	1780			...	...	...	...	...	...	...	...	...
	100			1780	404TC	<b>G151691</b>	7568	C	997	208-230/460	240.0	94.1
		1780		...	...	...	...	...	...	...	...	...
		1780		...	...	...	...	...	...	...	...	...

## TEFC • C FACE WITH BASE • THREE PHASE

NEMA Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Voltage	F.L. Amps 230V	% F.L. Eff.	"C" Dim. (Inches)
...	...	...	...	...	...	...	...	...
184TC	<b>G131173</b>	\$720	B	80	208-230/460	12.0	87.5	14.47
184TC	<b>132080</b> [W]	943	B	100	208-230/460	12.0	88.5	16.46
184TC	<b>G151446</b>	805	C	101	208-230/460	12.0	87.5	16.76
184TC	<b>G130328</b>	746	B	81	208-230/460	13.0	87.5	14.97
184TC	<b>131502</b> [W]	905	B	99	208-230/460	12.8	89.5	15.97
184TC	<b>G151566</b>	827	C	101	208-230/460	13.8	87.5	16.14
215TC	<b>G140482</b>	1237	B	144	208-230/460	17.6	87.5	18.21
184TC	<b>G130990</b>	931	B	91	208-230/460	16.8	88.5	15.97
S213TC	<b>G131774</b>	945	B	70	208-230/460	16.8	88.5	16.96
213TC	<b>140770</b> [W]	1166	B	160	208-230/460	17.8	90.2	19.64
213TC	<b>G150166</b>	1014	C	153	208-230/460	17.8	88.5	18.95
213TC	<b>G140183</b>	892	B	153	208-230/460	20.4	89.5	17.71
213TC	<b>140521</b> [W]	1035	B	144	208-230/460	21.4	91.7	18.70
213TC	<b>G150165</b>	944	C	156	208-230/460	19.2	89.5	18.95
254TC	<b>G150138</b>	1874	C	231	208-230/460	20.0	89.5	23.80
213TC	<b>G140696</b>	1177	B	115	208-230/460	24.0	89.5	20.57
215TC	<b>140769</b> [W]	1317	B	175	208-230/460	23.6	91.7	21.09
215TC	<b>G150168</b>	1188	B	163	208-230/460	23.6	89.5	20.36
215TC	<b>G140147</b>	1045	B	162	208-230/460	26.0	89.5	18.71
215TC	<b>140522</b> [W]	1250	B	160	208-230/460	26.6	91.7	19.70
215TC	<b>G150167</b>	1111	C	178	208-230/460	25.2	89.5	20.36
256TC	<b>G150139</b>	2088	C	252	208-230/460	26.2	89.5	25.50
215TC	<b>G140697</b>	1557	B	161	208-230/460	36.0	90.2	20.57
...	...	...	...	...	...	...	...	...
254TC	<b>G150103</b>	1657	C	245	208-230/460	35.0	90.2	23.80
254TC	<b>171586</b> [W]	2084	C	292	208-230/460	34.6	91.7	23.19
254TC	<b>G150102</b>	1594	C	268	208-230/460	36.6	91.0	23.80
254TC	<b>171587</b> [W]	2184	C	290	208-230/460	36.0	92.4	23.19
284TC	<b>G150104</b>	3110	C	369	208-230/460	40.4	90.2	26.26
256TC	<b>G150079</b>	2092	C	257	208-230/460	46.2	90.2	25.50
256TC	<b>171588</b> [W]	2560	C	326	208-230/460	46.0	92.4	24.92
256TC	<b>G150080</b>	1946	C	321	208-230/460	48.2	91.0	25.50
256TC	<b>171589</b> [W]	2608	C	332	208-230/460	49.0	93.0	24.92
...	...	...	...	...	...	...	...	...
284TSC	<b>G150106</b>	2471	C	362	208-230/460	58.2	91.0	24.88
284TSC	<b>171590</b> [W]	3217	C	393	208-230/460	56.8	93.0	24.88
284TC	<b>G151383</b>	2471	C	362	208-230/460	58.2	91.0	26.26
284TC	<b>G150081</b>	2509	C	387	208-230/460	58.8	92.4	26.26
284TC	<b>171591</b> [W]	3328	C	395	208-230/460	59.0	94.0	26.26
286TSC	<b>G150108</b>	2915	C	375	208-230/460	69.2	91.0	26.46
286TC	<b>G151396</b>	2915	C	375	208-230/460	69.2	91.0	27.83
286TC	<b>G150082</b>	2966	C	433	208-230/460	69.8	92.4	27.83
286TC	<b>171592</b> [W]	4010	C	442	208-230/460	70.0	93.6	27.83
324TSC	<b>G150110</b>	4298	C	574	208-230/460	93.0	91.7	28.00
324TC	<b>G150083</b>	3786	C	572	208-230/460	95.2	93.0	29.53
324TC	<b>171593</b> [W]	5184	C	538	208-230/460	92.0	94.1	29.53
326TSC	<b>G150112</b>	4424	C	604	208-230/460	112.0	92.4	29.53
326TC	<b>G150084</b>	4388	C	631	208-230/460	117.8	93.0	31.02
326TC	<b>171594</b> [W]	5695	C	597	208-230/460	117.0	94.5	31.02
364TSC	<b>G150114</b>	7232	C	860	208-230/460	139.0	93.0	30.51
364TC	<b>G150085</b>	6619	C	699	208-230/460	138.0	93.6	32.64
364TC	<b>171595</b> [W]	9032	C	676	208-230/460	137.0	95.4	32.64
365TSC	<b>G150115</b>	8683	C	773	208-230/460	172.0	93.0	31.49
365TC	<b>G150086</b>	8396	C	757	208-230/460	173.0	94.1	33.62
365TC	<b>171596</b> [W]	10392	C	743	208-230/460	170.0	95.8	33.62
...	...	...	...	...	...	...	...	...
405TC	<b>G151680</b>	10501	C	1100	208-230/460	229.0	94.5	37.91
405TC	<b>171597</b> [W]	12725	C	1002	208-230/460	225.0	95.4	37.91

Motors in this column have NEMA Service Factors — see page 308 for details.

[W] Premium efficiency WATTSaver® Motors. See page 15 for details.