

RGZESD TEFC Motors



High efficiency severe duty TEFC motors are ideal for both indoor and outdoor applications and in severe duty operating atmospheres. These motors are ideal for use in chemical processing, mining, foundry, pulp and paper, waste management and petro/chemical.

Performance Specifications

- 1 to 400 HP
- 1.15 service factor, 40°C ambient
- 3600, 1800, 1200, 900 or 720 RPM
- 3 phase, 60 Hz; 230/460 volt operation under 25 HP, 460 volt 25 HP and above; 200 & 575 volt available
- Meets or exceeds NEMA Energy Efficiency standards
- Class F insulation, Class B temperature rise
- NEMA Design B, Continuous Duty
- 143T through S449 frame




nema MOTORS

SIEMENS

RGZESD

TEFC Motors



Features for Long Life

Frame & End Shields – Cast iron construction for exceptional structural integrity with condensation T-drains. Lifting eyebolts are included for frames 213T to S449.

Rotor – A unique offset rotor bar design provides improved efficiency while larger bars and end rings reduce resistance for lower rotor losses. Each die cast aluminum rotor assembly is dynamically balanced for extended bearing life, and includes a high-strength carbon steel (C1045) shaft for maximum rotor performance.

Stator/Windings – Manufactured with premium electrical-grade steel laminations and copper electrical magnet wire to lower losses for improved efficiencies. A unique stator core design lowers flux density while increasing cooling capacity. Large conductor cross section reduces resistance, also lowering stator losses.

Insulation – Proprietary inverter-rated Class F non-hygroscopic insulation system with NEMA Class B temperature rise, provides an extra margin of thermal life. Varnish system application ensures maximum wire penetration to provide protection from moisture, corrosion and electrical shock. This insulation system meets or exceeds NEMA MG1-2003, Part 31 making all motors suitable for operation with variable frequency drives.

Cooling – A bi-directional, non-sparking fan is locked and keyed to the shaft. Its low-inertia design reduces windage losses, improves airflow, reduces noise and provides dependable cooling. Cast iron fan covers are provided on all frame sizes.

Bearings – Regreasable, oversized single-shielded with cast iron inner caps. Alemite grease fittings on the inlets and pipe plugs on the relief ports for ease of routine maintenance. For added bearing protection, 143T-256T frames have a drive end shaft seal and 284T-449T frames have a drive end shaft V-ring slinger.

Lubrication – A specially formulated, high temperature tested, polyurea-based grease is used to provide more than four times the lubrication life of other polyurea greases.

Oversized Conduit Box – Cast iron construction that is larger than industry standards, diagonally split, neoprene-gasketed and rotatable in 90° increments for quick and easy connections. Includes a ground lug and non-wicking, clearly and permanently marked leads.

Corrosion Resistance – Cast iron construction, zinc-plated hardware, epoxy enamel paint and stainless steel nameplate resist rust and corrosion.

Modifiable – All Siemens motors are available with a wide variety of modifications to meet your specific motor needs.

Siemens Energy & Automation, Inc.
3333 Old Milton Parkway
Alpharetta, GA 30005

1-800-964-4114
info.sea@siemens.com
www.sea.siemens.com

Siemens Canada, Ltd.
2185 Derry Road West
Mississauga, ON L5N 7A6

905-819-5800
Customer Interaction Centre **888-303-3353**
www.siemens.ca

© 2006 Siemens Energy & Automation, Inc. All rights reserved.
Siemens is a registered trademark of Siemens AG. Product names mentioned may be trademarks or registered trademarks of their respective companies. Specifications subject to change without notice.

NMFL-00802-0106 New 5M0106M2 Printed in USA