

RGZZESDI TEFC Motors



Inverter Duty High Efficiency Explosion-Proof motors are ideal for both variable torque and constant torque loads, designed for inverter or vector applications; are UL® listed for dust ignition-proof environments, and are suitable for use in Class I, Group C and/or D, Class II, Groups F & G, Division 1 hazardous areas. These motors are well suited to be used in adjustable speed applications such as chemical processing, mining, foundry, pulp and paper, waste management, and petro/chemical.

Performance Specifications

- 1 to 200 HP
- 6:1 variable or 6:1 constant torque speed range
- 1.0 service factor
- 40°C ambient
- T3B temperature code (Group D)
- T3C temperature code (Group C)
- 3600, 1800, 1200, or 900 RPM
- 3 phase, 60 Hz; 460 volt; 200, 230 & 575 volt available
- Class F insulation
- Continuous Duty
- 143T through 449T frame



nema MOTORS

SIEMENS

RGZZESDI

TEFC Motors



Features for Long Life

Frame & End Shields – Cast iron construction for exceptional structural integrity, with UL® listed breather drains on 404T to 449T frames. Lifting eyebolts are included for frames 213T to 449T.

Rotor – A unique offset rotor bar design provides improved efficiency while larger bars and end rings reduce resistance for lower rotor losses. Each die cast aluminum rotor assembly is dynamically balanced for extended bearing life, and includes a high-strength carbon steel (C1045) shaft for maximum rotor performance.

Stator/Windings – Manufactured with premium electrical-grade steel laminations and copper electrical magnet wire to lower losses for improved efficiencies. A unique stator core design lowers flux density while increasing cooling capacity. Large conductor cross section reduces resistance, also lowering stator losses.

Insulation – Proprietary inverter-rated Class F non-hygroscopic (corona resistant) insulation system with NEMA Class B temperature rise, provides an extra margin of thermal life. All motors are equipped with two series connected, normally closed, Class B thermostats for detection of overload conditions and/or excessive heating. Suitable for operation from adjustable speed drives with an insulation system that meets or exceeds NEMA MG1-2003, Part 31.

Cooling – A bi-directional, non-sparking fan is locked and keyed to the shaft. Its low-inertia design reduces windage losses, improves airflow, reduces noise and provides dependable cooling. Cast iron fan covers are provided on all frame sizes.

Bearings – Regreasable, oversized single-shielded with cast iron inner caps. Alemite grease fittings on the inlets and pipe plugs on the relief ports for ease of routine maintenance. For added bearing protection, 143T-256T frames have a drive end shaft seal and 284T-449T frames have a drive end shaft V-ring slinger.

Lubrication – A specially formulated, high temperature tested, polyurea-based grease is used to provide more than four times the lubrication life of other polyurea greases.

Oversized Conduit Box – Cast iron construction that is larger than industry standards, diagonally split and rotatable in 90° increments for quick and easy connections. Includes a ground lug and non-wicking, clearly and permanently marked leads.

Corrosion Resistance – Cast iron construction, zinc-plated hardware, epoxy enamel paint and stainless steel nameplate resist rust and corrosion.

Modifiable – All Siemens motors are available with a wide variety of modifications to meet your specific motor needs.

Siemens Energy & Automation, Inc.
3333 Old Milton Parkway
Alpharetta, GA 30005

1-800-964-4114
info.sea@siemens.com
www.sea.siemens.com

Siemens Canada, Ltd.
2185 Derry Road West
Mississauga, ON L5N 7A6

905-819-5800
Customer Interaction Centre **888-303-3353**
www.siemens.ca

© 2006 Siemens Energy & Automation, Inc. All rights reserved.
Siemens is a registered trademark of Siemens AG. Product names mentioned may be trademarks or registered trademarks of their respective companies. Specifications subject to change without notice.

NMFL-0????-0106 New 5M0106M2 Printed in USA