


# Permanent Split Capacitor Direct Drive Fan Single Shaft 5.0" Dia., Open, Air Over

## APPLICATIONS:

Designed for use on direct drive fan & blowers.

## FEATURES:

- Reversible Unless Noted
- Sleeve Bearings have All Angle Thrust System
- Designed for use with 370V Capacitors
- Continuous Duty, Air Over
- 24" Line Leads unless otherwise noted
- Automatic Reset Thermal Overload Protector
- Connection and Capacitor Information Furnished in the Nameplate Data
- Discount Symbol: DS-3HAC



## Permanent Split Capacitor, 5.0" Diameter, Stud or Hub Ring Mount (2.5")

HP	RPM/Spds.	Volts	Catalog Number	List Price	Bearings	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Stud YM	Ship Wgt.	Notes
1/10	1625/3	115	8956	\$98	Slv	5.0	1.2	5.3	4.8	4.3	10.7	.75	9	
1/8	1075/3	115	8950	\$93	Slv	5.0	-	4.0	4.4	3.9	8.9	.75	9	
1/6	1075	115	6479	\$78	Slv	4.0	2.8	4.1	-	3.8	7.9	N/A	-	3
1/5	1075/3	115	8951	\$99	Slv	5.0	2.7	4.0	5.3	4.8	9.9	.75	11	
	1075/3	203-230	8952	\$100	Slv	5.0	1.6	4.0	5.3	4.9	9.9	N/A	11	
	1075/4	115	1268	\$100	Slv	4.0	3.5	3.5	4.6	4.1	8.7	1	10	2
1/4	1050	115	6480	\$83	Slv	7.5	4.0	5.0	-	4.1	9.1	N/A	-	3
	1050/3	115	1390	\$94	Slv	7.5	2.8	4.0	4.9	4.3	8.9	1	13	1
	1050/3	208-230	1391	\$95	Slv	7.5	1.5	4.0	4.9	4.3	8.9	1	13	1
1/3	1075/3	115	8955	\$101	Slv	15.0	3.8	4.0	5.1	-	10.2	.75	13	

Note 1 Hub Rings not included

Note 2 Class B Insulation

Note 3 Band Mounting